OUTPATIENT PHARMACY

TECHNICAL MANUAL/SECURITY GUIDE

Version 7.0
December 1997

(Revised September 2006)

Department of Veterans Affairs
VistA Health Systems Design & Development

Revision History

Each time this manual is updated, the Title Page lists the new revised date and this page describes the changes. If the Revised Pages column lists "All," replace the existing manual with the reissued manual. If the Revised Pages column lists individual entries (e.g., 25, 32), either update the existing manual with the Change Pages Document or print the entire new manual.

Date	Revised Pages	Patch Number	Description
09/06	i-iii, 35	PSO*7*222	Updated the read access code of the PRESCRIPTION REFILL REQUEST file (#52.43) from "@" (programmer access) to "Pp" (Pharmacy package) access. (E. Williamson, PM; E. Phelps, Tech Writer)
04/06	13-14 40-43	PSO*7*148	Updated the Routine List with routines PSOBPSU1, PSOBPSUT, PSODAWUT, PSOHLDA, PSONDCUT, PSOORED7, PSOREJP0, PSOREJP1, PSOREJP2, PSOREJU1, PSOREJUT, PSOREJU2. Updated menu listing with new ePharmacy menu options. (S. Spence, PM; S. Krakosky, Tech. Writer)
03/06	90-91, 96, 101, 103	PSO*7*235	VistA Data Extraction Framework (VDEF) – Modified the explanation of the Trigger Events for the VDEF Message in Appendix D. Also updated the tables in Appendix D to include the Parent Institution. (H. Whitley, PM; L Woodson, Tech. Writer)
02/06	iv, 3, 9, 43, 79-80, 105, 107	PSO*7*227	Removed references to Transitional Pharmacy Benefit (TPB); functionality inactivated with this patch. (E. Williamson, PM; S. Krakosky, Tech Writer)
12/05	13-14	PSO*7*207	Updated Routine List with routines PSOORRDI, PSOORRD2. (E. Williamson, PM; R Maxson and S. Krakosky, Tech. Writers)
11/05	3, 13, 14	PSO*7*213	Encapsulation II project – Added a reference to the Pharmacy Re-Engineering (PRE) Application Program Interface (API) Manual. Updated the Routine List with the PSO5241, PSO525AP, PSO5252, PSO5291, PSO52API, PSO52AP1, PSO53, and PSO59 routines. (H. Whitley, PM; L Woodson, Tech. Writer)
11/05	90-91 96,100,103	PSO*7*220	Updated the tables in appendix D to add the NCPDP number from the OUTPATIENT SITE file (#59) to the Outpatient Pharmacy VDEF message that sends prescription information to the HDR. (E. Williamson, PM; R Maxson and S. Krakosky, Tech. Writers)
11/05	13-14	PSO*7*216	Updated Routine List with routine PSONCPDP. (E. Williamson, PM; R Maxson and S. Krakosky, Tech. Writers)

Date	Revised Pages	Patch Number	Description
08/05	13-15, 27	PSO*7*143	Updated the Routine List with routine PSOHDR, PSODIAG, PSOHLNE3, PSOHLSN2, PSOMLLD2, PSORN52D. Removed PSOICDA. Updated Exported Options to include the PROVIDER key. Updated External Relations to include NOTE referring to CPRS v25. (J. Podolec, PM; B. Manies and S. Krakosky, Tech. Writers)
08/05	3, 13-14	PSO*7*204	Under Related Manuals, removed revision date after User Manual. Added PSOMHV1 to the Routine List. (E. Williamson, PM; R Maxson, Tech.Writer)
08/05	iii, iv, 14, 57, 58, 90 - 108	PSO*7*205	VistA Data Extraction Framework (VDEF) project. (Re-formatted VistA within the document to adhere to new standards.) Added PSOVDF3 to the routine list. Added VHA and VUID to Glossary. Updated VDEF message example and the message details to include VUIDs when available. Regenerated the Table of Contents and Index. (H. Whitley, PM; L. Woodson, Tech. Writer)
03/05	3, 13, 14, 40-42, 48-54 54-56, 71	PSO*7*161	Laser Labels Phase II project. Updated the Routine list with two new routines. Added *Manual Print of Multi-Rx Forms* option and *Signature Log Reprint* option to the Outpatient Pharmacy Manager and Pharmacist menus. Added the routines to run in updating the control codes for the laser label printers. (H. Whitley, PM; L. Woodson, Tech. Writer) Added ScripTalk® printer terminal type and device type examples for cache sites. Added one order per message in Appendix B.
12/04	iv, 3, 14, 57, 89-102, 103-106	PSO*7*190	VistA Data Extraction Framework (VDEF) project. Added VDEF reference, routines and added Appendix D with HL7-specific information. Updated Table of Contents, Glossary and Index.
10/04	13, 19-26, 59-70, 70a-d	PSO*7*156	Automation Interface project. Updated the Routine list with eight new routines. Updated the “External Interfaces” section. Updated Appendix A to include new HL7 profile information.
06/04	3, 13, 14, 39, 45, 57, 73-75	PSO*7*132	Herbal /OTC project. Updated the Routine list with three new routines. Added a new report *Non-VA Meds Usage Report* option. Updated the Journaling Globals. Added the definition of Non-VA meds to the Glossary. Added the ZRN segment to the HL7 Order Message Segment Definition table and Discontinue Order Message.
05/04	13-14	PSO*7*157	Updated section 5. Routine List with routine PSORN52A.
11/03	iii - iv, 13, 40, 50, 54-55, 89-91	PSO*7*135	Updated Routine list for ScripTalk routines. Updated *the Outpatient Pharmacy Manager* option to include *the ScripTalk Main Menu* option. Added printer set-up. Included the new Table of Contents and Index. A correction to the Return Mail Initialization (RMI) control code in the TERMINAL TYPE file (#3.2) has been added.
11/03	79, 84-87	PSO*7*153	Added MailMan messages to the TPB HL7 extract information.

Date	Revised Pages	Patch Number	Description
11/03	62, 64, 66, 69	PSO*7*139	Updated Appendix A HL7 specific example and ZAL segment.
11/03	All		Re-numbered pages; removed headers.

(This page included for two-sided copying.)

Table of Contents

1. Introduction 1

2. Orientation 3
2.1. Online Documentation 3
2.2. Related Manuals 3

3. Implementation and Maintenance 5
3.1. Resource Requirements 5
3.2. Options to be Deleted during Installation 6
3.3. Templates to be Deleted during Installation 7
3.4. Routines to be Deleted during Installation 7
3.5. M Audiofax (Telephone Refill Requests) 7
3.6. Setting up the Bingo Board Device 8
3.7. Mail Group Setup for the HL7 External Interface 8
3.8. Using the Maintenance Menu 8
3.9. Queue Background Jobs 9

4. Files 11
4.1. Outpatient Pharmacy Files 11

5. Routine List 13

6. Exported Options 15
6.1. Menu Assignments 15
6.2. Security Keys 15
6.3. Package Security 16

7. Archiving and Purging 17
7.1. Setting up the Archive Device 17

8. Callable Routines 19

9. External Interfaces 19

10. External Relations 27
10.1. Data Base Integration Agreements (IAs) 27

11. Internal Relations 29

12. Package-Wide Variables 29

13. Templates 31

14. Software Product Security 33
14.1. Mail Group Setup for the HL7 External Interface 33
14.2. Archiving/Purging 33
14.3. Interfacing 33
14.4. Electronic Signatures 33
14.5. Menu Assignments 33
14.6. Security Keys 34

14.7. File Security 35

15. Outpatient Pharmacy V. 7.0 Menu Diagrams 37
15.1. Outpatient Pharmacy Manager 37
15.2. Pharmacist Menu 41
15.3. Pharmacy Technician's Menu 42
15.4. Standalone Options 43

16. Routine Mapping 45

17. Journaling Globals 45

18. Barcodes and Label Printer Support 45
18.1. Barcodes on Dot Matrix Printers 45
18.2. New Label Stock (Version 6.0 and Later Versions) – Dot Matrix Labels 46
18.3. Laser Label Printers 48
18.4. ScripTalk® Printers 54

Glossary 57

Appendix A: Outpatient Pharmacy HL7 Interface Specifications 59

Appendix B: HL7 Messaging with an External System 71

Appendix C: HL7 Messaging for Transitional Pharmacy Benefit Extract 79

Appendix D: HL7 Messaging for VistA Data Extraction Framework (VDEF) 89

Index 105

1. Introduction

This document briefly describes the technical and security aspects of Outpatient Pharmacy V. 7.0. It is intended for members of the Automated Data Processing (ADP)/Information Resources Management Service (IRMS) staff who have had experience with other Veterans Health Information Systems and Technology Architecture (VistA) software and have worked or will work with a package coordinator who is familiar with the functions of the Outpatient Pharmacy V. 7.0 in a VA Medical Center. Readers without this background are referred to the documentation for the Kernel, the VA FileMan and the User's Manual for this release.

The Outpatient Pharmacy V. 7.0 package provides a method for managing the medications given to veterans who have visited a clinic or who have received prescriptions upon discharge from the hospital. Prescription labels are automatically generated and refill request forms are printed. Medication histories are kept online to permit checks for potential interactions. Profiles can be generated to assist the clinician in managing the patient's medication regimen. Management reports aid the pharmacy in controlling inventory and costs.

A number of site parameters allow the individual Department of Veterans Affairs Medical Center (VAMC) to customize the package to meet local needs. The User's Manual describes these site parameters and the ways they influence the operation of the package.

See Section 10 of this manual, "External Relations," for a listing of software not included in this package that must be installed before this version of Outpatient Pharmacy is fully functional.

(This page included for two-sided copying.)

2. Orientation

2.1. Online Documentation

Throughout the entire Outpatient Pharmacy V. 7.0 package, enter a question mark (?) to obtain online information to assist in choosing actions at any prompt. Where examples of screen dialogs are given, user responses are shown as bolded text.

Additional information about this package is contained in help prompts and comments which are available online. Detailed information can also be obtained by using the Kernel routine XINDEX to produce detailed listings of the routines and by using the VA FileMan to generate listings of data dictionaries for the files.

The Data Dictionaries (DDs) are considered part of the online documentation for this software application. Use VA FileMan *List File Attributes* [DILIST] option, under the *Data Dictionary Utilities* [DI DDU] option, to print the DDs.

2.2. Related Manuals

Outpatient Pharmacy V. 7.0 Release Notes
Outpatient Pharmacy V. 7.0 User Manual
Computerized Patient Record System V. 1.0 Installation Guide
Computerized Patient Record System V. 1.0 Set-up Guide
Pharmacy Ordering Enhancements (POE) Phase 2 Release Notes
Outpatient Medication Copay Release Notes
Laser Printed Prescription Labels with PMI Sheets Phase I Release Notes
ScripTalk® Talking Prescription Labels Installation Guide
Herbal/OTC/Non-VA Meds Documentation Release Notes
VistA Data Extraction Framework (VDEF) Installation & User Configuration Guide
Pharmacy Re-Engineering (PRE) Application Program Interface (API) Manual

(This page included for two-sided copying.)

3. Implementation and Maintenance

3.1. Resource Requirements

Outpatient Pharmacy V. 7.0 contains approximately 404 routines including all PSO* routines and compiled templates, PSOX* and APSPT* that take up approximately 1.5MB disk space.

Response Time monitor hooks have been placed in the following routines:

Routine	Purpose
PSON52	File New Prescriptions in File #52
PSORN52	File Renewed Prescriptions in File #52
PSOR52	File Refill Prescriptions in File #52

This package requires 24 files (see "Files" section in this manual). A typical site may require the following disk space:

1 Mbyte	DRUG file (#50) (4000 entries)
3 Mbytes per month	DRUG COST file (#50.9) (800 items dispensed by 200 dispensing physicians)
150 Mbytes	PRESCRIPTION file (#52) (500,000 prescriptions)
50 Mbytes	PHARMACY PATIENT file (#55) (500,000 prescriptions)
About 1 to 2 Mbytes	Routines and the other files (except for RX VERIFY file (#52.4), RX SUSPENSE file (#52.5), and PHARMACY ARCHIVE file (#52.8))
3 to 5 Mbytes of "swing space"	RX VERIFY file (#52.4), RX SUSPENSE file (#52.5), and PHARMACY ARCHIVE file (#52.8)

Outpatient Pharmacy V. 7.0 may be expected to require about 350 Mbytes of disk space. The actual disk utilization will, of course, depend primarily on the size of the 3 large files—PRESCRIPTION file (#52), PHARMACY PATIENT file (#55) and DRUG COST file (#50.9).

The requirements for Video Display Terminals (VDTs) and printers also depend on the number of transactions Outpatient Pharmacy V. 7.0 performs. Approximately three VDTs and one printer are needed for each 500 prescriptions (or fraction of 500) issued each day. If mail-out refills are handled separately, at least one VDT and one printer for each 500 refills are required. An additional VDT and a printer may be desired in the supervisor's office, and

1 VDT in the office of people who are assigned to consult with patients about their medication regimens.

There are no special device requirements for dot matrix labels except to print barcodes on labels. In this case, the label printer must be able to print barcodes and must be able to be set to a form length of either 4 inches or 24 lines. The section in this document on barcodes provides additional information about this function.

Laser printed labels require one or more specially configured printers. The printer must be able to print to a legal length form and must print barcodes. In addition, the printer must support Hewlett Packard's Printer Control Language (PCL) version 5 or greater.

3.2. Options to be Deleted during Installation

NOTE: The options listed below are deleted on the initial installation of Outpatient Pharmacy V. 7.0. No options are deleted after the initial installation, up to patch PSO*7*46.

Option Name	Menu Text
PSO DRUG	Drug Enter/Edit
PSO DRUGMENU	Drug/Drug Interaction Functions
PSO HOLDRX	Hold Rx
PSO INTERACTION	Drug Interactions Menu
PSO INTERACTION LOCAL ADD	Enter/Edit Local Drug Interaction
PSO INTERACTION SEVERITY	Edit Drug Interaction Severity
PSO LAB MONITOR	Mark/Unmark Lab Monitor Drugs
PSO NEW	New Prescription Entry
PSO REF	Refill Prescriptions
PSO RXEDIT	Edit Prescriptions
PSO RXHOLD	Hold Features
PSO RXPAR	Partial Prescription
PSO SIGED	Medication Instruction File Add/Edit
PSO UNHOLDRX	Unhold Rx
PSO FACILITY SETUP	Enter Facility Data for Clozapine
PSO MARK DRUG	Mark Clozapine Drug
PSOL UNMARK DRUG	Unmark Clozapine Drug
PSOARCCO	Find
PSOARCHLIST	List One Patient's Archived Rxs
PSOARCIN	Tape Retrieval
PSOARCPURGE	Purge
PSOARCSV	Save

3.3. Templates to be Deleted during Installation

NOTE: The templates listed below are deleted on the initial installation of Outpatient Pharmacy V. 7.0. No options are deleted after the initial installation up to patch PSO*7*46.

Input	**File**
PSO DRUG	#50
PSO SIGED	#51
PSO BATCH PARTIAL	#52
Print	**File**
PSO ACTION PROFILE #3	#44
PSOBJP	#52
Sort:	**File**
PSOBJP	#52

3.4. Routines to be Deleted during Installation

NOTE: The routines listed below are deleted on the initial installation of Outpatient Pharmacy V. 7.0. No options are deleted after the initial installation up to patch PSO*7*46.

PSOCLDRG	PSOCLUS1	PSOCLUS2	PSOCLUS3	PSOCSRL1
PSOCSTAR	PSODRUG	PSOGMINS	PSOGMP12	PSOGMP25
PSOLIST	PSONODIB	PSONUM	PSOPOST3	PSOPRE
PSORX	PSORXPAR			

Prior to the initial installation of Outpatient Pharmacy V. 7.0, it is recommended that all PSO* routines be deleted using the system utility to delete routines. Back up local modifications to any PSO* routines.

After installation of Outpatient Pharmacy V. 7.0, compare routines to note the changes between locally modified routines and the V. 7.0 routines. Take care when installing local modifications as Outpatient Pharmacy V. 7.0 has been modified greatly with patch PSO*7*46.

3.5. M Audiofax (Telephone Refill Requests)

If telephone refill requests are processed using M Audiofax, a new VEXRX routine must be installed to interface with Outpatient Pharmacy V. 7.0. To install this routine, go to SHOP ALL on FORUM and in the TELEPHONE REFILL REQUESTS Basket, retrieve the message “VEXRX for Outpatient V. 7.” This message will contain the new VEXRX routine. This routine must be forwarded and installed on the production account.

Important
Telephone refill requests (M Audiofax) cannot be processed without the new VEXRX routine.

3.6. Setting up the Bingo Board Device

A dedicated device must be set up for use with the bingo board. The device setup is similar to that used to set up a printer, except the sub-type will be C-VT. Only devices with the sub-type C-VT will be allowed for entry at the "DISPLAY DEVICE" prompt in the *Enter/Edit Display* [PSO BINGO ENTER/EDIT DISPLAY] option found on the *Bingo Board Manager* [PSO BINGO MANAGER] menu. For further information, see the site's systems guide for information on setting up the device. Once a dedicated device is set up, the bingo board can be scheduled to automatically start and/or stop at user-defined times.

3.7. Mail Group Setup for the HL7 External Interface

A mail group and device **must** be set up in order to run the HL7 external interface. The recommended name of the mail group is PSO HLGROUP1. The recommended device name is PSO HLDEVICE1.

3.8. Using the Maintenance Menu

The *Maintenance (Outpatient Pharmacy)* [PSO MAINTENANCE] menu is used for implementation as well as maintenance of the Outpatient Pharmacy V. 7.0 package. The first five options, *Site Parameter Enter/Edit* [PSO SITE PARAMETERS] (example follows), *Edit Provider* [PSO PROVIDER EDIT], *Add New Providers* [PSO PROVIDER ADD], *Queue Background Jobs* [PSO AUTOQUEUE JOBS], and *Autocancel Rx's on Admission* [PSO AUTOCANCEL1] are used for implementation. The remaining options on this menu may be used for maintenance. (An example is given below for the *Queue Background Jobs* [PSO AUTOQUEUE JOBS] option. See the Outpatient Pharmacy V. 7.0 User Manual for an explanation of the other options on this menu.)

Maintenance (Outpatient Pharmacy) [PSO MAINTENANCE] menu

Site Parameter Enter/Edit
Edit Provider
Add New Providers
Queue Background Jobs
Autocancel Rx's on Admission
Bingo Board Manager ...
Edit Data for a Patient in the Clozapine Program
Enter/Edit Clinic Sort Groups
Initialize Rx Cost Statistics
Edit Pharmacy Intervention
Delete Intervention
Auto-delete from Suspense
Delete a Prescription
Expire Prescriptions
Manual Auto Expire Rxs
Prescription Cost Update
Purge Drug Cost Data
Purge External Batches
Recompile AMIS Data

3.9. Queue Background Jobs [PSO AUTOQUEUE JOBS]

This option is used to queue all background jobs. Once the *Queue Background Jobs* [PSO AUTOQUEUE JOBS] option is selected, the option automatically pre-selects the jobs. Entering "E" for exit will not exit the option. An up arrow (^) must be entered to exit a specific job and go on to the next one. The background jobs are as follows:

- Autocancel Rx's on Admission
- Nightly Rx Cost Compile
- Nightly Management Data Compile
- Compile AMIS Data (NIGHT JOB)
- Expire Prescriptions
- Auto-delete from Suspense

A date and time at least 2 minutes in the future must be entered. The jobs should be set to run at a time convenient for the site.

NOTE: The options listed above must be scheduled to run through the *Queue Background Jobs* [PSO AUTOQUEUE JOBS] option. Attempting to run them from any other option will cause problems.

Only the following prompts require responses. All others will be left blank.

QUEUED TO RUN AT WHAT TIME:	This is the date/time desired for TaskMan to start this option.
RESCHEDULING FREQUENCY:	If this field is blank then the job will run only once.

Example: View of Queue Background Jobs Screen

```
Select Maintenance (Outpatient Pharmacy) Option: QUEue Background Jobs

If time to run option is current do not edit.
Autocancel System Parameter must be set to 'YES'
before prescriptions are discontinued.
```

```
Edit Option Schedule
    Option Name: PSO AUTOCANCEL
    Menu Text: Autocancel on Admission                    TASK ID: 2617405
  ____________________________________________________________________________

  QUEUED TO RUN AT WHAT TIME: JUN 13,2000@01:00

DEVICE FOR QUEUED JOB OUTPUT: PP6;P-OTHER;132;64

 QUEUED TO RUN ON VOLUME SET:

      RESCHEDULING FREQUENCY: 1D

             TASK PARAMETERS:

            SPECIAL QUEUEING:
____________________________________________________________________________
COMMAND:                                     Press <PF1>H for help    Insert
```

These default values are highlighted on the screen display, not to indicate user input.

4. Files

This package requires the 24 files listed below. Information about the files can be obtained by using the VA FileMan to generate a list of file attributes.

The Data Dictionaries (DDs) are considered part of the online documentation for this software application. Use the VA FileMan *List File Attributes* [DILIST] option, under the *Data Dictionary Utilities* [DI DDU] option, to print the DDs. The following are the files for which DDs should be printed:

4.1. Outpatient Pharmacy Files

FILE #	NAME	UP DATE DD	SEND SEC. CODE	DATA COMES W/FILE	SITE DATA	RSLV PTS	USER OVER RIDE
50.073	DUE QUESTIONNAIRE	YES	YES	NO			
50.0731	DUE ANSWER SHEET	YES	YES	NO			
50.0732	DUE QUESTION	YES	YES	NO			
50.0733	DUE SECTION	YES	YES	NO			
50.9	DRUG COST	YES	YES	NO			
52	PRESCRIPTION	YES	YES	NO			
52.11	PATIENT NOTIFICATION (Rx READY)	YES	YES	NO			
52.4	RX VERIFY	YES	YES	NO			
52.41	PENDING OUTPATIENT ORDERS	YES	YES	NO			
52.43	PRESCRIPTION REFILL REQUEST	YES	YES	NO			
52.5	RX SUSPENSE	YES	YES	NO			
52.51	PHARMACY EXTERNAL INTERFACE	YES	NO	NO			
52.52	CLOZAPINE PRESCRIPTION OVERRIDES	YES	YES	NO			
52.8	PHARMACY ARCHIVE	YES	YES	NO			
52.9	PHARMACY PRINTED QUEUE	YES	YES	NO			
52.91	TPB ELIGIBILITY	YES	NO	NO			
52.92	TPB INSTITUTION LETTERS	YES	YES	NO			
53	RX PATIENT STATUS	YES	YES	NO			
59	OUTPATIENT SITE	YES	YES	NO			
59.1	OUTPATIENT AMIS DATA	YES	YES	NO			

FILE #	NAME	UP DATE DD	SEND SEC. CODE	DATA COMES W/FILE	SITE DATA	RSLV PTS	USER OVER RIDE
59.12	OUTPATIENT PHARMACY MANAGEMENT DATA	YES	YES	NO			
59.2	WAITING TIME	YES	YES	NO			
59.3	GROUP DISPLAY	YES	NO	NO			
59.8	OUTPATIENT CLINIC SORT GROUP	YES	YES	NO			

The namespace for the Outpatient Pharmacy V. 7.0 package is PSO.

5. Routine List

The following routine list for Outpatient Pharmacy appears when the new routine set is loaded. Each routine's first line contains a brief description of the routine's function. Use the *First Line Routine Print* [XU FIRST LINE PRINT] option to print a list of just the first line of each PSO* routine.

PSO146PS	PSO153PS	PSO5241	PSO525AP	PSO5252	PSO5291	PSO52API	PSO53
PSO55FX2	PSO55FX3	PSO59	PSOADDR	PSOAMIS	PSOAMIS0	PSOAMIS1	PSOARC
PSOARCCO	PSOARCCV	PSOARCDE	PSOARCF1	PSOARCF2	PSOARCF3	PSOARCF4	PSOARCF5
PSOARCF6	PSOARCIN	PSOARCLT	PSOARCR1	PSOARCR2	PSOARCRR	PSOARCS2	PSOARCSV
PSOARCTG	PSOARCTP	PSOARX	PSOARX1	PSOAUTOC	PSOB	PSOBARV	PSOBBC
PSOBGMG1	PSOBGMG2	PSOBGMG3	PSOBGMGR	PSOBING1	PSOBINGO	PSOBKDE1	PSOBKDED
PSOBMST	PSOBRPRT	PSOBPSU1	PSOBPSUT	PSOBSET	PSOBSET1	PSOBUILD	PSOCAN
PSOCAN1	PSOCAN2	PSOCAN3	PSOCAN4	PSOCLERK	PSOCLO1	PSOCLOLS	PSOCLPRE
PSOCLUTL	PSOCMOP	PSOCMOPA	PSOCMOPB	PSOCMOPC	PSOCMOPR	PSOCOPAY	PSOCOST
PSOCOSTP	PSOCP	PSOCP1	PSOCPA	PSOCPB	PSOCPBA2	PSOCPBAK	PSOCPC
PSOCPD	PSOCPDUP	PSOCPE	PSOCPIB	PSOCPTRH	PSOCPTRI	PSOCPVW	PSOCSRL
PSOCST	PSOCST10	PSOCST11	PSOCST12	PSOCST2	PSOCST3	PSOCST4	PSOCST5
PSOCST6	PSOCST7	PSOCST8	PSOCST9	PSOCSTD	PSOCSTM	PSOCSTX	PSODACT
PSODAWUT	PSODEA	PSODEDT	PSODELI	PSODEM	PSODGAL	PSODGDG1	PSODGDG2
PSODGDGI	PSODGNVI	PSODIAG	PSODIR	PSODIR1	PSODIR2	PSODIR3	PSODISP
PSODISP1	PSODISP2	PSODISP3	PSODISPS	PSODIV	PSODLKP	PSODP	PSODPT
PSODRDU1	PSODRDU2	PSODRDUP	PSODRG	PSODSPL	PSODSRC	PSODUE	PSOELPST
PSOEXBCH	PSOEXDT	PSOEXREF	PSOEXRST	PSOFSIG	PSOFTDR	PSOFUNC	PSOHCPRS
PSOHCSUM	PSOHDR	PSOHELP	PSOHELP1	PSOHELP2	PSOHELP3	PSOHELP4	PSOHLD
PSOHLDA	PSOHLDC	PSOHLDIS	PSOHLDS	PSOHLDS1	PSOHLDS2	PSOHLDS3	PSOHLDS4
PSOHLEXC	PSOHLEXP	PSOHLINC	PSOHLINL	PSOHLNE1	PSOHLNE2	PSOHLNE3	PSOHLNEW
PSOHLPII	PSOHLPIS	PSOHLSG	PSOHLSG1	PSOHLSG2	PSOHLSG3	PSOHLSG4	PSOHLSG5
PSOHLSIG	PSOHLSIH	PSOHLSN	PSOHLSN1	PSOHLSN2	PSOHLSNC	PSOHLUP	PSOHLUP1
PSOLAB	PSOLBL	PSOLBL1	PSOLBL2	PSOLBL3	PSOLBL4	PSOLBLD	PSOLBLD1
PSOLBLN	PSOLBLN1	PSOLBLN2	PSOLBLS	PSOLBLT	PSOLLL1	PSOLLL2	PSOLLL3
PSOLLL4	PSOLLL5	PSOLLL6	PSOLLL7	PSOLLL8	PSOLLL9	PSOLLLH	PSOLLLI
PSOLLLW	PSOLLU1	PSOLLU2	PSOLLU3	PSOLLU4	PSOLMAL	PSOLMAO	PSOLMDA
PSOLMLST	PSOLMPAT	PSOLMPF	PSOLMPI	PSOLMPO	PSOLMPO1	PSOLMPO2	PSOLMRN
PSOLMUTL	PSOLSET	PSOMAUEX	PSOMGCM1	PSOMGCOM	PSOMGM31	PSOMGMN1	PSOMGMN2
PSOMGMN3	PSOMGMN4	PSOMGMRP	PSOMGR31	PSOMGREP	PSOMGRP1	PSOMGRP2	PSOMGRP3
PSOMGRP4	PSOMHV1	PSOMLLD2	PSOMLLDT	PSON52	PSONCPDP	PSONDCUT	PSONEW
PSONEW1	PSONEW2	PSONEW3	PSONEWF	PSONEWG	PSONFI	PSONGR	PSONRXN
PSONTEG	PSONVAR1	PSONVARP	PSONVNEW	PSOORAL	PSOORAL1	PSOORAL2	PSOORAPI
PSOORCPY	PSONTEG0	PSOORDA	PSOORDER	PSOORDRG	PSOORED1	PSOORED2	PSOORED3
PSOORED4	PSOORED5	PSOORED6	PSOORED7	PSOOREDT	PSOORFI1	PSOORFI2	PSOORFI3
PSOORFI4	PSOORFIN	PSOORNE1	PSOORNE2	PSOORNE3	PSOORNE4	PSOORNE5	PSOORNE6
PSOORNEW	PSOORNW1	PSOORNW2	PSOORRDI	PSOORRD2	PSOORRL	PSOORRL1	PSOORRNW
PSOORUT1	PSOORUT2	PSOORUT3	PSOORUTL	PSOP	PSOP1	PSOP2	PSOPAT
PSOPKIV1	PSOPOLY	PSOPOST	PSOPOST1	PSOPOST2	PSOPOST3	PSOPOST4	PSOPOST5
PSOPOST6	PSOPOST7	PSOPOST8	PSOPRA	PSOPRF	PSOPRFSS	PSOPRI	PSOPRVW
PSOPST68	PSOPTPST	PSOR52	PSORDS	PSOREF	PSOREF0	PSOREF1	PSOREF2
PSOREJP0	PSOREJP1	PSOREJP2	PSOREJU1	PSOREJUT	PSOREJU2	PSORELD1	PSORELDT
PSORENW	PSORENW0	PSORENW1	PSORENW2	PSORENW3	PSORENW4	PSORESK	PSORESK1
PSORFL	PSORN52	PSORN52A	PSORN52C	PSORN52D	PSORPTS	PSORPTS1	PSORX1
PSORXCLE	PSORXDL	PSORXED	PSORXED1	PSORXEDT	PSORXI	PSORXL	PSORXL1
PSORXLAB	PSORXPA1	PSORXPR	PSORXPR1	PSORXRP1	PSORXRP2	PSORXRPT	PSORXVW

PSORXVW1	PSORXVW2	PSOSD	PSOSD0	PSOSD1	PSOSD2	PSOSD3	PSOSDP
PSOSIG	PSOSIGCX	PSOSIGDS	PSOSIGMX	PSOSIGNO	PSOSIGTX	PSOSITED	PSOSPSIG
PSOSTART	PSOSUBCH	PSOSUCH1	PSOSUCHG	PSOSUCLE	PSOSUDCN	PSOSUDEL	PSOSUDP1
PSOSUDP2	PSOSUDPR	PSOSUINV	PSOSULB1	PSOSULBL	PSOSULOG	PSOSUP	PSOSUPAT
PSOSUPOE	PSOSUPRX	PSOSURST	PSOSUSRP	PSOSUTL	PSOSUTL1	PSOTALK	PSOTALK1
PSOTALK2	PSOTALK3	PSOTPCAN	PSOTPCEE	PSOTPCL	PSOTPCLP	PSOTPCLR	PSOTPCLW
PSOTPCRP	PSOTPCRX	PSOTPCUL	PSOTPENV	PSOTPHL1	PSOTPHL2	PSOTPPOS	PSOTPPRE
PSOTPPRV	PSOTPRX1	PSOTRLBL	PSOUTIL	PSOUTL	PSOUTLA	PSOUTLA1	PSOVCNT
PSOVDF1	PSOVDF2	PSOVDF3	PSOVDFK	PSOVER	PSOVER1	PSOVER2	PSOVERC
PSOVRPT	PSOVWI						

6. Exported Options

6.1. Menu Assignments

Unless menus have already been assigned, the *Outpatient Pharmacy Manager* [PSO MANAGER] menu should be assigned to the Package Coordinator for Outpatient Pharmacy. It should also be added to the menu of the Site Manager and any ADP/IRMS staff that the Package Coordinator selects to help in the operation of Outpatient Pharmacy. The *Pharmacist Menu* [PSO USER1] option should be assigned to all pharmacists and the *Pharmacy Technician's Menu* [PSO USER2] option should be assigned to all pharmacy technicians and other pharmacy personnel who may view prescriptions and/or inquire into other Outpatient Pharmacy V. 7.0 files.

6.2. Security Keys

PROVIDER	Holders of this key will be prompted for ICD-9 Diagnosis code entry.
PSORPH	This key is required to use all of the Outpatient Pharmacy V. 7.0 options. It should be assigned to all pharmacists, the package coordinator, and all appropriate members of the ADP/IRMS staff.
PSO COPAY	This key is used to identify users to notify when a copay exemption cannot be determined at the time a prescription fill is released. Holders of this key are also notified any time the *Exempt Rx Patient Status from Copayment* [PSOCP EXEMPTION] option is used to change the copay exemption for an Rx Patient Status.
PSOA PURGE	***NOTE**: Disabled until further notice.* This key should be assigned to the package coordinator and/or any person who will be responsible for archiving prescriptions.
PSOLOCKCLOZ	This key is used to override the lockouts in the Clozapine options. All members of the Clozapine treatment team must be entered as users on the system and must be given this key. All pharmacists who have the ability to override the lockouts in this option must also hold this key. The Pharmacy Service representative of the Clozapine treatment team should identify these pharmacists.
PSOINTERFACE	This key is used to access the *External Interface Menu* [PSO EXTERNAL INTERFACE] option.

6.3. Package Security

Electronic signatures may be established by using the *Electronic Signature code Edit* [XUSESIG] option.

In Kernel V. 8.0 the *Electronic Signature code Edit* [XUSESIG] option has been tied to the Common Options, under the *User's Toolbox* [XUSERTOOLS] submenu, for easy access by all users.

7. Archiving and Purging

Detailed information is kept for each prescription, including all information about the original prescription, all refills and all editing. An average prescription requires about 300 bytes (0.3 Kbytes) of disk storage. The archiving options under the manager's menu allow the package coordinator and IRMS/ADP staff to manage this file. Old prescriptions, typically those that have been expired or canceled for more than a year, can be saved to tape and then purged from online storage. NOTE: The purge options under the *Archive Menu* [PRCAK AR SUPERVISOR] option are out of order until further notice. The User's Manual describes the operation of these options. Because not all prescriptions require the same amount of space and because of the way the operating system utilizes the disk, do not expect to regain 300 bytes of disk storage for every prescription purged. As prescriptions are purged, all references to these prescriptions from other files are also deleted.

The RX SUSPENSE file (#52.5) holds information about all prescriptions that have been suspended for later printing. There is an automatic purge for this file for prescriptions printed from 7 to 90 days ago. The package coordinator can run the *Auto-delete from Suspense* [PSO PNDEL] option at regular intervals to purge this file of suspended prescriptions which have been printed 7 to 90 days ago. The purging is tasked to run every 7 days.

Specific entries can be deleted using the *Change Suspense Date* [PSO PNDCHG] or *Pull Early From Suspense* [PSO PNDRX] options.

Drug cost data can now be purged using the *Purge Drug Cost Data* [PSO PURGE DRUG COST] option.

7.1. Setting up the Archive Device

The following examples display archive device setups for file and tape.

These examples may differ from site to site. If a device differs, check with IRMS for information on device set up.

```
                    HOST FILE SERVER (HFS) DEVICE SETUP:


NAME: HFS      $I: ARC0797.TMP
ASK DEVICE: YES      ASK PARAMETERS: NO
VOLUME SET(CPU): VAA QUEUING: ALLOWED
LOCATION OF TERMINAL: COMPUTER AREA   ASK HOST FILE: YES
ASK HFS I/O OPERATION: YES *MARGIN WIDTH: 132
*FORM FEED: #  *PAGE LENGTH: 64
*BACK SPACE: $C(8)   SUBTYPE: P-OTHER
TYPE: HOST FILE SERVER
BAUD RATE (c): UNKNOWN
```

```
                        MAGNETIC TAPE DEVICE SETUP:


NAME: TAPE (T7867)  $I: $3$MKA600:
ASK DEVICE: YES     ASK PARAMETERS: YES
SIGN-ON/SYSTEM DEVICE: NO
LOCATION OF TERMINAL: COMPUTER ROOM
*MARGIN WIDTH: 255  *FORM FEED: #
*PAGE LENGTH: 256   *BACK SPACE: $C(8)
OPEN PARAMETERS: (FORMAT="VAL4":BLOCKSIZE=2048)
SUBTYPE: MAGTAPE    TYPE: MAGTAPE
PERFORM DEVICE CHECKING: NO
BAUD RATE (c): UNKNOWN
```

8. Callable Routines

Entry points provided by the Outpatient Pharmacy V. 7.0 package to other packages can be found in the External Relations section of this manual. No other routines are designated as callable from outside of this package.

9. External Interfaces

For up to date information on maintaining the HL7 External Interface, go to the following web site:

http://www.va.gov/vdl/Infrastructure.asp?appID=8

The VDL stores documents related to HL7 development and installation. For more information about HL7, go to this web site:

http://vista.med.va.gov/messaging/hl7dev/index.asp

NOTE: The HL Logical Link Entry/Node set up for Outpatient Pharmacy V. 7.0 is PSO DISP. This is a new Logical Link installed with Patch PSO*7*156.

Steps for Startup/Shutdown of the External Interface

The following screens depict the steps necessary to startup and shutdown the external interface for Version 1.6 of the VistA Health Level Seven (HL7) application package. See Appendix A of this manual for more information on the Outpatient Pharmacy V. 7.0 HL7 Specification.

The following examples are options from the HL7 package. The top-level menu option being used is the HL MAIN MENU [*HL7 Main Menu*] option.

Example: Starting Up the Interface

```
Select OPTION NAME: HL MAIN MENU       HL7 Main Menu


          Event monitoring menu ...
          Systems Link Monitor
          Filer and Link Management Options ...
          Message Management Options ...
          Interface Developer Options ...
          Site Parameter Edit

Select HL7 Main Menu Option: FILer and Link Management Options


   SM     Systems Link Monitor
   FM     Monitor, Start, Stop Filers
   LM     TCP Link Manager Start/Stop
   SA     Stop All Messaging Background Processes
   RA     Restart/Start All Links and Filers
   DF     Default Filers Startup
   SL     Start/Stop Links
   PI     Ping (TCP Only)
   ED     Link Edit
   ER     Link Errors ...

Select Filer and Link Management Options Option: SL  Start/Stop Links

This option is used to launch the lower level protocol for the
appropriate device.  Please select the node with which you want
to communicate

Select HL LOGICAL LINK NODE: PSO DISP
The LLP was last shutdown on MAY 11, 2004 07:29:53.
This LLP has been enabled!
```

Page 21 referred to options that are no longer used in the HL7 package, and has been removed from this document.

Example: Shutting Down the Interface

```
Select OPTION NAME: HL MAIN MENU       HL7 Main Menu


          Event monitoring menu ...
          Systems Link Monitor
          Filer and Link Management Options ...
          Message Management Options ...
          Interface Developer Options ...
          Site Parameter Edit

Select HL7 Main Menu Option: FILer and Link Management Options


   SM     Systems Link Monitor
   FM     Monitor, Start, Stop Filers
   LM     TCP Link Manager Start/Stop
   SA     Stop All Messaging Background Processes
   RA     Restart/Start All Links and Filers
   DF     Default Filers Startup
   SL     Start/Stop Links
   PI     Ping (TCP Only)
   ED     Link Edit
   ER     Link Errors ...

Select Filer and Link Management Options Option: SL  Start/Stop Links

This option is used to launch the lower level protocol for the
appropriate device.  Please select the node with which you want
to communicate

Select HL LOGICAL LINK NODE: PSO DISP
The LLP was last started on JUN 02, 2004 09:52:02.

Okay to shut down this job? YES
The job for the PSO DISP Lower Level Protocol will be shut down.
```

Pages 23-26 referred to processes that are no longer used and have been removed from this document.

Pages 23-26 referred to processes that are no longer used and have been removed from this document.

10. External Relations

The following software is not included in this package and must be installed before this version of Outpatient Pharmacy is completely functional.

Package	Minimum Version Needed
Accounts Receivable (AR)	4.5
Adverse Reaction Tracking (ART)	4.0
Clinical Information Resources Network (CIRN)	1.0
Consolidated Mail Outpatient Pharmacy (CMOP)	2.0
Computerized Patient Record System (CPRS)	3.0
Decision Support System (DSS)	3.0
Fee Basis	3.5
VA FileMan	22.0
Integrated Funds Control, Accounting, and Procurement (IFCAP)	5.0
Inpatient Medications (IP)	5.0
Integrated Billing (IB)	2.0
Kernel	8.0
Laboratory	5.2
MailMan	7.1
Master Patient Index/Patient Demographics (MPI/PD)	1.0
National Drug File (NDF)	4.0
Order Entry/Results Reporting (OERR)	3.0
Patient Information Management System (PIMS)	5.3
Pharmacy Data Management (PDM)	1.0
Remote Procedure Call (RPC) Broker	1.1

NOTE: For Outpatient Medication Copay options to be fully functional, the Pharmacy Ordering Enhancement (POE) project software must be installed, which includes patches to Outpatient Pharmacy (PSO*7*46), Order Entry/Results Reporting (OR*3*94), Pharmacy Data Management (PSS*1*38), and Inpatient Medications (PSJ*5*50).

NOTE: For Clinical Indicator Data Capture (CIDC) to be fully functional, the Outpatient Pharmacy CIDC software (PSO*7*143) must be installed along with CPRS Version 25.

10.1. Data Base Integration Agreements (IAs)

Outpatient Pharmacy V. 7.0 has Data Base Integration Agreements (IAs) with the packages listed above, in addition to the following: Consolidated Mail Outpatient Pharmacy (CMOP), Drug Accountability (DA), and Controlled Substances (CS). For complete information regarding the IAs for Outpatient Pharmacy V. 7.0, please refer to the *Integration Agreement Menu* [DBA IA ISC] option under the *DBA* [DBA] option on FORUM.

(This page included for two-sided copying.)

11. Internal Relations

Very few of the options in this package can be invoked independently. Those that can be so invoked independently are

PSO MANAGER	Outpatient Pharmacy Manager
PSO P	Medication Profile
PSO USER1	Pharmacist Menu
PSO USER2	Pharmacy Technician's Menu
Any other option may not run independently.	

Any locally created menu which includes options from this package *must* have the ENTRY ACTION field read: D:'$D(PSOPAR) ^PSOLSET and should have the MENU EXIT ACTION field read: D FINAL^PSOLSET

12. Package-Wide Variables

The variables PSODIV, PSOINST, PSOIOS, PSOPAR, PSOPAR7, PSOSYS, PSOLAP, PSOPROP, PSOCLC, PSOCNT, PSODTCUT, PSOSITE, PSOPRPAS, PSOBAR0, PSOBAR1 and PSOBARS are used extensively throughout the package. They are set by the routine PSOLSET and are not killed until exiting from the package.

(This page included for two-sided copying.)

13. Templates

Sort	File
PSO COST STAT	50.9
PSO BBWAIT SORT	52.11
PSO DRUG LIST	50
PSO HOLD LIST	52
PSO INTERVENTIONS	9009032.4
PSO NARC LIST	52
PSOUPAT	52
Input	**File**
PSO CLOZDRUG	50
PSO DISPLAY EDIT	59.3
PSO INTERACT	56
PSO INTERVENTION EDIT	9009032.4
PSO INTERVENTION NEW	9009032.4
PSO OUTPT	2
PSO OUTPTA	2
PSO PARTIAL	52
PSO SITE	59
PSOD DUE BUILD QUESTIONNAIRE	50.073
PSOD DUE EDIT	50.0731
Print	**File**
PSO ACTION PROFILE	44
PSO ACTION PROFILE #2	44
PSO ALPHA DRUG LIST	50
PSO BBWAIT PRINT	52.11
PSO COST STAT	50.9
PSO DRUG LIST	50
PSO HOLD	52
PSO INACTIVE DRUG LIST	50
PSO INTERVENTIONS	9009032.4
PSO N/F LIST	50
PSO NARC LIST	52
PSO PHARMACY STATS	50.9
PSO REQUEST STATISTICS	50.9
PSO SUSPENSE LIST	52.5
PSO SYNONYM LIST	50
PSOD PRINT ANSWER SHEET	50.0731

(This page included for two-sided copying.)

14. Software Product Security

14.1. Mail Group Setup for the HL7 External Interface

A mail group and device should be set up in order to run the HL7 external interface. The recommended name of the mail group is PSO HLGROUP1. The recommended device name is PSO HLDEVICE1.

14.2. Archiving/Purging

For archiving and purging information, see the section titled “Archiving and Purging” in this manual.

14.3. Interfacing

For interface information, see the section titled “External Interfaces” in this manual.

14.4. Electronic Signatures

Electronic signatures may be established by using the *Electronic Signature code Edit* [XUSESIG] option. In Kernel V. 8.0 the *Electronic Signature code Edit* [XUSESIG] option has been tied to the Common Options, under the *User’s Toolbox* [XUSERTOOLS] submenu, for easy access by all users.

14.5. Menu Assignments

The *Outpatient Pharmacy Manager* [PSO MANAGER] menu should be assigned to the Package Coordinator for Outpatient Pharmacy and also added to the menu of the Site Manager and any ADP/IRMS staff that s/he selects to help in the operation of Outpatient Pharmacy. The *Pharmacist Menu* [PSO USER1] option should be assigned to all pharmacists and the *Pharmacy Technician’s Menu* [PSO USER2] option should be assigned to all pharmacy technicians and other pharmacy personnel who may view prescriptions and/or inquire into other Outpatient Pharmacy files.

14.6. Security Keys

PSORPH	This key should be assigned to all pharmacists, the package coordinator, and all appropriate members of the ADP/IRMS staff.
PSO COPAY	This key should be assigned to any users who need to be notified when a copay exemption cannot be determined at the time a prescription fill is released. Holders of this key are also notified any time the *Exempt Rx Patient Status from Copayment* [PSOCP EXEMPTION] option is used to change the copay exemption for an Rx Patient Status.
PSOA PURGE	*NOTE: Disabled until further notice.* This key should be assigned to the package coordinator and/or any person who will be responsible for archiving prescriptions.
PSOLOCKCLOZ	This key is used to override the lockouts in the Clozapine option. All members of the Clozapine treatment team must be entered as users on the system and must be given this key. All pharmacists who have the ability to override the lockouts in this option must also hold this key. The Pharmacy Service representative of the Clozapine treatment team should identify these pharmacists.
PSOINTERFACE	This key is used to access the *External Interface Menu* [PSO EXTERNAL INTERFACE] option.

14.7. File Security

This package requires 24 files in addition to those of the Kernel and other files to which it points, for example the PATIENT file (#2). Information about all files, including these can be obtained by using the VA FileMan to generate a list of file attributes.

File Numbers	File Names	DD	RD	WR	DEL	LAYGO
50.073	DUE QUESTIONNAIRE					
50.0731	DUE ANSWER SHEET					
50.0732	DUE QUESTION					
50.0733	DUE SECTION					
50.9	DRUG COST					
52	PRESCRIPTION					
52.11	PATIENT NOTIFICATION (Rx READY)					
52.4	RX VERIFY	@	@	@	@	@
52.41	PENDING OUTPATIENT ORDERS			@		
52.43	PRESCRIPTION REFILL REQUEST	@	Pp	@	@	@
52.5	RX SUSPENSE				#	
52.51	PHARMACY EXTERNAL INTERFACE	@	@	@	@	@
52.52	CLOZAPINE PRESCRIPTION OVERRIDES	@	@	@	@	@
52.8	PHARMACY ARCHIVE					
52.9	PHARMACY PRINTED QUEUE					
52.91	TPB ELIGIBILITY	@				
52.92	TPB INSTITUTION LETTERS	@				
53	RX PATIENT STATUS					
59	OUTPATIENT SITE					
59.1	OUTPATIENT AMIS DATA	@		@	@	@
59.12	OUTPATIENT PHARMACY MANAGEMENT DATA	@		@	@	@
59.2	WAITING TIME	@	@	@	@	@
59.3	GROUP DISPLAY	@	@	@	@	@
59.8	OUTPATIENT CLINIC SORT GROUP					

Please refer to Chapter 28 of Kernel V. 8.0 Systems Manual concerning installation of security codes sections entitled “Sending Security Codes.”

(This page included for two-sided copying.)

15. Outpatient Pharmacy V. 7.0 Menu Diagrams

Three main menus are exported with the package. The *Outpatient Pharmacy Manager* [PSO MANAGER] menu should be assigned to supervisors, package coordinators, and members of the ADP/IRMS staff. Pharmacists should have the *Pharmacist Menu* [PSO USER1] option and clerks and technicians should have the *Pharmacy Technician's Menu* [PSO USER2] option.

15.1. Outpatient Pharmacy Manager

Archiving ...
- Find
- Save to Tape
- Tape Retrieval
- Archive to File
- File Retrieval
- Purge
- **> Out of order: Unavailable - Under Construction
- List One Patient's Archived Rx's
- Print Archived Prescriptions

Autocancel Rx's on Admission

Bingo Board ...
- BM Bingo Board Manager ...
  - Enter/Edit Display
  - Auto-Start Enter/Edit
  - Print Bingo Board Statistics
  - Print Bingo Board Wait Time
  - Purge Bingo Board Data
  - Start Bingo Board Display
  - Stop Bingo Board Display
- BU Bingo Board User ...
  - Enter New Patient
  - Display Patient's Name on Monitor
  - Remove Patient's Name from Monitor
  - Status of Patient's Order

Change Label Printer

Clozapine Pharmacy Manager
- Display Lab Tests and Results
- Edit Data for a Patient in the Clozapine Program
- List of Override Prescriptions
- Register Clozapine Patient

Copay Menu ...
- CHAMPUS Billing Exemption
- Exempt Rx Patient Status from Copayment

Reset Copay Status/Cancel Charges

DUE Supervisor ...
- 1 Enter a New Answer Sheet
- 2 Edit an Existing Answer Sheet
- 3 Create/Edit a Questionnaire
- 4 Batch Print Questionnaires
- 5 DUE Report

Enter/Edit Clinic Sort Groups

External Interface Menu …
- Purge External Batches
- Reprint External Batches
- View External Batches

Label/Profile Monitor Reprint

Maintenance (Outpatient Pharmacy) ...
- Site Parameter Enter/Edit
- Edit Provider
- Add New Providers
- Queue Background Jobs
- Autocancel Rx's on Admission
- Bingo Board Manager ...
  - Enter/Edit Display
  - Auto-Start Enter/Edit
  - Print Bingo Board Statistics
  - Print Bingo Board Wait Time
  - Purge Bingo Board Data
  - Start Bingo Board Display
  - Stop Bingo Board Display
- Edit Data for a Patient in the Clozapine Program
- Enter/Edit Clinic Sort Groups
- Initialize Rx Cost Statistics
- Edit Pharmacy Intervention
- Delete Intervention
- Auto-delete from Suspense
- Delete a Prescription
- Expire Prescriptions
- Manual Auto Expire Rxs
- Prescription Cost Update
- Purge Drug Cost Data
- Purge External Batches
- Recompile AMIS Data

Medication Profile

Output Reports ...
- Action Profile (132 COLUMN PRINTOUT)
- Alpha Drug List and Synonyms
- AMIS Report
- CMOP Controlled Substance Rxs Dispense Report
- Commonly Dispensed Drugs

- Cost Analysis Reports ...
  - Clinic Costs
  - Division Costs by Drug
  - Drug Costs
  - Drug Costs by Division
  - Drug Costs by Division by Provider
  - Drug Costs by Provider
  - High Cost Rx Report
  - Patient Status Costs
  - Pharmacy Cost Statistics Menu ...
    - Pharmacy Statistics
    - Sort Statistics By Division
  - Provider by Drug Costs
  - Provider Costs
  - Request Statistics
- Daily AMIS Report
- Drug List By Synonym
- Free Text Dosage Report
- Inactive Drug List
- List Prescriptions on Hold
- Management Reports Menu ...
  - Daily Management Report Menu ...
    - All Reports
    - Cost of Prescriptions
    - Count of Prescriptions
    - Intravenous Admixture
    - Type of Prescriptions Filled
  - Date Range Recompile Data
  - Initialize Daily Compile
  - Monthly Management Report Menu ...
    - All Reports
    - Cost of Prescriptions
    - Count of Prescriptions
    - Intravenous Admixture
    - Type of Prescriptions Filled
  - One Day Recompile Data
  - Purge Data
- Medication Profile
- Monthly Drug Cost
- Narcotic Prescription List
- Non-Formulary List
- Non-VA Meds Usage Report
- Poly Pharmacy Report
- Released and Unreleased Prescription Report

Pharmacy Intervention Menu ...
- Enter Pharmacy Intervention
- Edit Pharmacy Intervention
- Print Pharmacy Intervention
- Delete Intervention
- View Intervention

Process Drug/Drug Interactions
Release Medication
Return Medication to Stock
Rx (Prescriptions) ...
- Patient Prescription Processing
- Barcode Rx Menu ...
  - Barcode Batch Prescription Entry
  - Check Quality of Barcode
  - Process Internet Refills
- Complete Orders from OERR
- Discontinue Prescription(s)
- Edit Prescriptions
- ePharmacy Menu ...
  - Third Party Payer Rejects - View/Process
  - Third Party Payer Rejects - Worklist
- List One Patient's Archived Rx's
- Manual Print of Multi-Rx Forms
- Reprint an Outpatient Rx Label
- Signature Log Reprint
- View Prescriptions

ScripTalk Main Menu ...
- PT ScripTalk Patient Enter/Edit
- QBAR Queue ScripTalk Label by Barcode
- QRX Queue ScripTalk Label by Rx#
- RPT ScripTalk Reports ...
  - AUD ScripTalk Audit History Report
  - WHO Report of ScripTalk Enrollees
  - Reprint a non-voided Outpatient Rx Label
- PARM Set Up and Test ScripTalk Device ...
  - ScripTalk Device Definition Enter/Edit
  - Print Sample ScripTalk Label
  - Test ScripTalk Device
  - Reinitialize ScripTalk Printer

Supervisor Functions ...
- Add New Providers
- Daily Rx Cost
- Delete a Prescription
- Edit Provider
- Initialize Rx Cost Statistics
- Inter-Divisional Processing

Inventory
Lookup Clerk by Code
Monthly Rx Cost Compilation
Patient Address Changes Report
Pharmacist Enter/Edit
Purge Drug Cost Data
Recompile AMIS Data
Site Parameter Enter/Edit
View Provider

Suspense Functions ...
Auto-delete from Suspense
Change Suspense Date
Count of Suspended Rx's by Day
Delete Printed Rx's from Suspense
Log of Suspended Rx's by Day (this Division)
Print from Suspense File
Pull Early from Suspense
Reprint Batches from Suspense

Update Patient Record

Verification ...
List Non-Verified Scripts
Non-Verified Counts
Rx Verification by Clerk

15.2. Pharmacist Menu

Bingo Board User ...
Enter New Patient
Display Patient's Name on Monitor
Remove Patient's Name from Monitor
Status of Patient's Order

Change Label Printer

Change Suspense Date

DUE Supervisor ...
1 Enter a New Answer Sheet
2 Edit an Existing Answer Sheet
3 Create/Edit a Questionnaire
4 Batch Print Questionnaires
5 DUE Report

Enter/Edit Clinic Sort Groups

External Interface Menu …
Purge External Batches
Reprint External Batches
View External Batches

Medication Profile

Pharmacy Intervention Menu ...
- Enter Pharmacy Intervention
- Edit Pharmacy Intervention
- Print Pharmacy Intervention
- Delete Intervention
- View Intervention

Print from Suspense File
Process Drug/Drug Interactions
Pull Early from Suspense
Release Medication
Return Medication to Stock
Rx (Prescriptions) ...
- Patient Prescription Processing
- Barcode Rx Menu ...
  - Barcode Batch Prescription Entry
  - Check Quality of Barcode
  - Process Internet Refills
- Complete Orders from OERR
- Discontinue Prescription(s)
- Edit Prescriptions
- ePharmacy Menu ...
  - Third Party Payer Rejects - View/Process
  - Third Party Payer Rejects - Worklist
- List One Patient's Archived Rx's
- Manual Print of Multi-Rx Forms
- Reprint an Outpatient Rx Label
- Signature Log Reprint
- View Prescriptions

Update Patient Record
Verification ...
- List Non-Verified Scripts
- Non-Verified Counts
- Rx Verification by Clerk

15.3. Pharmacy Technician's Menu

Bingo Board User ...
- Enter New Patient
- Display Patient's Name on Monitor
- Remove Patient's Name from Monitor
- Status of Patient's Order

Change Label Printer

DUE User ...

1 Enter a New Answer Sheet
2 Edit an Existing Answer Sheet
3 Batch Print Questionnaires

Medication Profile
Patient Prescription Processing
Pull Early from Suspense
Release Medication
Update Patient Record

15.4. Standalone Options

The Transitional Pharmacy Benefit (TPB) options were available in previous releases of Outpatient Pharmacy V. 7.0, but are currently placed “Out of Order” by PSO*7*227.

(This page included for two-sided copying.)

16. Routine Mapping

No recommendations are made for routine mapping. However, to map the Outpatient Pharmacy V. 7.0 package routines, the system will need to be brought down and then restarted to load the new routines into memory.

17. Journaling Globals

The primary global the Outpatient Pharmacy V. 7.0 package uses is ^PSRX. This global is recommended if journaling is used. The majority of the other files used by the Outpatient Pharmacy package are stored in the ^PS global. This global is also recommended for journaling, if used.

18. Barcodes and Label Printer Support

This version of Outpatient Pharmacy includes the ability to print barcodes on the patient copy, the pharmacist's copy, and the patient narrative documents for new label stock and laser labels. Two options utilize the barcodes.

Check Quality of Barcode [PSO BARCODE CHECK] option is used to monitor the quality and readability of the barcode before it is mailed.

Barcode Batch Prescription Entry [PSO BATCH BARCODE] option is used to actually refill the prescriptions utilizing barcodes in a batch entry.

If barcodes are not used, enter an "OUT OF ORDER MESSAGE" for these two options.

18.1. Barcodes on Dot Matrix Printers

Three parameters are used.

X is the barcode height. Values can be "S", "M" or "L". If X is undefined or not equal to one of these, the default value of "S" is used. "S" is 2/10 inch for the DS-220 and 1/6 inch for the MT-290. "M" is 4/10 inch for the DS-200 and 1/3 inch for the MT-290. "L" is one inch for both.

X1 is the value of $X at the left edge of the barcode. If X1 is undefined, the default value of 0 is used.

X2 is the data to be bar coded. Remember the code 39 character set that the VA uses is a limited subset of the ASCII character set containing only the numbers, uppercase letters, and eight punctuation characters. In most cases, any other characters are not printed. For example, the barcode for the string 123abc will be the same as the string 123.

On most printers, printing a barcode is a graphics operation that causes the value of $Y to be something other than the line count from the top of the page. Forms with barcodes must use a form feed to go to the top of the next form rather than a counted number of line feeds. This is why printers used to print barcodes on outpatient pharmacy labels *must be set for a form length of 24 lines or four inches.*

The following section, New Label Stock, contains barcode on and off sequences for various printers.

18.2. New Label Stock (Version 6.0 and Later Versions) – Dot Matrix Labels

*****IMPORTANT*****

Please test new label stock on all printers that will be used before going into production with new label stock.

Printers used to print the new label stock must be set to print at 12 characters per inch. The form length must be set to 5 inches.

Previously, old label stock printed barcodes in one column at 10 characters per inch. New label stock prints barcodes at 12 characters per inch in 2 columns, (columns 54 and 102). The following barcode entries in the TERMINAL TYPE file (#3.2) have worked at either the Birmingham Office of Information Field Office (OIFO) or at a site.

NOTE: If you cannot find barcodes that work, please contact the nearest OIFO.

Check to see that a line feed is performed after the barcode off sequence is executed. Due to limited space, information must be printed after certain barcodes print, without relying on a line feed in the Outpatient Pharmacy code. To test this, print a test label for an Rx with no refills. On the center copy of the label, on the next line after the "station number-Rx no." which prints directly under the barcode, one of the two following lines should print clearly:

```
* NO REFILLS REMAINING ** PHYSICIAN USE ONLY *
```

or

```
*** This prescription CANNOT be renewed ***
```

If there is a problem, insert a line feed at the end of the Barcode Off sequence.
(Add a ,! to the end of the sequence.)

Remember to set the New Label Stock site parameter to Yes.

Three site parameters provide patient instructions that will print after each patient's prescriptions. They are "NARRATIVE NON-REFILLABLE RX", "NARRATIVE REFILLABLE RX", and "NARRATIVE FOR COPAY DOCUMENT". The "NARRATIVE FOR COPAY DOCUMENT" will only print if at least one of the patient's prescriptions is subject to a Copay charge.

For the Data South 220

BAR CODE ON=
*27,"[1w",*27,"$70s",*94,"H",$S('$D(X):"04",X="M":"04",X="S":"02",X="L":"10",1:
"04"),*94, "BDB"

BAR CODE OFF=*94,"G",*27,"$70c",*27,"[2w",!

For the MT-661

BAR CODE ON=
*27,"[<4h",*94,$S($X<60:"T450",1:"T850"),*94,"W9;5;1",*94,"B1;35;1;3",*13

BAR CODE OFF=*13,*10,*27,"[<4l",*27,"[5w"

The character after the [<4 in the BAR CODE OFF above is a lower case L.

For the Genicom 4440:

BAR CODE ON=*27,"[;3;1;;4;;4;;;1;}",*27,"[3t"

BAR CODE OFF=*27,"[0t",!

For the MT290:

BAR CODE ON=*26, "F0",$S(‘$D(X):2,X="M":2,X="S":1,X="L":6,1:2), ";000",*25,*20,"*"

BAR CODE OFF="*",*20,!,?$S($D(X1):X1,1:0),$S($D(X2):X2,1:"")

or

BAR CODE ON=*26,*34,"F3;000",*25,*20,"*"

BAR CODE OFF="*",*20

For the OTC 560:

BAR CODE ON=*27,"[;",$S('$D(X):3,X="M":6,X="L":12,1:3),"} ",*27,"[3t"

BAR CODE OFF=*27,"[0t"

For the Genicom 4490:

BAR CODE ON=*27,"[3t",*14

BAR CODE OFF=*15,*27,"[0t",*13

**The setup of the MT290 will not allow for a form length of 5 inches. It skips from 4 to 5.5. Following is the terminal type information that will allow the MT290 to print the labels at a form length of 5 inches.

```
NAME: P-MANNESMANN MT290/132 (PHAR)     RIGHT MARGIN: 132
  FORM FEED: #                          PAGE LENGTH: 30
  BACK SPACE: $C(8)
  OPEN EXECUTE: W *27,"[4W",*27,"[0Y",*27,"[30t"
  10 PITCH: $C(27)_"[4w"                12 PITCH: $C(27)_"[5w"
  DESCRIPTION: MANNESMANN TALLY 290/132 COLUMNS
  16 PITCH: $C(27)_"[6w"                DEFAULT PITCH: $C(27)_"[4w"
  BAR CODE OFF: "*",*20,!,?$S($D(X1):X1,1:0),$S($D(X2):X2,1:"")
  BAR CODE ON: *26,"F0",$S('$D(X):2,X="M":2,X="S":1,X="L":6,1:2),";000",
*25,*20,"*"
```

The *27,"[30t" was added to the Open Execute.

18.3. Laser Label Printers

The Outpatient Pharmacy package, with the release of PSO*7*120, supports the use of laser printers to print prescription labels and all associated documents.

18.3.1. Hardware Setup

The printer must be physically connected to the network and then defined in the DEVICE (#3.5) and TERMINAL TYPE (#3.2) files just as any other laser printer on your network is defined.

In addition, the CONTROL CODES field (#55) of the TERMINAL TYPE file (#3.2) must be defined correctly. To facilitate this, a new routine assists with the setup. At the programmer prompt enter: D ^PSOLLU2. You will be prompted for the device. Enter the device you want to use for printing laser labels. Then, you will be prompted for HP or LexMark. Enter the appropriate selection.

Phase I of Laser Labels introduced the routine PSOLLU2. A pre-release to Phase II introduced the PSOLLU3 routine and Phase II introduced the PSOLLU4 routine. (Instructions for running the PSOLLU3 and PSOLLU4 routines are the same as running the PSOLLU2 routine above.) If you are setting up a laser printer for the first time, run all three routines in order – PSOLLU2, PSOLLU3, and PSOLLU4. If you are already running laser labels, you will only need to run the PSOLLU4 routine to update the control codes.

NOTE: If you are not using either an HP or a LexMark printer, select one. Then, you may need to modify the control codes to work correctly with your printer.

NOTE: Since there are many options for the barcode chip your printer supports, you may have to modify the codes that control the barcode. The names of the codes are: BLBC, EBLBC, SBT and EBT. If you were already using this printer to print barcodes, you can use the information in the fields BAR CODE ON (#60) and BAR CODE OFF (#61) from the TERMINAL TYPE file (#3.2) as a guide. If you weren't, the barcode chip should have come with documentation showing the sequences necessary. If the documentation is not available, many printers have the ability to print the font set, with escape sequences, from the control panel of the printer.

Example Session:

```
>D ^PSOLLU2
DEVICE: HOME// FIDO  PRINTERS CORNER - LINE 000    Right Margin: 132//
HP or LexMark: L
You will be copying the CONTROL CODES to device: _LTA9053: are you sure?
Y Copying...
```

18.3.2. Sample Control Code Entries

The following are sample control code entries from one TERMINAL TYPE. Actual entries may vary depending on make and model of printer or barcode chip.

```
NUMBER: 1                                CTRL CODE ABBREVIATION: LLI
  FULL NAME: LASER LABEL INIT
  CONTROL CODE: W *27,"&r1F",*27,"E",*27,"&l0O",*27,"&u300D",*27,"&l3A",*27,"&l0
E",!
NUMBER: 2                                CTRL CODE ABBREVIATION: F10
  FULL NAME: TEN POINT FONT - NO BOLD
  CONTROL CODE: W *27,"(10U",*27,"(s1p10v0s0b16602X"
NUMBER: 3                                CTRL CODE ABBREVIATION: F8
  FULL NAME: EIGHT POINT FONT - NO BOLD
  CONTROL CODE: W *27,"(10U",*27,"(s1p8v0s0b16602X"
NUMBER: 4                                CTRL CODE ABBREVIATION: F12
  FULL NAME: TWELVE POINT FONT - NO BOLD
  CONTROL CODE: W *27,"(10U",*27,"(s1p12v0s0b16602X"
NUMBER: 5                                CTRL CODE ABBREVIATION: F9
  FULL NAME: NINE POINT FONT - NO BOLD
  CONTROL CODE: W *27,"(10U",*27,"(s1p9v0s0b16602X"
NUMBER: 6                                CTRL CODE ABBREVIATION: ST
  FULL NAME: START OF TEXT
  CONTROL CODE: S PSOY=PSOY+PSOYI W *27,"*p",PSOX,"x",PSOY,"Y"
NUMBER: 7                                CTRL CODE ABBREVIATION: CDII
  FULL NAME: CRITICAL DRUG INTERACTION INITIALIZATION
  CONTROL CODE: S PSOX=0,PSOY=1400,PSOYI=50,PSOFONT="F10"
NUMBER: 8                                CTRL CODE ABBREVIATION: PMII
  FULL NAME: PMI SECTION INITIALIZATION
  CONTROL CODE: S PSOX=0,PSOY=1350,PSOYI=50,PSOFONT="F10",PSOYM=3899
NUMBER: 12                               CTRL CODE ABBREVIATION: ACI
  FULL NAME: ADDRESS CHANGE INITIALIZATION
  CONTROL CODE: S PSOHFONT="F12",PSOX=1210,PSOY=700,PSOFY=1270
NUMBER: 13                               CTRL CODE ABBREVIATION: ALI
  FULL NAME: ALLERGY SECTION INITIALIZATION
  CONTROL CODE: S PSOFONT="F10",PSOX=0,PSOY=1350,PSOYI=50,PSOYM=2700
NUMBER: 14                               CTRL CODE ABBREVIATION: FWU
  FULL NAME: FONT WITH UNDERLINE         CONTROL CODE: W *27,"&d0D"
NUMBER: 15                               CTRL CODE ABBREVIATION: FDU
```

```
  FULL NAME: FONT DISABLE UNDERLINE     CONTROL CODE: W *27,"&d@"
NUMBER: 17                              CTRL CODE ABBREVIATION: SPI
  FULL NAME: SUSPENSE PRINT INITIALIZATION
  CONTROL CODE: S PSOFONT="F10",PSOX=1210,PSOY=1350,PSOYI=50,PSOCX=1775,PSOYM=27
00
NUMBER: 18                              CTRL CODE ABBREVIATION: WLI
  FULL NAME: WARNING LABEL INITIALIZATION
  CONTROL CODE: S PSOX=1050,PSOY=55
NUMBER: 19                              CTRL CODE ABBREVIATION: RNI
  FULL NAME: REFILL NARRATIVE INITIALIZATION
  CONTROL CODE: S PSOY=2860,PSOFONT="F10",PSOX=0,PSOYI=50,PSOYM=3950
NUMBER: 20                              CTRL CODE ABBREVIATION: CNI
  FULL NAME: COPAY NARRATIVE INITIALIZATION
  CONTROL CODE: S PSOY=2860,PSOX=1210,PSOYM=3950,PSOFONT="F10",PSOYI=50
NUMBER: 21                              CTRL CODE ABBREVIATION: PII
  FULL NAME: PATIENT INSTRUCTION INITIALIZATION
  CONTROL CODE: S PSOX=1210,PSOY=760,PSOFONT="F12"
NUMBER: 22                              CTRL CODE ABBREVIATION: RPI
  FULL NAME: REFILL PRINT INITIALIZATION
  CONTROL CODE: S PSOFONT="F10",PSOBYI=65,PSOTYI=50,PSOLX=0,PSORX=1210,PSOY=1350
,PSOYM=3650,PSOXI=90,PSOSYI=135
NUMBER: 23                              CTRL CODE ABBREVIATION: BLH
  FULL NAME: BOTTLE LABEL HEADER INITIALIZATION
  CONTROL CODE: S PSOX=100,PSOY=50,PSOYI=30,PSOFONT="F9"
NUMBER: 24                              CTRL CODE ABBREVIATION: BLB
  FULL NAME: BOTTLE LABEL BODY INITIALIZATION
  CONTROL CODE: S PSOX=0,PSODX=275,PSOY=150,PSOYI=40,PSOYM=379,PSOFONT="F10"
NUMBER: 25                              CTRL CODE ABBREVIATION: BLF
  FULL NAME: BOTTLE LABEL FOOTER INITIALIZATION
  CONTROL CODE: S PSODY=460,PSOX=0,PSOCX=280,PSOQY=550,PSOTY=610,PSOFONT="F10",P
SOQFONT="F8",PSODFONT="F9",PSOTFONT="F10"
NUMBER: 26                              CTRL CODE ABBREVIATION: RT
  FULL NAME: ROTATE TEXT                CONTROL CODE: W *27,"&a90P"
NUMBER: 27                              CTRL CODE ABBREVIATION: NR
  FULL NAME: NORMAL ROTATION            CONTROL CODE: W *27,"&a0P"
NUMBER: 28                              CTRL CODE ABBREVIATION: PFDI
  FULL NAME: PHARMACY FILL DOCUMENT INITIALIZATION
  CONTROL CODE: S PSOFONT="F10",PSOX=0,PSOY=700,PSOYI=40,PSOYM=969
NUMBER: 29                              CTRL CODE ABBREVIATION: PFDQ
  FULL NAME: PHARMACY FILL DOCUMENT QUANTITY
  CONTROL CODE: S PSOX=0,PSOCX=200,PSOY=970,PSOYI=50,PSOQFONT="F8",PSOFONT="F10"
NUMBER: 31                              CTRL CODE ABBREVIATION: AWI
  FULL NAME: ALLERGY WARNING INITIALIZATION
  CONTROL CODE: S PSOX=0,PSOY=1400,PSOYI=50,PSOFONT="F10"
NUMBER: 32                              CTRL CODE ABBREVIATION: F6
  FULL NAME: SIX POINT FONT - NO BOLD
  CONTROL CODE: W *27,"(10U",*27,"(s1p6v0s0b16602X"
NUMBER: 33                              CTRL CODE ABBREVIATION: EBT
  FULL NAME: END OF BARCODE TEXT
  CONTROL CODE: W *27,"(8U",*27,"(s1p8v0s0b16602T",!
NUMBER: 34                              CTRL CODE ABBREVIATION: BLBC
  FULL NAME: BOTTLE LABEL BARCODE
  CONTROL CODE: W *27,"(s1p10.4v4,12b4,12s24670T",*27,"&a90P",*27,"*p3650x1000Y"
NUMBER: 35                              CTRL CODE ABBREVIATION: PFDT
  FULL NAME: PHARMACY FILL DOCUMENT TRAILER
  CONTROL CODE: S PSOY=1015,PSOYI=45,PSOX=0,PSOFONT="F10",PSOBYI=50,PSOTFONT="F9
",PSOBY=1280
NUMBER: 36                              CTRL CODE ABBREVIATION: EBLBC
  FULL NAME: END OF BOTTLE LABEL BARCODE
  CONTROL CODE: W *27,"(10U",*27,"(s1p10v0s0b16602T",*27,"&a0P",!
NUMBER: 37                              CTRL CODE ABBREVIATION: SBT
  FULL NAME: START OF BARCODE TEXT
```

```
  CONTROL CODE: S PSOY=PSOY+PSOYI W *27,"*p",PSOX,"x",PSOY,"Y",*27,"(s1p14.4v6,1
8b6,18s24670T"
NUMBER: 43                              ABBREVIATION: F6B
  FULL NAME: SIX POINT FONT, BOLDED
  CONTROL CODE: W *27,"(10U",*27,"(s1p6v0s3b16602T"
NUMBER: 44                              ABBREVIATION: F8B
  FULL NAME: EIGHT POINT FONT, BOLDED
  CONTROL CODE: W *27,"(10U",*27,"(s1p8v0s3b16602T"
NUMBER: 45                              ABBREVIATION: F9B
  FULL NAME: NINE POINT FONT, BOLDED
  CONTROL CODE: W *27,"(10U",*27,"(s1p9v0s3b16602T"
NUMBER: 46                              ABBREVIATION: F10B
  FULL NAME: TEN POINT FONT, BOLDED
  CONTROL CODE: W *27,"(10U",*27,"(s1p10v0s3b16602T"
NUMBER: 47                              ABBREVIATION: F12B
  FULL NAME: 12 POINT FONT BOLDED
  CONTROL CODE: W *27,"(10U",*27,"(s1p12v0s3b16602T"
NUMBER: 72                              ABBREVIATION: PFI
  FULL NAME: PATIENT FILL INITIALIZATION
  CONTROL CODE: S PSOFONT="F10",PSOX=1210,PSOY=710,PSOYI=45,PSOHFONT="F12",PSOBY
I=100
NUMBER: 73                              ABBREVIATION: PFDW
  FULL NAME: PHARMACY FILL DOCUMENT WARNING
  CONTROL CODE: S PSOY=1258,PSOX=660,PSOYI=30,PSOFONT="F8",PSOYM=1329
NUMBER: 74                              ABBREVIATION: MLI
  FULL NAME: MAILING LABEL INITIALIZATION
  CONTROL CODE: S PSOFONT="F10",PSOX=1680,PSOY=175,PSOYI=50
NUMBER: 75                              ABBREVIATION: RMI
  FULL NAME: RETURN MAIL INITIALIZATION
  CONTROL CODE: S PSOHFONT="F8",PSOFONT="F10",PSOX=1680,PSOY=35,PSORYI=40,PSOHYI
=40,PSOTFONT="F8",PSOTY=550
NUMBER: 12172                           CTRL CODE ABBREVIATION: LL
  FULL NAME: LASER LABEL                CONTROL CODE: Q
```

18.3.3. VMS Print Queue Setup

If you use VMS print queues, an additional setup may be necessary. The form for laser labels must have specific characteristics. If you need help defining the form, please contact the National Help Desk.

NOTE: The form must have a length of 255 and a width of 512.

The following is an example form:

```
Form name                               Number   Description
---------                               ------   -----------
LABELFORM                                    2   LASER LABEL
    /LENGTH=255 /MARGIN=(BOTTOM=6) /STOCK=LABELFORM /TRUNCATE /WIDTH=512
```

18.3.4. Control Codes

To modify the control codes to work appropriately with your device, use the following information.

Control Codes in use by Laser Labels:

ACI = ADDRESS CHANGE INITIALIZATION
ALI = ALLERGY SECTION INITIALIZATION
AWI = ALLERGY WARNING INITIALIZATION
BLB = BOTTLE LABEL BODY INITIALIZATION
BLBC = BOTTLE LABEL BARCODE
BLF = BOTTLE LABEL FOOTER INITIALIZATION
BLH = BOTTLE LABEL HEADER INITIALIZATION
CDII = CRITICAL DRUG INTERACTION INITIALIZATION
CNI = COPAY NARRATIVE INITIALIZATION
EBLBC = END OF BOTTLE LABEL BARCODE
EBT = END OF BARCODE TEXT
F10 = TEN POINT FONT - NO BOLD
F10B = TEN POINT FONT, BOLDED
F12 = TWELVE POINT FONT - NO BOLD
F12B = 12 POINT FONT BOLDED
F6 = SIX POINT FONT - NO BOLD
F6B = SIX POINT FONT BOLDED
F8 = EIGHT POINT FONT - NO BOLD
F8B = EIGHT POINT FONT BOLDED
F9 = NINE POINT FONT - NO BOLD
F9B = NINE POINT FONT BOLDED
FDU = FONT DISABLE UNDERLINE
FWU = FONT WITH UNDERLINE
LL = LASER LABEL
LLI = LASER LABEL INIT
MLI = MAILING LABEL INITIALIZATION
NR = NORMAL ROTATION
PFDI = PHARMACY FILL DOCUMENT INITIALIZATION
PFDQ = PHARMACY FILL DOCUMENT QUANTITY
PFDT = PHARMACY FILL DOCUMENT TRAILER
PFDW = PHARMACY FILL DOCUMENT WARNING
PFI = PATIENT FILL INITIALIZATION
PII = PATIENT INSTRUCTION INITIALIZATION
PMII = PMI SECTION INITIALIZATION
RMI = RETURN MAIL INITIALIZATION

RNI = REFILL NARRATIVE INITIALIZATION
RPI = REFILL PRINT INITIALIZATION
RT = ROTATE TEXT
SBT = START OF BARCODE TEXT
SPI = SUSPENSE PRINT INITIALIZATION
ST = START OF TEXT
WLI = WARNING LABEL INITIALIZATION

In addition to escape sequences to control printer output, variables are defined in the control codes that allow the routine to correctly position text and use the appropriate font.

The following is the description of the variables and their usage:

PSOX – X coordinate
PSOY – Y coordinate
PSOYI – Y increment, used to determine spacing between lines
PSOFONT – font size to be used. The font used is Arial.
PSOYM – bottom margin for this section

Some sections contain variables specific only to that section. They are as follows:

Control Code	Variable
MLI	PSOHFONT – font for header lines
ACI	PSOHFONT – font for header lines
RMI	PSORYI – Y coordinate for return mail name
	PSOHYI – Y coordinate for header line
	PSOTFONT – font for trailer line
	PSOTY – Y coordinate for trailer line
SPI	PSOCX – X coordinate for date
RPI	PSOBYI – Y increment for barcode
	PSOTYI – Y increment for trailer information
	PSOLX – X coordinate for left side of page
	PSORX – X coordinate for right side of page
	PSOSYI – Y increment for signature line
	PSOXI – X increment
BLB	PSOBX – X coordinate for barcode
BLF	PSODY – Y coordinate for discard line
	PSOCX – X coordinate for continued line
	PSOQY – Y coordinate for quantity information
	PSOTY – Y coordinate for trailer information

	PSOQFONT – font for quantity
	PSODFONT – font for discard line
	PSOTFONT – font for trailer information
PFDQ	PSOCX – X coordinate for continued line
	PSOQFONT – font for quantity
PFDT	PSOBYI – Y increment for barcode
	PSOTFONT – font for trailer information
	PSOBY – Y coordinate for barcode
PFI	PSOHFONT – font for header
	PSOBYI – Y increment for barcode

18.4. ScripTalk® Printers

ScripTalk® is a registered trademark of En-Vision America.

The Outpatient Pharmacy V. 7.0 package, with the release of PSO*7*135, supports the use of ScripTalk® printers that print to microchip-embedded label stock. The label will have printed text on it, along with the microchip containing the contents of the label. Pharmacy or other designated staff will enroll patients to receive these labels and issue those patients a special reader. When the patient holds a ScripTalk® label near the reader and presses a button, the content of the label is read aloud.

The TCP/IP-enabled printer must be physically connected to the network and then defined in the DEVICE (#3.5) and TERMINAL TYPE (#3.2) files. To connect the printer to the network, a micro print server is necessary for communication to VistA. En-Vision America can assist in identifying the micro print server necessary for the site.

The following are examples of the file set-ups. These examples are provided to guide the user in this set up. Please note that these are only examples and there will be some differences in the settings.

Example: DEVICE File (#3.5) Set Up for VMS Sites

```
NAME: WP706                          $I: USER$:[DSM_SPOOL]WP706.TXT
LOCATION OF TERMINAL: ScripTalk      ASK HOST FILE: NO
ASK HFS I/O OPERATION: NO            BARCODE AVAIL: YES
OPEN PARAMETERS: (NEWVERSION,PROTECTION=(S:RWED,O:RWED,W:RWED))
SUBTYPE: P-ZEBRA-PHARM
```

Example: DEVICE File (#3.5) Set Up for Cache Sites

```
NAME: WP706                              $I: PQ$:WP706$PRT.TXT
  ASK DEVICE: YES                        ASK PARAMETERS: NO
  TASKMAN PRINT A HEADER PAGE: NO        SIGN-ON/SYSTEM DEVICE: NO
  QUEUING: FORCED                        LOCATION OF TERMINAL:
1B-111/ScripTalk
  ASK HOST FILE: NO                      ASK HFS I/O OPERATION: NO
  SUPPRESS FORM FEED AT CLOSE: YES       BARCODE AVAIL: YES
  OPEN PARAMETERS: "NWS"                 SUBTYPE: P-ZEBRA-PHARM
  TYPE: HOST FILE SERVER
  PRINT SERVER NAME OR ADDRESS: wp706.west-palm.med.va.gov
  REMOTE PRINTER NAME: wp706
```

Example: TERMINAL TYPE File (#3.2) Set Up for VMS Sites

```
NAME: P-ZEBRA-PHARM                      SELECTABLE AT SIGN-ON: NO
  RIGHT MARGIN: 132                      FORM FEED: #
  PAGE LENGTH: 64                        BACK SPACE: $C(8)
  CLOSE EXECUTE: U IO K IO(1,IO) S IO=$ZIO C IO S
QUE="/QUEUE="_$E(ION,1,6)_"/DELETE",QUE=$ZC(%PRINT,IO,QUE)
NUMBER: 1                                CTRL CODE ABBREVIATION: FI
  FULL NAME: FORMAT INITIALIZATION       CONTROL CODE: W "^XA",!,"^LH30,60^FS",!
NUMBER: 2                                CTRL CODE ABBREVIATION: SB
  FULL NAME: START OF BARCODE
  CONTROL CODE: W "^BY2,3.0^FO70,25^B3N,N,80,Y,N"
NUMBER: 3                                CTRL CODE ABBREVIATION: ST
  FULL NAME: START OF TEXT
  CONTROL CODE: W "^FO",PSJBARX,",",PSJBARY,"^A0N,30,20" S PSJBARY=PSJBARY+40
NUMBER: 6                                CTRL CODE ABBREVIATION: EB
  FULL NAME: END OF BARCODE              CONTROL CODE: S LINE=LINE+1,PSJBARY=130
NUMBER: 7                                CTRL CODE ABBREVIATION: STF
  FULL NAME: START OF TEXT FIELD         CONTROL CODE: W "^FD"
NUMBER: 8                                CTRL CODE ABBREVIATION: SBF
  FULL NAME: START OF BARCODE FIELD      CONTROL CODE: W "^FD"
NUMBER: 9                                CTRL CODE ABBREVIATION: ETF
  FULL NAME: END OF TEXT FIELD           CONTROL CODE: W "^FS",!
NUMBER: 10                               CTRL CODE ABBREVIATION: SL
  FULL NAME: START OF LABEL
  CONTROL CODE: W "^XA",! S PSJBARY=50,PSJBARX=60
NUMBER: 11                               CTRL CODE ABBREVIATION: EL
  FULL NAME: END OF LABEL                CONTROL CODE: W "^XZ",!
NUMBER: 12                               CTRL CODE ABBREVIATION: EBF
  FULL NAME: END OF BARCODE FIELD        CONTROL CODE: W "^FS",!
```

Example: TERMINAL TYPE File (#3.2) Set Up for Cache Sites

```
NAME: P-ZEBRA-PHARM                      SELECTABLE AT SIGN-ON: NO
  RIGHT MARGIN: 140                      FORM FEED: #
  PAGE LENGTH: 64                        BACK SPACE: $C(8)
  CLOSE EXECUTE: D CLOSE^NVSPRTU
NUMBER: 1                                CTRL CODE ABBREVIATION: FI
  FULL NAME: FORMAT INITIALIZATION       CONTROL CODE: W
"^XA",!,"^LH30,60^FS",!
NUMBER: 2                                CTRL CODE ABBREVIATION: SB
  FULL NAME: START OF BARCODE
  CONTROL CODE: W "^BY2,3.0^FO70,25^B3N,N,80,Y,N"
NUMBER: 3                                CTRL CODE ABBREVIATION: ST
  FULL NAME: START OF TEXT
  CONTROL CODE: W "^FO",PSJBARX,",",PSJBARY,"^A0N,30,20" S
PSJBARY=PSJBARY+40
NUMBER: 6                                CTRL CODE ABBREVIATION: EB
  FULL NAME: END OF BARCODE              CONTROL CODE: S
LINE=LINE+1,PSJBARY=130
NUMBER: 7                                CTRL CODE ABBREVIATION: STF
  FULL NAME: START OF TEXT FIELD         CONTROL CODE: W "^FD"
```

Example: TERMINAL TYPE File (#3.2) Set Up for Cache Sites (continued)

```
NUMBER: 8                               CTRL CODE ABBREVIATION: SBF
   FULL NAME: START OF BARCODE FIELD     CONTROL CODE: W "^FD"
NUMBER: 9                               CTRL CODE ABBREVIATION: ETF
  FULL NAME: END OF TEXT FIELD          CONTROL CODE: W "^FS",!
NUMBER: 10                              CTRL CODE ABBREVIATION: SL
  FULL NAME: START OF LABEL
  CONTROL CODE: W "^XA",! S PSJBARY=50,PSJBARX=60
NUMBER: 11                              CTRL CODE ABBREVIATION: EL
  FULL NAME: END OF LABEL               CONTROL CODE: W "^XZ",!
NUMBER: 12                              CTRL CODE ABBREVIATION: EBF
  FULL NAME: END OF BARCODE FIELD       CONTROL CODE: W "^FS",!
```

Glossary

ADP	Automated Data Processing
Archive	Prescriptions, typically those that have been expired or canceled for more than a year, can be saved to tape, and then purged from online storage.
CPRS	Computerized Patient Record System. CPRS is a Graphical User Interface (GUI) in VistA that provides order entry and results reporting for multiple packages.
DHCP	See VistA.
IRMS	Information Resources Management Service
Non-VA Meds	Term that encompasses any Over-the-Counter (OTC) medications, Herbal supplements, Veterans Health Administration (VHA) prescribed medications but purchased by the patient at an outside pharmacy, and medications prescribed by providers outside VHA. All Non-VA Meds must be documented in patients' medical records.
POE	Pharmacy Ordering Enhancements project. POE is a series of enhancements to improve the ordering processes between Inpatient Medications and Outpatient Pharmacy. For Outpatient Pharmacy, POE changes occur in patch PSO*7*46.
Prescription	This term is now referred to throughout the software as medication orders.
Purge	Prescriptions, typically those that have been expired or canceled for more than a year, are saved to tape. Purging removes them from online storage.
Reprinted Label	Unlike a partial prescription, a reprint does not count as workload.
VDEF	VistA Data Extraction Framework
VHA	Veterans Health Administration
VistA	Acronym for **V**eterans Health **I**nformation **S**ystems and **T**echnology **A**rchitecture, the new name for Decentralized Hospital Computer Program (DHCP).

VUID VHA Unique Identifier. A unique integer assigned to reference terms VHA wide.

Appendix A:
Outpatient Pharmacy HL7 Interface Specifications

A. General Information

Introduction

This document specifies an interface between the VistA Outpatient Pharmacy V. 7.0 application and any automatic dispensing system. It is based upon the Health Level 7 Standard (HL7) V. 2.4.

The term “Level 7” refers to the highest level of the Open System Interconnection (OSI) model of the International Standards Organization (ISO). The OSI model is divided into seven levels or layers. The HL7 Standard is primarily focused on what happens within the seventh or application layer. At this layer, the definitions of the data to be exchanged, the timing of the exchanges, and the communication of certain application specific errors occurs. The lower levels support the actual movement of data between systems.

The high-level communication requirements for this interface include TCP/IP, HL7 Logical link and bi-directional communications for the BusinessWare server at the VAMC. BusinessWare will support MLLP connection.

Message Rules

The HL7 Standard describes the basic rules for the exchange of information between two computer systems. The unit of data transferred is referred to as the message. It is comprised of a group of segments in a defined sequence. Each message has a three-character code called a message type that defines its purpose. The real-world event that initiates an exchange of messages is called a trigger event. There is a one-to-many relationship between message types and trigger event codes. A message type may be associated with more than one trigger event, but the same trigger event code may not be associated with more than one message type. All message type and trigger event codes beginning with Z are reserved for locally defined messages. No such codes will be defined within the HL7 Standard.

Some special characters are used to construct messages. They are the segment terminator, field separator, component separator, sub-component separator, repetition separator, and escape character. The segment terminator is always a carriage return (CR in ASCII or hex OD). The other characters recommended by HL7 are used in this application (See HL7 Standard V. 2.4, Chapter 2 for details).

Segment Rules

A segment is a logical grouping of data fields. Segments of a message may be required or optional. They may occur only once in a message or they may be allowed to repeat. Each segment is given a name and is identified by a unique three-character code. All segments beginning with Z are reserved for locally defined messages. No such code will be defined within the HL7 Standard.

Field Rules

A field is a string of characters. HL7 does not care how systems actually store data within an application. Except where noted, HL7 data fields may take on the null value. Sending the null value, which is transmitted as two double quote marks ("""), is different from omitting an optional data field. The difference appears when the contents of a message will be used to update a record in a database rather than create a new one. If no value is sent (i.e., it is omitted) the old value should remain unchanged. If the null value is sent, the old value should be changed to null. In defining a segment, the following information is specified about each field:

a) position - position of the data field within the segment.

b) name - unique descriptive name for the field.

c) ID number - integer that uniquely identifies the data field throughout the Standard.

d) maximum length - maximum number of characters that one occurrence of the data field may occupy.

e) optionality - whether the data field is required (R), optional (O), or conditional (C) in a segment.

f) repetition - whether the field may repeat (N=no; Y=yes; (integer)= no. of repeats).

g) table - a table of values for a field (See HL7 Standard V. 2.4, Section 2.7.6 for source of tables).

h) data type - restrictions on the contents of the data field (See HL7 Standard V. 2.4, Section 2.9).

B. TRANSACTION SPECIFICATIONS

Communication Protocol

The lower level communication protocol used by Outpatient Pharmacy V. 7.0 to transmit data between systems is either X3.28 or HLLP over an RS-232 connection.

A site parameter in the Outpatient Pharmacy V. 7.0 application called External Interface controls transmission of data to the dispensing machine. If the parameter is set to **0**, no transmission will occur.

There is also a new parameter that is used for sites running HL7 V.2.4. It is in the OUTPATIENT SITE file (#59), and is called AUTOMATED DISPENSE. This must be set to determine which version of HL7 the site is running.

Processing Rules

A Pharmacy Encoded Order Message (event type=O01) is transmitted whenever an order is placed in Outpatient Pharmacy V. 7.0 and the criteria are met for the dispensing machine. Upon successful receipt and storage of the message, the dispensing machine will generate and transmit a Pharmacy Encoded Order Acknowledgement Message (event type=O02).

The following HL7 messages will be used to support the exchange of Outpatient Pharmacy data with any automatic dispensing system:

RDS	Pharmacy Encoded Order Message
RRD	Pharmacy Encoded Order Ack. Message
ACK	General Ack. Message

The messages for the dispense request will consist of the following HL7 segments:

IAM	Patient Adverse Reaction Information
MSH	Message Header
NTE	Notes and Comments
PID	Patient Identification
PV1	Patient Visit
PV2	Patient Visit – additional information
ORC	Common Order
RXE	Pharmacy/Treatment Encoded Order
RXD	Pharmacy/Treatment Dispense
RXR	Pharmacy/Treatment Route

Specific Transaction – Dispense Request

The Pharmacy/Treatment Encoded Order Message (Dispense Request) is as follows:

RDS	Pharmacy/Treatment Encoded Order Message
MSH	Message Header
[PID]	Patient Identification
[PV1]	Patient Visit
[PV2]	Patient Visit – additional information
{IAM}	Patient Adverse Reaction Information
{ORC	Common Order
{NTE}	Notes and Comments
RXE	Pharmacy/Treatment Encoded Order
RXD	Pharmacy/Treatment Dispense
{NTE}	Notes and Comments (contains PMI)
{RXR}	Pharmacy/Treatment Route
}	

Example:

```
MSH|^~\&|PSO VISTA|521^OUTPATIENT|PSO
DISPENSE|521|20030620125043||RDS^O13^RDS_O13|10001|P|2.4|||AL|AL
PID|||5000000022V981671^^^USVAMC^PN^USVHA~1234^^^USVAMC^USVAMC^USVAMC~000456789^^^
USSSA^SS^USSSA||OPPATIENT^ONE||19590116|M|||60 Park Pl&Apt 25&Suite
600^^Birmingham^AL^35233-1234^^C||(251) 555-5555
PV1||O
PV2||||||||||||||||||||||||SCL50~NO COPAY
IAM||D^Drug^LGMR120.8|128^ASPIRIN^LGMR120.8|SV|ALLERGY||||||||19961205||||C
ORC|NW|12345^OP7.0|||||||20030608|10^OPPROVIDER^TWO||987^OPPROVIDER^ONE|_TNA1225
:||20030616|NEW|57^7TH FLOOR^99PSC||65421^OPPROVIDER5^THREE||Albany^^52312|700
South 19th Street^^Birmingham^AL^35233|(817) 555-5555
[{NTE|1||Free Text|Medication Instructions~Patient Instructions Narrative~Drug
Warning Narrative~Profile Information~Drug Interactions~Drug Allergy Indications
RXE|"""|D0082^DIGOXIN 0.25MG TAB^99PSNDF^372.3^DIGOXIN 0.25MG
TAB^99PSD|"""||20^MG^99PSU|120^TAB, RAPID DISINTEGRATE^99PSF||WINDOW|LANOXIN
0.125MG|30|^TAB|3|EZ9278277|188^OPPROVIDER3^ONE|123987|3|2|199809070830|||||||||
|||Y~N~N
RXD|3|D0082^DIGOXIN 0.25MG TAB^99PSNDF^372.3^DIGOXIN 0.25MG
TAB^99PSD|20030610||||100001351|3|~6P~6505-00-584-
0398|157^OPPROVIDER^TWO||30|CERTIFIED MAIL||^NON-SAFETY||||20040615
NTE|PMI||CORTICOSTEROIDS - ORAL|Patient Medication Instructions
RXR|6^Oral^99PSR
```

The Pharmacy Encoded Order Acknowledgment Message is as follows:

RRD	Pharmacy Encoded Order Ack. Message
MSH	Message Header
MSA	Message Acknowledgement

Example:

```
MSH|~^\&|PSO DISPENSE|BP-CHEYENNE|PSO VISTA|BP-CHEYENNE|20040227222454-
0500||ACK|4425981296|T|2.4||
MSA|AA|10001
```

Segments used in the Outpatient Pharmacy HL7 interface Dispense Request:

SEGMENT	SEQ#	LEN	DT	R/O	RP/#	TBL#	ELEMENT NAME	EXAMPLE
MSH	1	1	ST	R			Field Separator	|
	2	4	ST	R			Encoding Characters	~^\&
	3	180	HD	R		0361	Sending Application	PSO VISTA
	4	180	HD	R		0362	Sending Facility – station ID and station DNS name	521~FO-BIRM.MED.VA.GOV~DNS
	5	180	HD	R		0361	Receiving Application	PSO DISPENSE
	6	180	HD	R		0362	Receiving Facility – DNS name and port of dispensing machine	~DISPENSE.VHA.MED.VA.GOV:9300~DNS
	7	26	TS				Date/Time of Message	20040405152416
	9	15	CM	R	0076		Message Type	RDS~013
	10	20	ST	R			Message Control ID	10001
	11	3	PT	R	0103		Processing ID	P
	12	3	VID	R	0104		Version ID	2.4
	15	2	ID			0155	Accept Ack. Type	AL
	16	2	ID			0155	Application Ack Type	AL
PID	3	250	CX	R	Y		Patient ID (will contain IEN, SSN, ICN, Claim #, etc if exists)	218~~~USVHA&&0363~PI~VA FACILITY ID&500&L
	5	250	XPN	R			Patient Name	OPPATIENT~ONE
	7	26	TS	R			Date/Time of Birth	19280622
	8	1	IS			0001	Administrative Sex	M
	11	250	XAD	R	Y/3		Patient Address	164 Friendship DR~""~TROY~NY~12180~~P~""
	13	250	XTN	R	Y/3		Phone Number-Home	(555)555-5555
PV1	2	1	IS	R		0004	Patient Class	O for Outpatient
PV2	24	15	IS	R	Y		Patient Status Code	SC~NO COPAY
IAM	2	250	CE	O	Y	0127	Allergen Type Code	D~DRUG~LGMR120.8
	3	250	CE	R	Y		Allergen Code/Mnemonic/Description	128~ASPIRIN~LGMR120.8
	4	250	CE	O	Y	0128	Allergy Severity Code	SV
	5	15	ST	O	Y		Allergy Reaction Code	ALLERGY
	13	26	TS	O	Y		Reported Date/Time	19961205
	17	250	CE	O	Y	0438	Allergy Clinical Status Code	C

Segments used in the Outpatient Pharmacy HL7 interface Dispense Request: (continued)

SEGMENT	SEQ#	LEN	DT	R/O	RP/#	TBL#	ELEMENT NAME	EXAMPLE
ORC	1	2	ID	R		0119	Order Control	NW
	2	80	EI	C			Placer Order Number	402331~OP7.0
	9	26	TS	O			Date/Time of Transaction	20040405
	10	250	XCN	R			Entered By	10~OPPROVIDER~TWO
	12	250	XCN	O			Ordering Provider	987~OPPROVIDER~ONE
	13	80	PL	O			Enterer's Location	_TNA1225:
	15	26	TS	O			Order Effective Date	20030616
	16	10	ST	R			Order Control Code Reason	NEW
	17	250	CE	O			Entering Organization	57~7TH FLOOR~99PSC
	19	250	XCN	O			Action By	65421~OPPROVIDER5~THREE
	21	250	XON	O			Ordering Facility Name	AL BANY~~500
	22	250	XAD	O			Ordering Facility Address	101 CHURCH AVE~~ALBANY~NY~12208
	23	250	XTN	O			Ordering Facility Phone #r	(518)555-5554
NTE	1	1	SI	O			Set ID	1
	3	65536	FT	O			Comment	USE 50 FOR TESTING BY MOUTH TWICE A DAY FOR 30 DAYS
	4	250	RE	O			Comment Type – 1 = Medication Instructions 2 = Patient Instructions Narrative 3 = Drug Warning Narrative 4 = Profile Information 5 = Drug Interactions	Medication Instructions
RXE	1	200	TQ	R			Quantity/Timing	Null
	2	250	CE	R			Give Code	XH001~HEMATEST TAB (NOT FOR ORAL USE)~99PSNDF~3207.12039.4321~HEMATEST REAGENT TAB. 100/BTL~99PSD
	3	20	NM	R			Give Amount-Minimum	Null
	5	250	CE	R			Give Units	20~MG~99PSU
	6	250	CE	O			Give Dosage Form	165~TAB,TEST~99PSF
	8	200	CM	O			Deliver-To Location	WINDOW

Segments used in the Outpatient Pharmacy HL7 interface Dispense Request: (continued)

SEGMENT	SEQ#	LEN	DT	R/O	RP/#	TBL#	ELEMENT NAME	EXAMPLE
	9	25	ST	O			Substitution Status	(Trade name)
	10	20	NM	O			Dispense Amount	30
	11	250	CE	O			Dispense Units	~TAB
	12	3	NM	O			Number of Refills	3
	13	250	XCN	O			Ordering Provider's DEA Number	EZ9278277
	14	250	XCN	C			Pharmacist/Treatment Supplier's Verifier ID	188~OPPROVIDER3~ONE
	15	20	ST	R			Prescription Number	100002202
	16	20	NM	O			Number of Refills Remaining	3
	17	20	NM	O			Number of Refills/Doses Dispensed	0
	18	26	TS	O			D/T of Most Recent Refill	200404050830
	31	1	ID	R			Supplementary Code = spec hdlg, ScripTalk, PMI language preference	N^0^N
RXD	1	10	NM	R			Dispense Sub-ID Counter	0
	2	250	CE	R			Dispense/Give Code	XH001~HEMATEST TAB (NOT FOR ORAL USE)~99PSNDF~3207.12039.4321~HEMATEST REAGENT TAB. 100/BTL~99PSD
	3	26	TS	R			Date/Time Dispensed	20040405
	7	20	ST	R			Prescription Number	100002202
	8	20	NM	O			Number of Refills Remaining	3
	9	25	ST	O			Dispense Notes – DEA spec hdlg, NDC code	S^193-2426-21
	10	200	XCN	O			Dispensing Provider	157~OPPROVIDER~TWO
	12	10	CQ	O			Total Daily Dose	30
	13	200	CM	O			Dispense-To Location	CERTIFIED MAIL
	15	10	CE	O			Pharmacy/Treatment Supplier's Special Dispensing Instructions	~NON-SAFETY
	19	26	TS	O			Substance Expiration Date	20040615
	25	250	CE	O			Supplementary Code	8~NO ALCOHOL
NTE	1	4	SI	O			Set ID-Notes and Comments	7
	3	6000	FT	O	Y		Comment	PMI free text
	4	250	CE	O			Comment Type – P MI	Patient Medication Instructions
RXR	1	250	CE			0162	Route	1~ORAL (BY MOUTH)~99PSR

Notes pertaining to some of the data elements:

[MSH-3] Sending Application is the station ID along with the DNS name of the sending facility.

[MSH-5] Receiving Application is the DNS name and DNS port number of the dispensing application.

[MSH-10] Message Control ID is the number that uniquely identifies the message. It is returned in MSA-2 of the dispense completion message.

[PID-3] Patient ID will contain the following possibilities to identify a patient:

- NI = ICN #
- SS = Social Security #
- PN = Claim #
- PI = DFN #

[PV1-2] Patient Class is hard-coded to an O for outpatient.

[PV2-24] Patient Status Code contains the patient status from the prescriptions file followed by a tilde and then whether or not the patient is COPAY.

[IAM-2] Allergen Type Code is the allergy type of F=Food, DF=Drug/Food, D=Drug, DP=Drug/Other, O=Other, DFO=Drug/Food/Other.

[IAM-5] Allergy Reaction Code will contain the possible reactions ALLERGY, PHARMACOLOGIC or UNKNOWN.

[IAM-17] Allergy Clinical Status Code is VERIFIED or NON-VERIFIED.

[ORC-2] Placer Order Number is a composite field. The first component is the IEN from the PRESCRIPTION file (#52). The second component is hard-coded to a value of OP7.0.

[ORC-10] Entered By is the person's pointer to the NEW PERSON file (#200) and name in VistA who keyed in the order.

[ORC-12] Ordering Provider is a composite ID field. The first component is the Provider's pointer to the NEW PERSON file (#200) in VistA and the second component is his/her name.

[ORC.13] Enterer's Location is the printer where the dispensing machine should print the label.

[ORC-15] Order Effective Date is the date/time the order took effect.

[ORC-16] Order Control Code Reason is a coded element field. The fifth component reflects the status of the order (for example, New, Refill, Partial, Reprint, or Partial Reprint).

[ORC-17] Entering Organization is the Clinic number and name.

[ORC-19] Action By is the physician who cosigned, if any, and is a composite field. The first component is the physician's pointer to the NEW PERSON file (#200) in VistA and the second component is his/her name.

[ORC-21] Ordering Facility Name is the facility name and number found in the OUTPATIENT SITE file (#59).

[NTE] The Set ID field will identify the NTE segment (1=Med. Instructions; 2=Patient Instructions Narrative; 3=Drug Warning Narrative; 4=Profile Information; 5=Drug Interactions; 6=Drug Allergy Indications). The Comment field will contain the respective information.

[RXE-1] Quantity Timing is a required field but it will not be used in Outpatient Pharmacy V. 7.0. It will always be a null value ("").

[RXE-2] Give Code identifies the substance ordered as encoded by the Pharmacy. The components, in order, are the VA Product ID, VA Product Name, National Drug File, local file pointer, local drug name, and the local file.

[RXE-3] Give Amount - Minimum is a required field but it will not be used in Outpatient Pharmacy V. 7.0. It will always be a null value ("").

[RXE-5] Give Units identifies the units for the give amount as encoded by the VA National Drug file.

[RXE-6] Give Dosage Form is a coded element field. The fourth component is the pointer to the DOSAGE FORM file (#50.606). The fifth component is the form name, and the sixth component is the name of coding system (99PSF).

[RXE-8] Deliver-To-Location is the Method of Pickup (Window or Mail).

[RXE-9] Substitution Status is the value of the TRADE NAME field (#6.5) found in the PRESCRIPTION file (#52).

[RXE-10] Dispense Amount identifies the quantity.

[RXE-11] Dispense Units identifies the units for the dispense amount as encoded by the Pharmacy.

[RXE-13] Ordering Provider's DEA Number will contain the physician's DEA number if the drug is a controlled substance.

[RXE-14] Pharmacist/Treatment Supplier's Verifier ID identifies the pharmacist who verified the order. The first component is the DFN pointer in the NEW PERSON file (#200) of VistA and the second component is the name.

[RXE-18] D/T of Most Recent Refill or Dose Dispensed contains the last date/time the patient received this particular drug. This is the PRIOR FILL DATE field (#102.1) from the PRESCRIPTION file (#52).

[RXE-31] Supplementary Code contains three pieces of information:

- An indicator that the drug is a controlled substance or not (Y/N).
- An indicator if the patient is a ScripTalk patient (0 or 1).
- An indicator if the patient's PMI language preference is something other than English (Y/N).

[RXD-1] Dispense Sub-ID Counter identifies the prescription fill number.

[RXD-2] Dispense/Give code will contain the same give code as in RXE-2.

[RXD-9] Dispense Notes have two pieces of information:

- DEA, SPECIAL HDLG field (#3) from the DRUG file (#50).
- NDC field (#27) from the PRESCRIPTION file (#52).

[RXD-10] Dispensing Provider is the person who finished the order.

[RXD-12] Total Daily Dose is the days of supply for a partial fill.

[RXD-13] Dispense-To-Location will contain how the patient will receive the medication. Possible answers are WINDOW, REGULAR MAIL, CERTIFIED MAIL or DO NOT MAIL.

[RXD-15] Pharmacy/Treatment Supplier's Special Dispensing Instructions will indicate what sort of bottle cap should be employed. It is a safety cap or non-safety cap.

[RXD-25] Supplementary Code is the drug warning number and text.

[NTE] This segment following the RXD segment will contain the Patient Medication Instructions if any.

[RXR-1] Route is the medication route.

Specific Transaction – Dispense Release Date/Time

The messages for the Dispense Release Date/Time will consist of the following HL7 segments:

MSH	Message Header
PID	Patient Identification
PV1	Patient Visit
PV2	Patient Visit – additional information
RXE	Pharmacy/Treatment Encoded Order
RXD	Pharmacy/Treatment Dispense

Example:

```
MSH|^~\&|PSO VISTA|521^OUTPATIENT|PSO
DISPENSE|521|20030620125043||RDS^O13^RDS_O13|10001|P|2.4|||AL|AL
PID|||5000000022V981671^^^USVAMC^PN^USVHA~1234^^^USVAMC^USVAMC^USVAMC~000456789^^^
USSSA^SS^USSSA||OPPATIENT^ONE||19590116|M|||60 Park Pl&Apt 25&Suite
600^^Birmingham^AL^35233-1234^^C||(251) 555-5555
PV1||O
PV2||||||||||||||||||||||||SCL50~NO COPAY
RXE|""""|D0082^DIGOXIN 0.25MG TAB^99PSNDF^372.3^DIGOXIN 0.25MG
TAB^99PSD|""""||20^MG^99PSU|120^TAB, RAPID DISINTEGRATE^99PSF|||LAXOXIN
0.125MG||||||123987
RXD|3|^ASPIRIN 325 MG TAB|20030610||||100001351||20031212~233~6505-00-584-
0398|||||||||20040615
```

Segments used in the Outpatient Pharmacy HL7 interface Dispense Release Date/Time Request:

SEGMENT	SEQ#	LEN	DT	R/O	RP/#	TBL#	ELEMENT NAME	EXAMPLE
MSH	1	1	ST	R			Field Separator	|
	2	4	ST	R			Encoding Characters	~^\&
	3	180	HD	R		0361	Sending Application	PSO VISTA
	4	180	HD	R		0362	Sending Facility – station ID and station DNS name	521~FO-BIRM.MED.VA.GOV~DNS
	5	180	HD	R		0361	Receiving Application	PSO DISPENSE
	6	180	HD	R		0362	Receiving Facility – DNS name and port of dispensing machine	~DISPENSE.VHA.MED.VA.GOV:9300~DNS
	7	26	TS				Date/Time of Message	20040405152416
	9	15	CM	R	0076		Message Type	RDS~013
	10	20	ST	R			Message Control ID	10001
	11	3	PT	R	0103		Processing ID	P
	12	3	VID	R	0104		Version ID	2.4
	15	2	ID			0155	Accept Ack. Type	AL
	16	2	ID			0155	Application Ack Type	AL
PID	3	250	CX	R	Y		Patient ID (will contain IEN, SSN, ICN, Claim #, etc if exists)	218~~~USVHA&&0363~PI~VA FACILITY ID&500&L
	5	250	XPN	R			Patient Name	OPPATIENT~ONE
	7	26	TS	R			Date/Time of Birth	19280622
	8	1	IS			0001	Administrative Sex	M
	11	250	XAD	R	Y/3		Patient Address	164 Friendship DR~""~TROY~NY~12180~~P~""
	13	250	XTN	R	Y/3		Phone Number-Home	(555)555-5555
PV1	2	1	IS	R		0004	Patient Class	O for Outpatient
PV2	24	15	IS	R	Y		Patient Status Code	SC~NO COPAY
RXE	1	200	TQ	R			Quantity/Timing	Null
	2	250	CE	R			Give Code	XH001~HEMATEST TAB (NOT FOR ORAL USE)~99PSNDF~3207.12039.4321~HEMATEST REAGENT TAB. 100/BTL~99PSD
	3	20	NM	R			Give Amount-Minimum	Null
	5	250	CE	R			Give Units	20~MG~99PSU
	6	250	CE	O			Give Dosage Form	165~TAB,TEST~99PSF
	8	200	CM	O			Deliver-To Location	WINDOW
	9	25	ST	O			Substitution Status	(Trade name)
	15	20	ST	R			Prescription Number	100002202

Segments used in the Outpatient Pharmacy HL7 interface Dispense Release Date/Time Request: (continued)

SEGMENT	SEQ#	LEN	DT	R/O	RP/#	TBL#	ELEMENT NAME	EXAMPLE
RXD	1	10	NM	R			Dispense Sub-ID Counter	3
	2	250	CE	R			Dispense/Give Code	XH001~HEMATEST TAB (NOT FOR ORAL USE)~99PSNDF~3207.12039.4321~HEMATEST REAGENT TAB. 100/BTL~99PSD
	3	26	TS	R			Date/Time Dispensed	20040405
	7	20	ST	R			Prescription Number	100002202
	9	25	ST	O			Dispense Notes – Release Date/Time, Bingo Wait time, NDC Code	200312120830^35^6505-00-584-0398

Notes pertaining to some of the data elements:

[MSH-3] Sending Application is the station ID along with the DNS name of the sending facility.

[MSH-5] Receiving Application is the DNS name and DNS port number of the dispensing application.

[MSH-10] Message Control ID is the number that uniquely identifies the message. It is returned in MSA-2 of the dispense completion message.

[PID-3] Patient ID will contain the following possibilities to identify a patient:

- NI = ICN #
- SS = Social Security #
- PN = Claim #
- PI = DFN #

[PV1-2] Patient Class is hard-coded to an O for outpatient.

[PV2-24] Patient Status Code contains the patient status from the prescriptions file followed by a tilde and then whether or not the patient is COPAY.

[RXE-1] Quantity Timing is a required field but it will not be used in Outpatient Pharmacy V. 7.0. It will always be a null value ("").

[RXE-2] Give Code identifies the substance ordered as encoded by the Pharmacy. The components, in order, are the VA Product ID, VA Product Name, National Drug File, local file pointer, local drug name, and the local file.

[RXE-3] Give Amount - Minimum is a required field but it will not be used in Outpatient Pharmacy V. 7.0. It will always be a null value ("").

[RXE-5] Give Units identifies the units for the give amount as encoded by the VA National Drug file.

[RXE-6] Give Dosage Form is a coded element field. The fourth component is the pointer to the DOSAGE FORM file (#50.606). The fifth component is the form name, and the sixth component is the name of coding system (99PSF).

[RXD-1] Dispense Sub-ID Counter identifies which fill the prescription is.

[RXD-2] Dispense/Give code will contain the same give code as in RXE-2.

[RXD-9] Dispense Notes has three pieces of information:

- FILE RELEASE DATE/TIME field (#105.1) from the PRESCRIPTION file (#52).
- BINGO WAIT TIME field (#32) from the PRESCRIPTION file (#52).
- NDC field (#27) from the PRESCRIPTION file (#52).

Specific Transaction – Dispense Completion

The messages for the dispense completion will consist of the following HL7 segments:

MSA	Message Acknowledgment
MSH	Message Header
PID	Patient Identification
ORC	Common Order
RXD	Pharmacy/Treatment Dispense

Example:

```
MSH|^~\&|PSO DISPENSE|521|PSO
VISTA|521|20031215125043||RRD^O14^RRD_O14|10001|P|2.4|||AL|AL
MSA|AA~CA|10001
PID|||5000000022V981671^^^USVAMC^PN~1234^^^PN^PI~000456789^^^USSSA^SS||OPPATIENT^
ONE||19590116|M
ORC|OR|12345||||||||^OPPROVIDER2^THREE|^OPPROVIDER^TWO
RXD|1|D0082^DIGOXIN 0.25MG TAB^99PSNDF^372.3^DIGOXIN 0.25MG
TAB^99PSD|20031215||||123987||6505-00-584-
0398~20031212|1234567^OPPROVIDER1^ONE||||||||45201|20041201|BAXTER
```

Segments used in the Outpatient Pharmacy HL7 interface Dispense Completion:

SEGMENT	SEQ#	LEN	DT	R/O	RP/#	TBL#	ELEMENT NAME	EXAMPLE
MSH	1	1	ST	R			Field Separator	|
	2	4	ST	R			Encoding Characters	^~\&
	3	180	HD	R		0361	Sending Application	PSO DISPENSE
	4	180	HD	R		0361	Sending Facility	~DISPENSE.VHA.MED.VA.GOV:9300~DNS
	5	180	HD	R		0361	Receiving Application	PSO VISTA
	6	180	HD	R		0362	Receiving Facility	
	7	26	TS	R			Date/Time of Message	200304050938
	9	15	CM_MSG	R		0076	Message Type	RRD~014
	10	20	ST	R			Message Control ID	10001
	11	3	PT	R		0103	Processing ID	P
	12	60	VID	R		0104	Version ID	2.4
	15	2	ID	O		0155	Accept Acknowledgment	AL
	16	2	ID	O		0155	Application Acknowledgment Type	NE
MSA	1	2	ID	R		0008	Acknowledgment Code	AA
	2	20	ST	R			Message Control ID	10001

Segments used in the Outpatient Pharmacy HL7 interface Dispense Completion: (continued)

SEGMENT	SEQ#	LEN	DT	R/O	RP/#	TBL#	ELEMENT NAME	EXAMPLE
PID	3	250	CX	R	Y		Patient ID (will contain IEN, SSN, ICN, Claim #, etc if exists)	218~~~USVHA&&0363~PI~VA FACILITY ID&500&L
	5	250	XPN	R			Patient Name	OPPATIENT~ONE
	7	26	TS	R			Date/Time of Birth	19280622
	8	1	IS			0001	Administrative Sex	M
ORC	1	2	ID	R		0119	Order Control	OR
	2	22	EI	C			Placer Order Number	12345
	10	250	XCN	O			Entered By	114~OPPROVIDER2~THREE
	11	250	XCN	O			Verified By	115~OPPROVIDER~TWO
RXD	1	4	NM	R			Dispense Sub-ID Counter	1 (Fill Number)
	2	250	CE	R		0292	Dispense/Give Code	XH001~HEMATEST TAB (NOT FOR ORAL USE)~99PSNDF~3207.12039.4321~HEMATEST REAGENT TAB. 100/BTL~99PSD
	3	26	TS	R			Date/Time Dispensed	20040405
	7	20	ST	R			Prescription Number	100002202
	9	25	ST	O			Dispense Notes	6505-00-584-0398^200404050830
	10	200	XCN	O			Dispensing Provider	1234~OPPROVIDER1~ONE
	18	20	ST	O			Substance Lot Number	45201
	19	26	TS	O			Substance Expiration Date	20050405
	20	250	CE	O		0227	Substance Manufacturer Name	BAXTER

Notes pertaining to some data elements:

[MSH-3] Receiving Application is the DNS name and DNS port number of the dispensing application.

[MSH-5] Sending Application is the station ID along with the DNS name of the facility.

[MSH-10] Message Control ID is the number that uniquely identifies the message.

[MSA-2] Message Control ID is the same number that was in MSH-2 in the dispense request message.

[PID-3] Patient ID will contain the following possibilities to identify a patient:

- NI = ICN #
- SS = Social Security #
- PN = Claim #
- PI = DFN #

[ORC-2] Placer Order Number is the RX internal entry number.

[ORC-10] Entered By is the name of the Filling Person for the prescription.

[ORC-11] Verified By is the name of the Checking Pharmacist for the prescription.

[RXD-1] Dispense Sub-ID Counter is the fill number for the prescription.

[RXD-3] Date/Time Dispensed is the fill date and time.

[RXD-9] Dispense Notes contains two components. First component is the NDC code and the second component is the release date/time of the prescription from the dispensing machine.

[RXD-10] Dispensing Provider is the name of the releasing pharmacist.

(This page included for two-sided copying.)

Appendix B:
HL7 Messaging with an External System

New Protocol

A new protocol, PSO RECEIVE ORDER, is exported for processing orders from an external system. To use this functionality, this protocol must be added as a SUBSCRIBER to the Event Driver protocol in the PROTOCOL file (#101), which sends the external order message.

New Application Parameter

A new HL7 application parameter, PSO RECEIVE, is exported as the Receiving Application of the PSO RECEIVE ORDER protocol from the HL7 APPLICATION PARAMETER file (#771).

New Logical Link

A new HL7 logical link, PSO LLPO from the HL LOGICAL LINK file (#870), is being exported as the Logical Link of the PSO RECEIVE ORDER protocol. This link information will need to be edited to match the communication method of the interface if this interface is activated.

For any orders received from an external source, two new fields are stored with the Outpatient Pending Order and with the prescription, once the Pending Order is finished. These fields are EXTERNAL PLACER ORDER NUMBER field (#114) and EXTERNAL APPLICATION field (#116) in the PENDING OUTPATIENT ORDERS file (#52.41). These fields are also within the PRESCRIPTION file (#52) and are the EXTERNAL PLACER ORDER NUMBER field (#123) and EXTERNAL APPLICATION field (#124).

Any external systems that send orders through this interface to VistA must comply with having **unique** external placer order numbers within the orders from this system. This number is used for various look-ups within the interface, in conjunction with the EXTERNAL APPLICATION field (#116) in the PENDING OUTPATIENT ORDERS file (#52.41) and the EXTERNAL APPLICATION field (#124) in the PRESCRIPTION file (#52).

Any message sent through this interface to VistA, whether it is a New Order message or a Discontinue message must contain only one order per message. The interface is not set up to receive multiple orders per message.

HL7 Order Message Segment Definition Table

When the PSO RECEIVE ORDER protocol is enabled to process orders from an external system, the following table defines the data elements required for each segment of the incoming order message. This is a unilateral interface. No order information will be returned to the external system.

Segment	Piece	Description/Field Name	Data	Data Type
MSH	1	Field Separator	|	String
	2	Encoding Characters	^~\&	String
	3	Sending Application	Sending Application Name	String
	4	Sending Facility		String
	5	Receiving Application	PSO RECEIVE	String
	6	Receiving Facility		String
	9	Message Type	ORM^O01	Coded Value
	10	Message Control ID		String
	11	Processing ID	P	Coded Value
	12	Version ID	2.3.1	Coded Value
	15	Accept Acknowledgement	NE	Coded Value
	16	Application Acknowledgement	AL	Coded Value
	17	Country Code	USA	Coded Value
PID	3	Patient (pointer to File #2)	VistA IEN of Patient from File #2	Composite ID
	5	Patient Name		Person Name
PVI	3	Clinic (pointer to File #44)	VistA IEN of Hospital Location from File #44	Composite
ORC	1	Order Control Code	'NW'	Coded Value
	2	Placer Order Number*	External Placer Order Number	Composite
	9	Date/Time of Transaction	Current Date/Time	Time Stamp
	10	Entered By	VistA IEN of Provider from File #200	Composite ID Number and Name
	12	Ordering Provider	VistA IEN of Provider from File #200	Composite ID Number and Name
	15	Order Effective Date	Current Date/Time	Time Stamp

Segment	Piece	Description/Field Name	Data	Data Type
RXO	10	Dispense Drug	VistA IEN of Drug from File #50	Coded Element
	11	Quantity	Quantity	Numeric
	13	Number of Refills	Number of Refills	Numeric
NTE	6	Provider's Instructions to Dispensing Pharmacy	Free Text Provider Comments	String
	7	Patient's Instructions	Expanded Sig	String
ZRN	1	Non-VA	N	Coded Element (N=Non VA med)
	2	Statement/Reason	Non-VA Medication not recommended by VA provider or Medication prescribed by non-VA provider	String
ZRX	4	Routing	'W' (for Window)	String

* Field must contain unique data

The PSO RECEIVE ORDER protocol can also receive discontinue order messages. The following table gives the details of the fields that need to be received in the incoming order message.

Segment	Piece	Description/Field Name	Data	Data Type
MSH	1	Field Separator	|	String
	2	Encoding Characters	^~\&	String
	3	Sending Application	Sending Application Name	String
	4	Sending Facility		String
	5	Receiving Application	PSO RECEIVE	String
	6	Receiving Facility		String
	9	Message Type	ORM^O01	Coded Value
	10	Message Control ID		String
	11	Processing ID	P	Coded Value
	12	Version ID	2.3.1	Coded Value
	15	Accept Acknowledgement	NE	Coded Value
	16	Application Acknowledgement	AL	Coded Value
	16	Country Code	USA	Coded Value
PID	3	Patient (pointer to File #2)	VistA IEN of Patient from File #2	Composite ID
	5	Patient Name		Person Name
PVI	3	Clinic (pointer to File #44)	VistA IEN of Hospital Location from File #44	Composite
ORC	1	Order Control Code	'CA'	Coded Value
	2	Placer Order Number*	External Placer Order Number	Composite
	9	Date/Time of Transaction	Current Date/Time	Time Stamp
	10	Entered By	VistA IEN of Provider from File #200	Composite ID Number and Name
	12	Ordering Provider	VistA IEN of Provider from File #200	Composite ID Number and Name
	15	Order Effective Date	Current Date/Time	Time Stamp

ZRN	1	Non-VA	N	Coded Element (N=Non VA med)
	2	Statement/Reason	Non-VA Medication not recommended by VA provider or Medication prescribed by non-VA provider	String

* Field must contain unique data

An Application Acknowledgement message is returned for new and discontinue messages received from the external system. Sequence 1 (Acknowledgement Code) of the MSA segment will always be Application Accept (AA), regardless of whether or not the incoming message passed all of the exception checks. Sequence 3 (Text Message) of the MSA segment will be null if the message was accepted and passed all of the exception checks. If the message is rejected by the receiving application, Sequence 3 (Text Message) will contain the reason for the rejection.

Segment	Piece	Description/Field Name	Data	Data Type
MSH	1	Field Separator	|	String
	2	Encoding Characters	^~\&	String
	3	Sending Application	PSO RECEIVE	String
	4	Sending Facility	(Sending Facility)	String
	5	Receiving Application	(Receiving Application Name)	String
	6	Receiving Facility	(Receiving Facility)	String
	7	Date/time of Message	Current Date/Time	Time Stamp
	9	Message Type	ORR^O01	Coded Value
	10	Message Control ID		String
	11	Processing ID	P	Coded Value
	12	Version ID	2.3.1	Coded Value
	15	Accept Acknowledgement	NE	Coded Value
	16	Application Acknowledgement	NE	Coded Value
	17	Country Code	US	Coded Value
MSA	1	Acknowledgement Code	AA	Coded Value
	2	Message Control ID		String
	3	Text Message	(Null, or Rejection Reason)	String

Order Messaging Exceptions

Exceptions will occur when VistA rejects a new or discontinue order message. For new order messages, the rejections are largely based on the drug, provider, or patient associated with the prescription order.

Drug exceptions

- Drug is inactive (less than today's date)
- Drug is not marked for outpatient use
- Drug is not associated with a Pharmacy Orderable Item
- Invalid drug entry

Provider exceptions

- Provider is not authorized to write med orders
- Provider has an inactive date (date of today or less)
- Provider has a termination date (date of today or less)
- Provider does not hold the PROVIDER key
- Invalid provider entry

Patient exceptions

- Patient is deceased
- Invalid patient entry

Other exceptions

- Invalid NTE segment, greater than 245 characters
- Invalid message structure
- Missing MSH segment
- Missing PID segment
- Missing PVI segment
- Missing ORC segment
- Missing RXO segment
- External order, unable to successfully transmit to CPRS
- Unable to derive Institution from Clinic
- Unable to add order to Pending file
- Missing sending application name
- Invalid Order Control Code
- No Patient Location
- Missing CHCS Placer Order Number
- Duplicate order number in Outpatient Pending file
- Duplicate order number in Outpatient Prescription file
- Missing number of refills
- Missing effective date
- Missing Entered by data

For discontinue order messages, these are the possible exceptions:

Provider exceptions

- Provider is not authorized to write med orders
- Provider has an inactive date (date of today or less)
- Provider has a termination date (date of today or less)
- Provider does not hold the PROVIDER key
- Invalid provider entry

Other exceptions

- Invalid message structure
- Missing MSH segment
- Missing PID segment
- Missing ORC segment
- Missing sending application name
- Missing CHCS Placer Order Number
- Unable to find order in Pharmacy
- Patient mismatch in Pending order
- Pending order is being edited by another user
- Unable to cancel Pending order, status is HOLD
- Unable to cancel Pending order, status is RENEW
- Unable to cancel Pending order, status is DISCONTINUE (EDIT)
- Unable to cancel Pending order, status is DISCONTINUE
- Unable to cancel Pending order, status is REFILL REQUEST
- Patient mismatch in prescription
- Prescription is being edited by another user
- Unable to cancel prescription, status is DISCONTINUED
- Unable to cancel prescription, status is DELETED
- Unable to cancel prescription, status is DISCONTINUED BY PROVIDER
- Unable to cancel prescription, status is DISCONTINUED (EDIT)

(This page included for two-sided copying.)

Appendix C:

The Transitional Pharmacy Benefit (TPB) functionality has been placed “Out of Order” with the PSO*7*227 patch; pages 79-88 have been removed.

(This page included for two-sided copying.)

Appendix D:
HL7 Messaging for VistA Data Extraction Framework (VDEF)

Important Note
Patch PSO*7*190 should not be installed prior to the site's assigned HDR installation date. Each site will be contacted approximately two weeks prior to the assigned HDR installation date and provided instructions on when and in what order to install this patch and the VDEF V. 1.0 software. Additionally, sites should not configure or attempt to utilize the VDEF software associated with this patch prior to the assigned HDR installation date. Technical Support Office personnel will work with each site to activate that application and start the site's data transmissions to the HDR database. (Information on HDR installation dates can be found by going to the link <http://vaww.teamshare.va.gov/hdr_implementation/> and selecting "Implementation Schedule" from the Quick Launch panel on the left side of the page.)

Please refer to the *VistA Data Extraction Framework (VDEF) Installation & User Configuration Guide* for all technical assistance.

New Protocols
Patch PSO*7*190 adds six new protocols to the PROTOCOL file (#101) to facilitate the VistA Data Extraction Framework (VDEF) Outpatient Pharmacy messaging.

PROTOCOL: (VS = Event Driver protocol, HR = Subscriber protocol)
PSO VDEF RDE O11 OP PHARM PRES VS
PSO VDEF RDE O11 OP PHARM PRES HR

PSO VDEF RDS O13 OP PHARM PPAR VS
PSO VDEF RDS O13 OP PHARM PPAR HR

PSO VDEF RDS O13 OP PHARM PREF VS
PSO VDEF RDS O13 OP PHARM PREF HR

New Application Parameters
Patch PSO*7*190 adds four new HL7 application parameters to the HL7 APPLICATION PARAMETER file (#771):

HDRPPAR is exported as the Sending Application for the PSO VDEF RDS O13 OP PHARM PPAR VS protocol.
HDRPREF is exported as the Sending Application for the PSO VDEF RDS O13 OP PHARM PREF VS protocol.
HDRPRES is exported as the Sending Application for the PSO VDEF RDE O11 OP PHARM PRES VS protocol.
PSO VDEF IE SIDE is exported as the Receiving application for the three Subscriber protocols:
PSO VDEF RDE O11 OP PHARM PRES HR
PSO VDEF RDS O13 OP PHARM PPAR HR
PSO VDEF RDS O13 OP PHARM PREF HR

New Logical Link

There are currently four HL7 logical links (VDEFVIEn) exported with VDEF V. 1.0. The VDEFVIEn links will transmit messages from the local site to the HDR Receiving host system at Austin. VDEFVIE3 is the logical link assigned to Outpatient Pharmacy and it has been added to the HL LOGICAL LINK file (#870).

HL7 Outpatient Pharmacy VDEF Message

When particular events (listed below) occur to a prescription within the Outpatient Pharmacy package, a VDEF request will be queued up at the VDEF Request Queue, with the MessageType, EventType, SubType, and the internal entry number to the PRESCRIPTION file (#52). VDEF will then go through the VDEF Request Queue to generate an HL7 message that contains all of the prescription information and send the message to the Receiving Facility through the VDEFVIE3 Logical Link.

Outpatient Pharmacy VDEF messages will be generated when:

- A new order is entered through the Outpatient Pharmacy options
- A Pending Order from Computerized Patient Record System (CPRS) is finished in the Outpatient Pharmacy options
- A refill is entered for a prescription
- A partial fill for a prescription is entered
- All prescription status changes
- A Prescription is edited and does not create a new order

Example of VDEF HL7 Message

```
MSH^~|\&^HDRPREF^613~TEST.MARTINSBURG.MED.VA.GOV~DNS^PSO VDEF IE
SIDE^200HD~HDR.MED.VA.GOV~DNS^20041216192259-
0500^^RDS~O13^61332594923^T^2.4^^^AL^NE^US
PID^1^1234567890V123456^1234567890V123456~~~USVHA&&0363~NI~VA FACILITY
ID&613&L|000654321~~~USSSA&&0363~SS~VA FACILITY
ID&613&L|1234~~~USVHA&&0363~PI~VA FACILITY
ID&613&L|000654321~~~USVBA&&0363~PN~VA FACILITY
ID&613&L^^LastName~FirstName~M~~~~L^MotherMaidenLastName~~~~~~M^19150511^M^^"
"^HC 11, BOX 22B~""~CAPON
BRIDGE~WV~12345~~P~""|~~BARNESVILLE~MD~~~N^027^(123)555-
1212^""^^D^0^^000654321^^^""^BARNESVILLE MD^^^^^^20000301^^
ORC^RE^^1685567~613_52_.001^^CM^^~~~19950109~19960110~~FILL/EXPIRATION|~~~~19
950109~~ISSUED|~~~19950109~19950330~~DISPENSED/LAST
DISPENSED|~~~~19950629~~CANCEL^^19950109123449-
0500^63~OPPROVIDER40~TWO~~~~~VistA200^^947~OPPROVIDER41~TWO~A~MD~~MD~RE^^^^^6
13~MARTINSBURG VAMC~613_52_20~5005423~MARTINSBURG VAMC~NCPDP
^^^^MARTINSBURG, WV^^^^4500704~DISCONTINUED~99VA_52_100
RXE^1&100MG~~~19950109~19950629~~FILL/CANCEL^4005192~AMANTADINE HCL 100MG
CAP~99VA_52_6~0781-2048-
01~~NDC^0^^20~MG~613_52_6^^^~~~~~WINDOW^^90^^1^^2992~OPPROVIDER42~THREE~M~~~~
PHARMACIST^5430744^^^19950111170823-0500^^^TAKE ONE CAP QD~~613_52_10^D90
RXR^1~ORAL (BY MOUTH)~613_52.0113_6
FT1^^^^19950109^^CG^AMANTADINE~~613_52_39.2^^^^^0.009^^^^^^ONSC
```

```
OBX^1^CE^WAS THE PATIENT COUNSELED^^4500633~YES~99VA_52_41^^^^^^F
OBX^2^CE^WAS COUNSELING UNDERSTOOD^^4500630~NO~99VA_52_42^^^^^^F
NTE^1^^RENEWED FROM RX # 123456^RE~REMARKS~613_52_12
ORC^RF^^1^^^^~~~19950330~~~DISPENSED^~1685567^19950306^^^947~OPPROVIDER41~TWO
~A~MD~~MD~VistA200^^^^REFILL^613~MARTINSBURG
VAMC~613_52.1_8~5005423~MARTINSBURG VAMC~NCPDP^^^^MARTINSBURG, WV
RXE^~~~19950330~~~REFILL^4005192~AMANTADINE HCL 100MG CAP~99VA _52_6~0781-
2048-01~~NDC
^0^^20~MG~613_52_6^^^~~~~~MAIL^^90^^^^2992~OPPROVIDER42~THREE~M~~~~PHARMACIST
^^^^199503290934-0500^^^^D90
ORC^RF^^1^^^^^~1685567^199503061212-
0500^^^947~OPPROVIDER41~TWO~A~MD~~MD~VistA200^^^^PARTIAL^613~MARTINSBURG
VAMC~613_52.2_.09~5005423~MARTINSBURG VAMC~NCPDP^^^^MARTINSBURG, WV
RXE^~~~19950306~~~PARTIAL^4005192~AMANTADINE HCL 100MG CAP~99VA _52_6~0781-
2048-01~~NDC
^0^^20~MG~613_52_6^^^~~~~~WINDOW^^30^^^^2992~OPPROVIDER42~THREE~M~~~~PHARMACI
ST^^^^19950307144822-0500^^^^D30
NTE^^^PT OUT RX ON SUSP FOR 24 MORE DAYS^RE~REMARKS
```

HL7 Outpatient Pharmacy VDEF Message

Some data values in the following table represent VistA data fields that have been assigned VUIDs (VHA Unique Identifiers). In these instances, when a VUID is available, the data value will be the VUID, along with the appropriate coding scheme. If for some reason the VUID is not available, the data value will be the VistA data value, along with the appropriate coding scheme.

The exception to this format would be the data value for the coded element for Give Code in the segment RXE 2. If a VUID is available, the first three pieces would be:

VUID from the VA PRODUCT file (#50.68)
VA PRODUCT Name from the VA PRODUCT file (#50.68)
99VA_52_6

If a VUID is not available, for example if the local drug from the DRUG file (#50) is not matched to the National Drug File, the first three pieces would be:

Null
DRUG Name from the DRUG file (#50)
(Station Number)_52_6

Also in the following table, dosing information is sent in the RXE 1 segment. There are different formats for the dosing information, depending on the type of dosage. Here are examples, which include a possible dosage, a local possible dosage and a possible dosage with complex dosing instructions.

Example 1: This example is for a possible dosage, which is a numeric dosage, with a numeric dispense units per dose. These types of dosages are limited to single ingredient drugs, with a numeric strength, usually with a dosage form of tablets or capsules.

2&200MG~~10D~20050720~20060721~~FILL/EXPIRATION
The dosage in this case is 2&200MG~~10D, where 2 represents the dispense units per dose, 200MG represents the total dosage for the 2 tablets or capsules, and 10D represents the duration, which in this case is 10 days. (duration is optional)

Example 2: This example is for a local possible dosage, which is a text dosage, with no dispense units per dose. These types of dosages apply to items such as multi-ingredient drugs, creams, ointments, drops, etc.

&1 DROP~~~20050720~20060721~~FILL/EXPIRATION
The dosage in this case is &1 DROP~~~, where 1 DROP represents the dosage. Since it is a local possible dosage, there is no dispense units per dose, and in this case there is no duration, though a duration can be applied to any type of dosage.

Example 3: This example is for a possible dosage, with complex dosing instructions.

1&100MG~~10D~20050720~20060721~~FILL/EXPIRATION|2&200MG~~5D
The first set of dosing instructions is 1&100MG~~10D, where 1 represents the dispense units per dose, 100MG represents the total dosage, and 10D represents a duration of 10 Days. The next set of dosing instructions is 2&200MG~~5D, where 2 represents the dispense units per dose, 200MG represents the total dosage, and 5D represents a duration of 5 Days.

NOTE: The dosage will only appear in the RXE segment associated with the original fill, it will not appear in RXE segments associated with refills or partial fills.

Example of VDEF HL7 Message Details

Segment	Piece/ Sequence	Description/ Field Name	Data Type	Data Value
MSH	1	Field Separator	ST	^
MSH	2	Encoding Characters	ST	~|\&
MSH	3	Sending Application	HD	HDRPREF
MSH	4	Sending Facility	HD	613~TEST.MARTINSBURG.MED.VA.GOV~DNS
MSH	5	Receiving Application	HD	PSO VDEF IE SIDE
MSH	6	Receiving Facility	HD	200HD~HDR.MED.VA.GOV~DNS
MSH	7	Date/Time Of Message	TS	20041216192259-0500
MSH	8	Security	ST	
MSH	9	Message Type	CM	RDS~O13
MSH	10	Message Control ID	ST	61332594923
MSH	11	Processing ID	PT	T
MSH	12	Version ID	VID	2.4
MSH	13	Sequence Number	NM	
MSH	14	Continuation Pointer	ST	
MSH	15	Accept Acknowledgment Type	ID	AL
MSH	16	Application Acknowledgment Type	ID	NE
MSH	17	Country Code	ID	US
MSH	18	Character Set	ID	
MSH	19	Principal Language Of Message	CE	
MSH	20	Alternate Character Set Handling Scheme	ID	
MSH	21	Conformance Statement ID	ID	
PID	1	Set ID - PID	SI	1
PID	2	Patient ID	CX	1234567890V123456
PID	3	Patient Identifier List	CX	1234567890V123456~~~USVHA&&0363~NI~VA FACILITY ID&613&L
PID	3	Patient Identifier List_rep		000654321~~~USSSA&&0363~SS~VA FACILITY ID&613&L

Segment	Piece/ Sequence	Description/ Field Name	Data Type	Data Value
PID	3	Patient Identifier List_rep		1234~~~USVHA&&0363~PI~VA FACILITY ID&613&L
PID	3	Patient Identifier List_rep		000654321~~~USVBA&&0363~PN~VA FACILITY ID&613&L
PID	4	Alternate Patient ID - PID	CX	
PID	5	Patient Name	XPN	LastName~FirstName~M~~~~L
PID	6	Mother's Maiden Name	XPN	MotherMaidenLastName~~~~~~~M
PID	7	Date/Time Of Birth	TS	19150511
PID	8	Administrative Sex	IS	M
PID	9	Patient Alias	XPN	
PID	10	Race	CE	""
PID	11	Patient Address	XAD	HC 11, BOX 22B~""~CAPON BRIDGE~WV~12345~~P~""
PID	11	Patient Address_rep		~~BARNESVILLE~MD~~~N
PID	12	County Code	IS	027
PID	13	Phone Number - Home	XTN	(123)555-1212
PID	14	Phone Number - Business	XTN	""
PID	15	Primary Language	CE	
PID	16	Marital Status	CE	D
PID	17	Religion	CE	0
PID	18	Patient Account Number	CX	
PID	19	SSN Number - Patient	ST	654321
PID	20	Driver's License Number - Patient	DLN	
PID	21	Mother's Identifier	CX	
PID	22	Ethnic Group	CE	""
PID	23	Birth Place	ST	BARNESVILLE MD
PID	24	Multiple Birth Indicator	ID	
PID	25	Birth Order	NM	
PID	26	Citizenship	CE	
PID	27	Veterans Military Status	CE	
PID	28	Nationality	CE	
PID	29	Patient Death Date and Time	TS	20000301

Segment	Piece/ Sequence	Description/ Field Name	Data Type	Data Value
PID	30	Patient Death Indicator	ID	
PID	31	Identity Unknown Indicator	ID	
PID	32	Identity Reliability Code	IS	
PID	33	Last Update Date/Time	TS	
PID	34	Last Update Facility	HD	
PID	35	Species Code	CE	
PID	36	Breed Code	CE	
PID	37	Strain	ST	
PID	38	Production Class Code	CE	
ORC	1	Order Control	ID	RE
ORC	2	Placer Order Number	EI	
ORC	3	Filler Order Number	EI	1685567~613_52_.001
ORC	4	Placer Group Number	EI	
ORC	5	Order Status	ID	CM
ORC	6	Response Flag	ID	
ORC	7	Quantity/ Timing	TQ	~~~19950109~19960110~~FILL/EXPIRATION
ORC	7	Quantity/ Timing_rep		~~~~19950109~~ISSUED
ORC	7	Quantity/ Timing_rep		~~~19950109~19950330~~DISPENSED/LAST DISPENSED
ORC	7	Quantity/ Timing_rep		~~~~19950629~~CANCEL
ORC	8	Parent	CM	
ORC	9	Date/Time of Transaction	TS	19950109123449-0500
ORC	10	Entered By	XCN	63~OPPROVIDER40~TWO~~~~~VistA200
ORC	11	Verified By	XCN	
ORC	12	Ordering Provider	XCN	947~OPPROVIDER41~TWO~A~MD~~MD~RE
ORC	13	Enterer's Location	PL	
ORC	14	Call Back Phone Number	XTN	
ORC	15	Order Effective Date/Time	TS	
ORC	16	Order Control Code Reason	CE	

Segment	Piece/ Sequence	Description/ Field Name	Data Type	Data Value
ORC	17	Entering Organization	CE	613~MARTINSBURG VAMC~613_52_20~5005423~MARTINSBURG VAMC~NCPDP
ORC	18	Entering Device	CE	
ORC	19	Action By	XCN	
ORC	20	Advanced Beneficiary Notice Code	CE	
ORC	21	Ordering Facility Name	XON	MARTINSBURG, WV
ORC	22	Ordering Facility Address	XAD	
ORC	23	Ordering Facility Phone Number	XTN	
ORC	24	Ordering Provider Address	XAD	
ORC	25	Order Status Modifier	CWE	4500704~DISCONTINUED~99VA_52_100 **OR** 12~DISCONTINUED~613_52_100
RXE	1	Quantity/Timing	TQ	1&100MG~~~19950109~19950629~~FILL/CANCEL
RXE	2	Give Code	CE	4005192~AMANTADINE HCL 100MG CAP~99VA_52_6~0781-2048-01~~NDC **OR** ~AMANTADINE 100MG CAP~613_52_6~0781-2048-01~~NDC
RXE	3	Give Amount - Minimum	NM	0
RXE	4	Give Amount - Maximum	NM	
RXE	5	Give Units	CE	20~MG~613_52_6
RXE	6	Give Dosage Form	CE	
RXE	7	Provider's Administration Instructions	CE	
RXE	8	Deliver-To Location	CM	~~~~~WINDOW
RXE	9	Substitution Status	ID	
RXE	10	Dispense Amount	NM	90
RXE	11	Dispense Units	CE	
RXE	12	Number of Refills	NM	1
RXE	13	Ordering Provider's DEA Number	XCN	

Segment	Piece/ Sequence	Description/ Field Name	Data Type	Data Value
RXE	14	Pharmacist/Treatment Supplier's Verifier ID	XCN	2992~OPPROVIDER42~THREE~M~~~~ PHARMACIST
RXE	15	Prescription Number	ST	5430744
RXE	16	Number of Refills Remaining	NM	
RXE	17	Number of Refills/Doses Dispensed	NM	
RXE	18	D/T of Most Recent Refill or Dose Dispensed	TS	19950111170823-0500
RXE	19	Total Daily Dose	CQ	
RXE	20	Needs Human Review	ID	
RXE	21	Pharmacy/Treatment Supplier's Special Dispensing Instructions	CE	TAKE ONE TAB QD~~613_52_10
RXE	22	Give Per (Time Unit)	ST	D90
RXE	23	Give Rate Amount	ST	
RXE	24	Give Rate Units	CE	
RXE	25	Give Strength	NM	
RXE	26	Give Strength Units	CE	
RXE	27	Give Indication	CE	
RXE	28	Dispense Package Size	NM	
RXE	29	Dispense Package Size Unit	CE	
RXE	30	Dispense Package Method	ID	
RXE	31	Supplementary Code	CE	
RXR	1	Route	CE	1~ORAL (BY MOUTH)~613_52.0113_6
RXR	2		CE	
RXR	3		CE	
RXR	4		CE	
RXR	5		CE	
FT1	1	Set ID - FT1	SI	
FT1	2	Transaction ID	ST	

Segment	Piece/ Sequence	Description/ Field Name	Data Type	Data Value
FT1	3	Transaction Batch ID	ST	
FT1	4	Transaction Date	TS	19950109
FT1	5	Transaction Posting Date	TS	
FT1	6	Transaction Type	IS	CG
FT1	7	Transaction Code	CE	AMANTADINE~~613_52_39.2
FT1	8	Transaction Description	ST	
FT1	9	Transaction Description - Alt	ST	
FT1	10	Transaction Quantity	NM	
FT1	11	Transaction Amount - Extended	CP	
FT1	12	Transaction Amount - Unit	CP	0.009
FT1	13	Department Code	CE	
FT1	14	Insurance Plan ID	CE	
FT1	15	Insurance Amount	CP	
FT1	16	Assigned Patient Location	PL	
FT1	17	Fee Schedule	IS	
FT1	18	Patient Type	IS	ONSC
FT1	19	Diagnosis Code - FT1	CE	
FT1	20	Performed By Code	XCN	
FT1	21	Ordered By Code	XCN	
FT1	22	Unit Cost	CP	
FT1	23	Filler Order Number	EI	
FT1	24	Entered By Code	XCN	
FT1	25	Procedure Code	CE	
FT1	26	Procedure Code Modifier	CE	
OBX	1	Set ID - OBX	SI	1
OBX	2	Value Type	ID	CE
OBX	3	Observation Identifier	CE	WAS THE PATIENT COUNSELED
OBX	4	Observation Sub-Id	ST	
OBX	5	Observation Value	CE	4500633~YES~99VA_52_41 **OR** 1~YES~613_52_41
OBX	6	Units	CE	

Segment	Piece/ Sequence	Description/ Field Name	Data Type	Data Value
OBX	7	References Range	ST	
OBX	8	Abnormal Flags	IS	
OBX	9	Probability	NM	
OBX	10	Nature of Abnormal Test	ID	
OBX	11	Observation Result Status	ID	F
OBX	12	Date Last Observation Normal Value	TS	
OBX	13	User Defined Access Checks	ST	
OBX	14	Date/Time of the Observation	TS	
OBX	15	Producer's ID	CE	
OBX	16	Responsible Observer	XCN	
OBX	17	Observation Method	CE	
OBX	18	Equipment Instance Identifier	EI	
OBX	19	Date/Time of the Analysis	TS	
OBX	1	Set ID - OBX	SI	2
OBX	2	Value Type	ID	CE
OBX	3	Observation Identifier	CE	WAS COUNSELING UNDERSTOOD
OBX	4	Observation Sub-Id	ST	
OBX	5	Observation Value	CE	4500630~NO~99VA_52_42 **OR** 0~NO~613_52_42
OBX	6	Units	CE	
OBX	7	References Range	ST	
OBX	8	Abnormal Flags	IS	
OBX	9	Probability	NM	
OBX	10	Nature of Abnormal Test	ID	
OBX	11	Observation Result Status	ID	F
OBX	12	Date Last Observation Normal Value	TS	
OBX	13	User Defined Access Checks	ST	

Segment	Piece/ Sequence	Description/ Field Name	Data Type	Data Value
OBX	14	Date/Time of the Observation	TS	
OBX	15	Producer's ID	CE	
OBX	16	Responsible Observer	XCN	
OBX	17	Observation Method	CE	
OBX	18	Equipment Instance Identifier	EI	
OBX	19	Date/Time of the Analysis	TS	
NTE	1	Set ID - NTE	SI	1
NTE	2	Source of Comment	ID	
NTE	3	Comment	FT	RENEWED FROM RX # 123456
NTE	4	Comment Type	CE	RE~REMARKS~613_52_12
ORC	1	Order Control	ID	RF
ORC	2	Placer Order Number	EI	
ORC	3	Filler Order Number	EI	1
ORC	4	Placer Group Number	EI	
ORC	5	Order Status	ID	
ORC	6	Response Flag	ID	
ORC	7	Quantity/Timing	TQ	~~~19950330~~~DISPENSED
ORC	8	Parent	CM	~1685567
ORC	9	Date/Time of Transaction	TS	19950306
ORC	10	Entered By	XCN	
ORC	11	Verified By	XCN	
ORC	12	Ordering Provider	XCN	947~OPPROVIDER41~TWO~A~MD~~MD~VistA200
ORC	13	Enterer's Location	PL	
ORC	14	Call Back Phone Number	XTN	
ORC	15	Order Effective Date/Time	TS	
ORC	16	Order Control Code Reason	CE	REFILL
ORC	17	Entering Organization	CE	613~MARTINSBURG VAMC~613_52.1_8~5005423~MARTINSBURG VAMC~NCPDP
ORC	18	Entering Device	CE	
ORC	19	Action By	XCN	

Segment	Piece/ Sequence	Description/ Field Name	Data Type	Data Value
ORC	20	Advanced Beneficiary Notice Code	CE	
ORC	21	Ordering Facility Name	XON	MARTINSBURG, WV
ORC	22	Ordering Facility Address	XAD	
ORC	23	Ordering Facility Phone Number	XTN	
ORC	24	Ordering Provider Address	XAD	
ORC	25	Order Status Modifier	CWE	
RXE	1	Quantity/Timing	TQ	~~~19950330~~~REFILL
RXE	2	Give Code	CE	4005192~AMANTADI NE HCL 100MG CAP~99VA_52_6~0781-2048-01~~NDC **OR** ~AMANTADINE 100MG CAP~613_52_6~0781-2048-01~~NDC
RXE	3	Give Amount - Minimum	NM	0
RXE	4	Give Amount - Maximum	NM	
RXE	5	Give Units	CE	20~MG~613_52_6
RXE	6	Give Dosage Form	CE	
RXE	7	Provider's Administration Instructions	CE	
RXE	8	Deliver-To Location	CM	~~~~~MAIL
RXE	9	Substitution Status	ID	
RXE	10	Dispense Amount	NM	90
RXE	11	Dispense Units	CE	
RXE	12	Number of Refills	NM	
RXE	13	Ordering Provider's DEA Number	XCN	
RXE	14	Pharmacist/Treatment Supplier's Verifier ID	XCN	2992~OPPROVIDER42~THREE~M~~~~ PHARMACIST
RXE	15	Prescription Number	ST	
RXE	16	Number of Refills Remaining	NM	
RXE	17	Number of Refills/Doses Dispensed	NM	

Segment	Piece/ Sequence	Description/ Field Name	Data Type	Data Value
RXE	18	D/T of Most Recent Refill or Dose Dispensed	TS	199503290934-0500
RXE	19	Total Daily Dose	CQ	
RXE	20	Needs Human Review	ID	
RXE	21	Pharmacy/Treatment Supplier's Special Dispensing Instructions	CE	
RXE	22	Give Per (Time Unit)	ST	D90
RXE	23	Give Rate Amount	ST	
RXE	24	Give Rate Units	CE	
RXE	25	Give Strength	NM	
RXE	26	Give Strength Units	CE	
RXE	27	Give Indication	CE	
RXE	28	Dispense Package Size	NM	
RXE	29	Dispense Package Size Unit	CE	
RXE	30	Dispense Package Method	ID	
RXE	31	Supplementary Code	CE	
ORC	1	Order Control	ID	RF
ORC	2	Placer Order Number	EI	
ORC	3	Filler Order Number	EI	1
ORC	4	Placer Group Number	EI	
ORC	5	Order Status	ID	
ORC	6	Response Flag	ID	
ORC	7	Quantity/Timing	TQ	
ORC	8	Parent	CM	~1685567
ORC	9	Date/Time of Transaction	TS	199503061212-0500
ORC	10	Entered By	XCN	
ORC	11	Verified By	XCN	
ORC	12	Ordering Provider	XCN	947~OPPROVIDER41~TWO~A~MD~~MD~VistA200
ORC	13	Enterer's Location	PL	
ORC	14	Call Back Phone Number	XTN	
ORC	15	Order Effective Date/Time	TS	

Segment	Piece/ Sequence	Description/ Field Name	Data Type	Data Value
ORC	16	Order Control Code Reason	CE	PARTIAL
ORC	17	Entering Organization	CE	613~MARTINSBURG VAMC~613_52.2_.09~5005423~MARTINSBURG VAMC~NCPDP
ORC	18	Entering Device	CE	
ORC	19	Action By	XCN	
ORC	20	Advanced Beneficiary Notice Code	CE	
ORC	21	Ordering Facility Name	XON	MARTINSBURG, WV
ORC	22	Ordering Facility Address	XAD	
ORC	23	Ordering Facility Phone Number	XTN	
ORC	24	Ordering Provider Address	XAD	
ORC	25	Order Status Modifier	CWE	
RXE	1	Quantity/Timing	TQ	~~~19950306~~~PARTIAL
RXE	2	Give Code	CE	4005192~AMANTADINE HCL 100MG CAP~99VA_52_6~0781-2048-01~~NDC **OR** ~AMANTADINE 100MG CAP~613_52_6~0781-2048-01~~NDC
RXE	3	Give Amount - Minimum	NM	0
RXE	4	Give Amount - Maximum	NM	
RXE	5	Give Units	CE	20~MG~613_52_6
RXE	6	Give Dosage Form	CE	
RXE	7	Provider's Administration Instructions	CE	
RXE	8	Deliver-To Location	CM	~~~~~WINDOW
RXE	9	Substitution Status	ID	
RXE	10	Dispense Amount	NM	30
RXE	11	Dispense Units	CE	
RXE	12	Number of Refills	NM	
RXE	13	Ordering Provider's DEA Number	XCN	
RXE	14	Pharmacist/Treatment Supplier's Verifier ID	XCN	2992~OPPROVIDER42~THREE~M~~~~PHARMACIST

Segment	Piece/ Sequence	Description/ Field Name	Data Type	Data Value
RXE	15	Prescription Number	ST	
RXE	16	Number of Refills Remaining	NM	
RXE	17	Number of Refills/Doses Dispensed	NM	
RXE	18	D/T of Most Recent Refill or Dose Dispensed	TS	19950307144822-0500
RXE	19	Total Daily Dose	CQ	
RXE	20	Needs Human Review	ID	
RXE	21	Pharmacy/Treatment Supplier's Special Dispensing Instructions	CE	
RXE	22	Give Per (Time Unit)	ST	D30
RXE	23	Give Rate Amount	ST	
RXE	24	Give Rate Units	CE	
RXE	25	Give Strength	NM	
RXE	26	Give Strength Units	CE	
RXE	27	Give Indication	CE	
RXE	28	Dispense Package Size	NM	
RXE	29	Dispense Package Size Unit	CE	
RXE	30	Dispense Package Method	ID	
RXE	31	Supplementary Code	CE	
NTE	1	Set ID - NTE	SI	
NTE	2	Source of Comment	ID	
NTE	3	Comment	FT	PT OUT RX ON SUSP FOR 24 MORE DAYS
NTE	4	Comment Type	CE	RE~REMARKS

Index

A

Archiving and Purging 17

B

Barcodes and Label Printer Support 45
Barcodes on Dot Matrix Printers 45

C

Callable Routines 19
Communication Protocol 61
Control Code Entries, Samples 49
Control Codes in use by Laser Labels 52

D

Data Base Integration Agreements 27
Data South 220 47
Dot Matrix Labels 46
Dot Matrix Printers and Barcodes 45

E

Electronic Signatures 33
Exported Options 15
External Interfaces 19
External Relations 27

F

Field Rules 60
File Security 35
Files 11

G

General Information 59
Genicom 4440 47
Genicom 4490 48

H

Hardware Setup, Laser Label Printers 48
HL7 Messaging for Transitional Pharmacy Benefit Extract 79
HL7 Messaging with an External System 71
HL7 Order Message Segment Definition Table 72
HL7 Schedule Information Unsolicited (SIU) Table 81

I

Implementation and Maintenance 5
Interfacing 33
Internal Relations 29
Introduction 1

J

Journaling Globals 45

L

Label Printer Support 45
Laser Label Control Codes 52
Laser Label Printers 48
Laser Label Printers, Hardware Setup 48

M

M Audiofax (Telephone Refill Requests) 7
Mail Group Setup for the HL7 External Interface 8, 33
Menu Assignments 15, 33
Menu Diagrams 37
Message Rules 59
MT290 47
MT-661 47

N

New Label Stock (Version 6.0 and Later Versions) 46

O

Online Documentation 3
Options to be Deleted during Installation 6
Order Messaging Exceptions 76
Orientation 3
OTC 560 47
Outpatient Pharmacy Files 11
Outpatient Pharmacy HL7 Interface Specifications 59
Outpatient Pharmacy Manager Menu 37
Outpatient Pharmacy V. 7.0 Menu Diagrams 37

P

Package Security 16
Package-Wide Variables 29
Pharmacist Menu 41
Pharmacy Technician's Menu 42
Print Queue Setup, VMS 51
Processing Rules 61

Q

Queue Background Jobs 9

R

Related Manuals..... 3
Resource Requirements 5
Routine List..... 13
Routine Mapping 45
Routines to be Deleted during Installation..... 7

S

ScripTalk® Printers 54
Security Keys 15, 34
Segment Rules 60
Setting up the Archive Device 17
Setting up the Bingo Board Device 8
Setting Up the Interface 20
Shutting Down the Interface 22
Software Product Security 33
Specific Transaction..... 62, 69, 73
Standalone Options 43
Steps for Setup/Shutdown of the External Interface..... 19

T

Telephone Refill Requests 7
Templates..... 31
Templates to be Deleted during Installation 7
Transaction Specifications..... 61

U

Using the Maintenance Menu 8

V

VDEF 89
View of Queue Background Jobs Screen..... 10
VMS Print Queue Setup..... 51
VUID..... 91

(This page included for two-sided copying.)