



BARCODE MEDICATION ADMINISTRATION (BCMA)

BCMA Backup System (BCBU)

INSTALLATION GUIDE

PSB*3*108

Version 3.0

July 2021

Acknowledgments

The Bar Code Administration - Enterprise Tactical Support Team (National VistA Support Team) would like to extend the following acknowledgements to:

REDACTED and **REDACTED** of the New Jersey Health Care System.

The Bar Code Medication Administration Backup System (BCBU) has been based on their original conceptual model and retains many of the ideas implemented in the Class III plan. Their hard work and determination has led the way for us to provide all VA Medical Centers with a viable BCMA Contingency Plan.

REDACTED of VA Medical Center San Francisco, California.

His knowledge of the VistA HL7 package and work on the security portion of the Bar Code Medication Administration Backup System (BCBU) made it possible for the Class I acceptance of the package.

Revision History

Each time this manual is updated, the Title Page lists the new revised date and this page describes the changes. If the Revised Pages column lists “All”, replace the existing manual with the reissued manual. If the Revised Pages column lists individual entries (e.g., 25, 32), either update the existing manual with the Change Pages Document or print the entire new manual.

Date	Revised Pages	Patch Number	Description
7/2021	i 9 42	PSB*3*108	Added notifications to the Medication Administration Record (MAR) reports for hazardous to handle and hazardous to dispose drugs.
9/2016	i-iv 9 39 42	PSB*3*87	Updated revision history, table of contents. Removed repeating headers. Added data dictionary changes for Transdermal. Added updates to the List/Display Orders section. Added BCBU MAR (Medical Administration Record) Report. REDACTED
1/2014	i-iv , 5 , 10-11 , 12 , 12a- 12b , 13- 14 , 19- 21 , 21a- 21b , 22-23 , 25 , 31 , 44-44a , 45-46 , 48 , 48a- 48d	PSB*3*73	This patch will enhance the BCMA Backup System (BCBU) to support Clinic Orders. The Backup System will be able to store a Clinic name, per each order, for orders associated with clinic locations. The existing MAR reports will now print the clinic name along with the order under a heading label of "Location". The word "INPATIENT" will also print under the “Location” heading for Inpatient Medication orders, which are associated with the ward, of patients that are admitted. This patch will add two new menu options to support the printing of MAR reports for Selected Clinic or All Clinics. REDACTED
11/2013	42-46	PSB*3*59	Patients with no current medication orders are now printed consistently on the three BCBU MAR reports (Print MAR for All Wards, Print MAR for Selected Patient, and Print MAR for Selected Ward). The patient’s information is followed by a message stating “No Active Medication Orders were reported to the Contingency at the time the MAR was printed”, followed by multiple blank lines and a footer. Also, a blank page is no longer used as a separator on the Print MAR for a Selected Ward (PW) and the Print MAR for All Wards (PA).

			<p>On both the Print MAR for a Selected Ward (PW) and the Print MAR for All Wards (PA) menus, after the question 'Report [A]LL or [C]URRENT orders?' has been answered 'CURRENT', a prompt appears, 'Include Patients without Active Medications?' (defaults to 'Yes'). Answering 'No' prevents current patients without medications from printing on the report.</p> <p>REDACTED</p>
--	--	--	--

Date	Revised Pages	Patch Number	Description
09/2012	i, 44, 44a-44b	PSB*3*69	<p>The Special Instructions and Other Print Info project changed these comment type fields to unlimited word processing text. This text is sent over in the same NTE segment as before. BCBU has been enhanced to receive and store the unlimited word processing text and print the word processing lines of text on the MAR reports as they were typed and stored in the Inpatient Order.</p> <p>REDACTED</p>
03/2006	All	PSB*3*8	<p>Document reissued for significant enhancements and issue resolution.</p> <p>See patch description for details.</p> <p>REDACTED</p>
08/2003			<p>Original Released Bar Code Medication Administration Backup System (BCBU) Installation Guide.</p>

Table of Contents

Department of Veterans Affairs	1
Product Development	1
BCMA V. 3.0 and This Guide	1
Benefits of BCMA	1
Benefits of This Guide	1
Our Target Audience	1
This Manual Includes	2
Other Sources of Information	2
Conventions Used in This Guide	2
Locating Detailed Listings	4
Routines	4
Data Dictionaries	4
Interface Software	4
Alerts	4
BCMA Menus	5
Security Information	6
Mail Group	6
Remote Systems	6
Archiving/Purging	6
Contingency Planning	6
Menus	6
Security Keys	6
References	6
Pre-Installation Information	7
Recommended Users	7
VistA Operating System and Performance Capacity	7
Central Processing Unit (CPU) Requirements	7
Test Sites	8
Minimum Required Packages	8
Installation Time Estimates	8
Required Patches	8
Users on the System	8
Options Out of Order	8
Namespace	9
Data Dictionary Changes	9
Resource Requirements	9
Printers	10
Routines Installed	10
Installation Information	11
VistA Server Installation Instructions	11
PC Workstation Database Initialization	11
MAR Reports	11
BCMA Backup System (BCBU) InterSystems Cache Installation Setup	12

BCMA Backup System (BCBU) Linux Installation Setup	12
Sample Installation	13
Sample PC Workstation Database Initialization	15
Technical Information.....	19
Option Descriptions	19
HL7 Parameters.....	22
PSB BCBU CLIENT.....	22
PSB BCBU SERVER	22
PSB PMU SEND.....	22
HL7 Message Examples.....	22
Unit Dose Orders.....	22
IV Orders.....	23
Med Log.....	23
Parameter Definitions.....	24
PSB BKUP DEFAULT	24
PSB BKUP MACHINES	24
PSB BKUP ONLINE	25
PSB BKUP IPH.....	25
PSB BKUP MEDLG.....	25
PSB BKUP DOM FILTER	25
List Templates.....	26
PSB ERROR LOG	26
PSB SELECT ORDERS	26
PSB SELECT PATIENT	27
PSB SHOW ORDERS	28
HL Communication Server Parameters.....	28
Files Associated with GT.M/Linux BCMA:	29
Adding a BCMA printer to the Cache/NT Contingency system:.....	30
Contingency Workstation (VistA) printer:.....	30
From within Contingency Workstation (VistA) Printer.....	31
Adding a BCMA printer to the GT.M/Linux Contingency system:.....	32
Contingency Workstation (VistA)	32
From within Contingency Workstation (VistA).....	32
From within Contingency Workstation (VistA).....	34
Workstation Queued Tasks	35
Quick Reference Installation Checklist	37
Contingency PC Workstation Reports	39
List/Display Orders	39
BCBU MAR (Medical Administration Record) Report	42
Print MAR for All Wards.....	43
Print MAR for Selected Patient.....	46
Print MAR for Selected Ward.....	47
Print MAR for All Clinics.....	47
Print MAR for Selected Clinic.....	49
Print Blank MAR for Selected Patient.....	50
Blank 3 Day MAR for Selected Patient	50
Blank 7 Day MAR for Selected Patient	53
List of Wards in BCMA Backup File	53

Trouble Shooting Guide 55

BCMA V. 3.0 and This Guide

Benefits of BCMA

The Veterans Health Information Systems and Technology Architecture (VistA) Bar Code Medication Administration Backup System (BCBU) software will provide a Class I solution to the BCMA Contingency IRA #20020403. This plan reflects the intent of VHA Directive #6210, the Automated Information Systems (AIS) Security, which states that all facilities are responsible for the development, maintenance, and annual testing of individual AIS contingency. This software maintains a current copy on the designated workstation, of all the inpatient pharmacy activities including the inpatient medication orders, medication administrations, and allergies that are included on a Pharmacy Medication Administration Record (MAR).

The Bar Code Medication Administration Backup System (BCBU) will interface with the BCMA VistA product to provide a real-time backup of all inpatient medication activities on a designated workstation(s). Designated workstation(s) will contain current information regarding inpatient medication orders (Unit Dose and IV), medication administration record (MAR), medication administration history (MAH), and patient allergies. Workstation(s) are updated using the VA Health Level Seven (HL7) package. These workstation(s) are available for use according to local policies concerning VistA, BCMA, or network outages.

Benefits of This Guide

The Veterans Health Information Systems and Technology Architecture (VistA) Bar Code Medication Administration Backup System (BCBU) Installation provides detailed instructions required for installing and implementing this new software. Additional manuals are available with instructions for installing and implementing the new software on either a Linux or Caché workstation environment.

Our Target Audience

This guide was developed for the following individuals, who are responsible for the installation, maintenance, support, and use of the package.

- Information Resources Management (IRM)
- Clinical Application Coordinator (CAC) – called Applications Package Coordinator (ADPAC) at some sites
- National VistA Support (NVS)
- Independent Verification and Validation (IV&V)

This Manual Includes

Security Information: This section contains information regarding the mail group, alerts, and file security associated with the Bar Code Medication Administration Backup System (BCBU) software.

Pre-Installation Information: This section provides information needed prior to installing the Bar Code Medication Administration Backup System (BCBU) software.

Installation Information: This section contains instructions and examples of the Bar Code Medication Administration Backup System (BCBU) software.

Technical Information: This section provides information on protocols involved in the Bar Code Medication Administration Backup System (BCBU) software.

Other Sources of Information



TIP:
Bookmark these sites for future reference.

For more background and technical information about BCMA V. 3.0, refer to the Web sites listed below.

Background/Technical Information

To access the BCMA Home page, enter **REDACTED** in the Address field of your browser. The BCMA Backup System Installation Guide can be accessed from the VA Software Document Library (VDL) at <http://www.va.gov/vdl>. The document is available in MS Word (.doc) format and Adobe Portable Document Format (.PDF).

Conventions Used in This Guide

Before installing BCBU patches, review this section to learn the many conventions used throughout this guide.

- **Keyboard Responses:** Keys provided in boldface, within the steps, help you quickly identify what to press on your keyboard to perform an action. See the examples provided below.
 - **Within the Steps:** At the "Select Kernel Installation & Distribution System Option" prompt, type **INSTALL**, and then press **ENTER**.
 - **Within Screen Captures:** Text in **boldface**, centered between arrows on screen captures, identifies the key you must press for the system to capture your response or to move the cursor to the next field. See the following example.

DEVICE FOR QUEUED JOB OUTPUT: <**Enter**>

- **Mouse Responses:** Buttons provided in **boldface**, within the steps, indicate what you should click on your computer screen using the mouse. For example, when you see **NEXT**, **YES/NO**, or **OK** in the steps, click the appropriate button on your computer screen.
- **User Responses:** Information presented in **boldface**, within steps or shaded screen captures, indicate what you should "type" (enter) onto your computer screen. See the examples provided below.
 - **Within the Steps:** At the "Select OPTION NAME" prompt, type **XPD MAIN** and then press **ENTER**.
 - **Within Screen Captures:** See the following example.

Conventions Used in This Guide (cont.)

RESCHEDULING FREQUENCY: **1M**

- **Screen Captures:** Provide "shaded" examples of what you will see on your computer screen, and possible user responses.
- **Notes:** Provided within the steps, describe exceptions or special cases about the information presented. They reflect the experience of our Staff, Developers, and Testers.
- **Menu Options:** When provided in italics, identifies a menu option. When provided in boldface, ALL CAPS, identifies the letters that you should type onto your computer screen, before pressing ENTER. The system then goes directly to the menu option. (Note: The letters do not have to be entered as capital letters, even though they are provided within the steps in this format.) See the examples provided below.
 - **Italicized:** Use the Kernel *First Line Routine Print* option to print a list containing the first line of every PSB routine.
 - **Capitalized:** At the "TaskMan Management Option:" prompt, type **Schedule/Unscheduled Options**, and then press ENTER.

Locating Detailed Listings

You can obtain and print listings about routines and Data Dictionaries using the information provided below.

Routines

Use the Kernel routine XINDEX to produce detailed listings of routines. Use the Kernel *First Line Routine Print* option to print a list containing the first line of every ALPB routine.

Data Dictionaries

The Data Dictionaries (DDs) are included in the on-line documentation for this software application. You can use the VA FileMan *List File Attributes* option, under *Data Dictionary Utilities* option, to print the Dictionaries. Journaling is not recommended for the ALPB global.

Interface Software

The interface software is HL7. This will transmit the pharmacy data to the designated workstation.

Alerts

The mail group, PSB BCBU ERRORS, will receive all alerts.

BCMA Menus

Bar Code Medication Administration Backup System (BCBU) software two main menus listed below. The options for each menu are listed in this section.

- BCMA Backup System (Wrkstn)
[PSB BCBU WRKSTN MAIN]
- BCMA Backup System (VistA)
[PSB BCBU VistA MAIN]

BCMA Backup System (Wrkstn)

This menu includes the following options:

- List/Display Orders
- Print MAR for All Wards
- Print MAR for Selected Patient
- Print MAR for Selected Ward
- Print MAR for All Clinics
- Print MAR for Selected Clinics
- Print Blank MAR for Selected Patient
- List of Wards in BCMA Backup File
- BCMA Backup System Management Menu
 - *BCMA Backup System Error Log*
 - *Edit Workstation Parameter Settings*
 - *Purge Orders Past X days old*

BCMA Backup System (VistA)

This menu includes the following options:

- Associate Backup Workstations with a Division
- Default Workstation Initialize
- Divisional Workstation Initialize
- Initialize a Backup Workstation with BCMA Users
- Single Patient Init

Security Information

Mail Group	The PSB BCBU Errors Mail Group is used to notify responsible users of potential problems with sending information to the Contingency Workstation(s). Members of this group should include the staff that monitors the BCMA Backup System.
Remote Systems	The workstation where the software resides is the only remote system that will receive any data.
Archiving/Purging	The product purges itself and only keeps active inpatient data. The journal files are flipped and purged nightly so disk space is not consumed by journaling.
Contingency Planning	This contingency plan software can be used if there is a VistA outage. The sites can use the data stored on the workstations using the outputs on the menu supplied.
Menus	There are two menus for use with this package, BCMA Backup System (Wrkstn) and BCMA Backup System (VistA). The BCMA Backup System Management Menu is under the first menu and requires a Security Key as described below.
Security Keys	The BCMA Backup System Management Menu is secured by the security key, PSB BUMGR and MUST be assigned to the designated IRM personnel who currently manage the system for total access to the Bar Code Medication Administration Backup System.
References	Kernel Systems Manual V. 8.0 Kernel Toolkit V. 7.3 VA FileMan V. 22.0 MailMan V. 8.0 Health Level Seven (HL7) V. 1.6

Pre-Installation Information

Recommended Users

Information Resource Management (IRM) Staff is recommended for installing, implementing and supporting the Bar Code Medication Administration Backup System (BCBU). IRM, Pharmacy, and Nursing staff must coordinate the implementation of the setup tasks after the package is installed.

VistA Operating System and Performance Capacity

VistA Bar Code Medication Administration Backup System (BCBU) currently runs on the standard hardware platforms used by the Department of Veterans Affairs Health Care System facilities. These hardware platforms consist of standard or upgraded Alpha 4100, ES40, or ES45 clusters, and run either DSM on VMS, Caché/VMS, Caché/NT, or CachéXP. There are no significant changes in the performance capacity of the VistA operating system once the VistA Bar Code Medication Administration Backup System (BCBU) has been installed. The software application should not create any appreciable global growth or network transmission problems. There are no memory constraints.

Central Processing Unit (CPU) Requirements

The following workstation configuration is recommended for installing and running the VistA Bar Code Medication Administration Backup System (BCBU).

Sites previously using the New Jersey Class III package should be able to use current workstations and Caché license.

Hardware

- 1-2 Ghz CPU
- 256-512 Mb RAM
- 20 Gb hard drive
- Monitor
- Printer

Central Processing Unit (CPU) Requirements (cont.)

Software

- Microsoft Windows XP, Windows 2000 or Windows NT with Intersystems Cache 5.x.x (4.1.4), (3.2.1) 20 user License
- or
- RedHat Linux 8.0 with Greystone GT.M

Test Sites

VistA BCBU software was tested at the following VA Sites and platforms prior to being released:

REDACTED

Minimum Required Packages

Before installing BCBU PSB*3*8, make sure that your VistA system includes the following Department of Veterans Affairs (VA) software packages and versions (those listed or higher):

Package	Minimum Version Needed
Kernel	8.0
VA FileMan	22.0
VA MailMan	8.0
Health Level Seven (HL7)	1.6
Pharmacy Inpatient Medications	5.0
Bar Code Med Admin (BCMA)	3.0

Installation Time Estimates

VistA Bar Code Medication Administration Backup System (BCBU) patch installation time is less than 2 minutes during off peak hours. The time for workstation setup is approximately 30 minutes.

Important! You should install and test BCBU patches in your test accounts BEFORE installing in your production accounts.

Required Patches

Before installing BCBU patches, make sure that the required released patches listed in the Patch Descriptions are installed:

Users on the System

Users may remain on the system; however, the VistA Bar Code Medication Administration Backup System (BCBU) installation should be done during off peak hours when minimal Pharmacy activity is occurring.

Options Out of Order

The options, *Inpatient Order Entry* [PSJ OE] and *Non-Verified/Pending Orders* [PSJU VBW] are to be placed out of order during installation.

Namespace

VistA Bar Code Medication Administration Backup System (BCBU) routine namespace is ALPB. The options/protocols/templates/parameters and keys use the PSB namespace. Files are distributed under the PSB namespace, but use ALPB global namespace.

Data Dictionary Changes

There are no changes made to the Data Dictionaries, but two new files have been added. These files are located on both the workstation and the VistA server, but are only populated on the workstation.

- ^ALPB(53.7, BCMA Backup Data
- ^ALPB(53.71, BCMA Backup Parameters

Journaling is not recommended for the ALPB global.

There is one Data Dictionary change to support Clinic Orders in BCMA with the install of PSB*3*73.

- CLINIC NAME field (#3.5) was added to the ORDER NUMBER file multiple field (#9).

There are three data dictionary changes to support Transdermal Medications in BCMA with the install of PSB*3*87.

- ASSOC. MED LOG GIVE DATE/TIME field (#4)
- ASSOC. MED LOG GIVE ENTERED BY field (#5)
- ASSOC. MED LOG GIVE STATUS MSG field (#6)

The above fields were added to the MED LOG DATE/TIME field (#10).

There are two data dictionary changes to support Hazardous to Handle and Hazardous to Handle drugs in BCBU with the installation of PSB*3*108:

- The HAZARDOUS TO HANDLE field (#14) was added to the BCMA BACKUP DATA file (#53.7);
- The HAZARDOUS TO DISPOSE field (#15) was added to the BCMA BACKUP DATA file (#53.7).

Resource Requirements

This section summarizes the (approximate) number of resources required to install BCMA V. 3.0.

- Routines 29
- Globals 1 (^ALPB)
- Files 2 (53.7, 53.71)
- ^ALPB Size Backup data= 268,288 bytes
(131 blocks) per order

Note: Population of the ALPB global will only occur on the workstation, there is no global growth on the VistA server. ALPB global size estimate was acquired by dividing the number of blocks consumed by the total number of orders in file 53.7. This results in the number of blocks per order, which is multiplied by 2048, which is the number of bytes per block in Cache.

- FTEE Support .2
- FTEE Maintenance .2

Printers

Your site should provide dedicated printers for each of the contingency workstations, which would allow printing of the MAR or MAH if the network was down.

Note: The printer must have the capability to print 132 characters per line.

Routines Installed

Review the listing below to learn the routines installed on your site's VistA Server during the installation of patch PSB*3*8. The first line of each routine briefly describes its general function.

Note: You can use the Kernel *First Line Routine Print* option to print a list containing the first line of each ALPB routine.

BCMA Routines Installed on VistA Server

ALPB8
 ALPBBK
 ALPBCBU
 ALPBELOG
 ALPBFRM1
 ALPBFRM2
 ALPBFRMU
 ALPBGEN
 ALPBGEN1
 ALPBGEN2
 ALPBHL1

ALPBHL1U
ALPBIN
ALPBIND
ALPBINP
ALPBOP
ALBPALL
ALBPARM
ALBPCLN
ALBPPAT
ALBPWRD
ALPBSP1
ALPBSP2
ALPBSPAT
ALPBSWRD
ALPBUTL
ALPBUTL1
ALPBUTL2
ALPBUTL3

Installation Information

VistA Server Installation Instructions

VistA Bar Code Medication Administration Backup System (BCBU) patch distribution is done by using the VA KIDS package. An example of this installation is found at the end of this installation guide.

PC Workstation Database Initialization

Once the PC Workstation(s) have been setup and assigned an IP address, proceed with setting up the workstation link.

Create a link (node) for the PC workstation. This will be the regular transmission node. Name it "BC" and the ward. For example, if the ward is 2A the link could be called "BC 2A". This will indicate that the link is tied to a BCBU package and where the contingency workstation is located. Use the *Link Edit* [HL EDIT LOGICAL LINK] option of the HL Interface menu. An example of this installation is found at the end of this installation guide in the Sample PC Workstation Database Initialization Section.

MAR Reports

Various MAR reports are located at the end of this installation guide under the Contingency PC Workstation Reports Section.

Please refer to the following documents for additional Installation Information:

**BCMA Backup System
(BCBU) InterSystems
Cache Installation Setup**

Refer to "Bar Code Medication Administration Backup System (BCBU) InterSystems Caché Installation Setup" guide for a systematic installation of Caché install on a PC workstation.

**BCMA Backup System
(BCBU) Linux Installation
Setup**

Refer to "Bar Code Medication Administration Backup System (BCBU) Linux Installation Setup" for systematic installation of Linux on a PC workstation.

This manual also includes step-by-step installation of GT/M, VistA, and the Bar Code Medication Administration Backup System (BCBU) on the Linux workstation.

Sample Installation

Select Kernel Installation & Distribution System Option: **Installation**

- 1 Load a Distribution
- 2 Verify Checksums in Transport Global
- 3 Print Transport Global
- 4 Compare Transport Global to Current System
- 5 Backup a Transport Global
- 6 Install Package(s)
Restart Install of Package(s)
Unload a Distribution

Select Installation Option: INSTAll Package(s)

Select INSTALL NAME: PSB*3.0*73 12/6/13@14:30:01
=> PSB*3*73 v10 ;Created on Dec 03, 2013@12:42:21

This Distribution was loaded on Dec 06, 2013@14:30:01 with header of
PSB*3*73 v10 ;Created on Dec 03, 2013@12:42:21

It consisted of the following Install(s):

PSB*3.0*73

Checking Install for Package PSB*3.0*73

Install Questions for PSB*3.0*73

Incoming Files:

53.7 BCMA BACKUP DATA (Partial Definition)

Note: You already have the 'BCMA BACKUP DATA' File.

Want KIDS to Rebuild Menu Trees Upon Completion of Install? YES// NO

Want KIDS to INHIBIT LOGONS during the install? NO//

Want to DISABLE Scheduled Options, Menu Options, and Protocols? NO//

Enter the Device you want to print the Install messages.

You can queue the install by enter a 'Q' at the device prompt.

Enter a '^' to abort the install.

DEVICE: HOME// SSH VIRTUAL TERMINAL

PSB*3.0*73

Installing Data Dictionaries:

Dec 06, 2013@14:43:10

Installing PACKAGE COMPONENTS:

Installing OPTION

Dec 06, 2013@14:43:10

Updating Routine file...

Updating KIDS files...

PSB*3.0*73 Installed.

Dec 06, 2013@14:43:11

Install Message sent #1327

```
-----  
100% |                25                50                75                |  
Complete +-----+
```

Install Completed

Sample PC Workstation Database Initialization

When initializing the workstations, you add an entry at the HL Logical Link Node prompt for each pc workstation your site has. The name of each link should represent the actual workstation location. For example, if you have a workstation on Ward 2A, the name of the workstation should be BC 2A. Associating the name of the HL Logical Link Node with the ward where the workstation is located, will aid in locating specific workstations should a problem arise. Once you have initialized the workstation with the correct workstation location, you can update the workstation with the users from the VistA system that have the [PSB GUI CONTEXT - USER] option. This initialization process will queue the activity and when complete send an alert.

On new installations, check the Parameter Value. The parameter can be left off until the workstation is ready to be initialized. If the workstation is already running, **do not** turn the Parameter Value off. Use the *General Parameter Tools* [XPAR MENU TOOLS] option to edit the parameter values.

```
XPAR MENU TOOLS      General Parameter Tools

LV   List Values for a Selected Parameter
LE   List Values for a Selected Entity
LP   List Values for a Selected Package
LT   List Values for a Selected Template
EP   Edit Parameter Values
ET   Edit Parameter Values with Template
EK   Edit Parameter Definition Keyword

Select General Parameter Tools Option: ep Edit Parameter Values
      --- Edit Parameter Values ---

Select PARAMETER DEFINITION NAME: PSB BKUP ONLINE

----- Setting PSB BKUP ONLINE for Package: BAR CODE MED ADMIN -----
Value: YES//<ENTER>
-----

Select PARAMETER DEFINITION NAME: PSB BKUP IPH      BCMA Contingency Active Pharm Order

----- Setting PSB BKUP IPH for Package: BAR CODE MED ADMIN -----
Value: 7// <ENTER>
-----

Select PARAMETER DEFINITION NAME: PSB BKUP MEDLG    BCMA Contingency MedLog DFT

----- Setting PSB BKUP MEDLG for Package: BAR CODE MED ADMIN -----
Value: 15// <ENTER>
-----
```

Continue with the Workstation setup.

```
>D ^XUP
Setting up programmer environment
Terminal Type set to: C-VT100

Select OPTION NAME: HL MAIN MENU      HL7 Main Menu
      Systems Link Monitor
      Filer and Link Management Options ...
      Message Management Options ...
      Interface Developer Options ...
      Site Parameter Edit
```

```

Select HL7 Main Menu Option: INTERFACE Developer Options
  EA      Application Edit
  EP      Protocol Edit
  EL      Link Edit
  VI      Validate Interfaces
          Reports ...

Select Interface Developer Options Option: EL Link Edit

Select HL LOGICAL LINK NODE: BC 2A
INSTITUTION:<ENTER> ← leave blank
DOMAIN: <ENTER> ← leave blank
AUTOSTART: Enabled
QUEUE SIZE: 10
LLP TYPE: TCP
TCP/IP SERVICE TYPE: CLIENT (SENDER)
  TCP/IP ADDRESS: (workstation IP address)
  TCP/IP PORT: (10000)
ACK TIMEOUT:10                RE-TRANSMISSION ATTEMPTS: 2
READ TIMEOUT:10              EXCEED RE-TRANSMIT ACTION: restart
BLOCK SIZE: 256
STARTUP NODE: ←leave blank    PERSISTENT: NO
RETENTION: 120                UNI-DIRECTIONAL WAIT: ←leave blank

Save the link

```

Sign out and then sign back in by doing the following:

```

>D ^XUP

Setting up programmer environment
Terminal Type set to: C-VT100

Select OPTION NAME:      PSB BCBU VISTA MAIN      BCMA Backup System (VISTA)

PSB BCBU VISTA MAIN BCMA Backup System (VISTA)
  LNK  Associate Backup Workstations with a Division
  DFT  Default Workstation Initialize
  DIV  Divisional Workstation Initialize
  USR  Initialize a Backup Workstation with BCMA Users
  PAT  Singe Patient Init

Select BCMA Backup System (VISTA) Option: LNK Associate Backup Workstations
with a Division
Do you want all backup data to go to the same group of
backup devices regardless of the patient's division?
Enter Yes or No: YES// <ENTER>

  Select one of the following:

      A      Add a Logical Link
      D      Delete a Logical Link

```

```
OPERATION: ADD// <ENTER> Add a Logical Link
The following DEFAULT links are associated with this package:
BC KEVC
BC SID
BC KEVINK
BC SFVA
Select HL LOGICAL LINK: BC 2A ...Added
Select HL LOGICAL LINK: ?
```

```
LNK    Associate Backup Workstations with a Division
DFT    Default Workstation Initialize
DIV    Divisional Workstation Initialize
USR    Initialize a Backup Workstation with BCMA Users
PAT    Singe Patient Init
```

Note: If you want to remove an HL7 Link from your system, make sure you use the *LNK Associate Backup Workstation with a Division* option to delete the logical link association prior to deleting the link in HL7. If this is not done, you will get undefined errors on the VistA system. It is recommended that the Workstation Initialize be queued to run during non-peak hours. These inits may run for several hours depending on the parameter settings.

```
Select BCMA Backup System (VISTA) Option: DFT <RET> Default Workstation
Initialize
Include all workstations
Enter Yes or No? YES// NO
Select WorkStation Link : BC 2A
```

Selected Workstations

```
BC 2A
Select WorkStation Link :
Requested Start Time: NOW// <RET> (FEB 18, 2003@14:28:13)
2624847
```

```
LNK    Associate Backup Workstations with a Division
DFT    Default Workstation Initialize
DIV    Divisional Workstation Initialize
USR    Initialize a Backup Workstation with BCMA Users
PAT    Singe Patient Init
```

```
Select BCMA Backup System (VISTA) Option: USR Initialize a Backup
Workstation with BCMA Users
```

This option searches for users that hold the option, 'PSB GUI CONTEXT - USER' and if they are active users, transmits the information to your BCMA Backup Workstations.

NOTE that you must have completed the step of assigning workstations to either a single default group or by division.

```
Do you wish to continue? YES// <ENTER>
```

```
Do you wish to queue this init? YES//<ENTER>
Requested Start Time: NOW// <ENTER> (FEB 20, 2003@17:17:02)
TASK #: 2625005
```

```
LNK    Associate Backup Workstations with a Division
DFT    Default Workstation Initialize
DIV    Divisional Workstation Initialize
USR    Initialize a Backup Workstation with BCMA Users
PAT    Singe Patient Init
```

```
You have PENDING ALERTS
Enter "VA to jump to VIEW ALERTS option
Select BCMA Backup System (VISTA) Option: "VA
```

```
1.I BCBU INIT Started Feb 20, 2003@17:17:04 and finished Feb 20, 2003@17:2
Select from 1 to 1
or enter ?, A, I, D, F, S, P, M, R, or ^ to exit: 1
Processed Alert Number 1
BCBU INIT Started Feb 20, 2003@17:17:04 and finished Feb 20, 2003@17:27:57.
556
```

Menu option from the BCBU Contingency Workstation for parameter settings

```
Select BCMA Backup System (Wrkstn) Option: MM BCMA Backup System Management
Menu
```

```
EL     BCMA Backup System Error Log
PE     Edit Workstation Parameter Settings
PO     Purge Orders Past X days old
```

```
Select BCMA Backup System Management Menu Option: PE Edit Workstation
Parameter Settings
```

```
Workstation Parameter ONE
BCBU Workstation Parameter Setup
```

```
DEFAULT DAYS FOR MAR: 7
```

```
DEFAULT MAR PRINTER: BCBU
```

```
PURGE ORDER DAYS:
```

```
PURGE PATIENT:
```

```
MED-LOG NUMBER:
```

```
Exit      Save      Refresh
```

Technical Information

Option Descriptions

PSB BCBU MANAGEMENT MENU

BCMA Backup System Management Menu

This Menu contains all Management options for the BCMA Contingency (Workstation Menu)

TYPE: menu

ITEM: PSB BCBU ERROR LOG

ITEM: PSB BCBU WRKSTN PARAMETER EDIT

ITEM: PSB BCBU WRKSTN PURGE ORDERS

PSB BCBU ERROR LOG

BCMA Backup System Error Log

This option is used to view the Error Log. (Workstation Menu)

TYPE: run routine Routine: ALPBELOG

PSB BCBU WRKSTN PARAMETER EDIT

Edit Workstation Parameter Settings

This option will allow the user to edit Site definable parameter settings for the BCMA Contingency Workstation. (Workstation Menu)

TYPE: ScreenMan

DIC {DIC}: ALPB(53.71,

DIC(0): A

DIC(A): Workstation Parameter:

DR{DDS}: [PSB BCBU PARAMETERS]

DDSFIL: 53.71

DDSPAGE: 1

PSB BCBU WRKSTN PURGE ORDERS

Purge Orders Past X days old

This option purges order information based on stop date first. Purge is also based on parameter setting for number of days to hold patient orders (default is 7 days) and parameter setting for number of days to hold patient record (default is 30 days with no order information). (Workstation Menu)

TYPE: run routine Routine: ALPBOP

PSB BCBU WRKSTN MAIN

This is the main menu for the BCMA Backup system -- the ward workstation containing the BCMA backup/contingency data. (Workstation Menu)

TYPE: menu

ITEM: PSB BCBU SHOW PATIENT

ITEM: PSB BCBU PRINT MAR ALL

ITEM: PSB BCBU PRINT MAR PATIENT

ITEM: PSB BCBU PRINT MAR WARD

ITEM: PSB BCBU MANAGEMENT MENU

ITEM: PSB BCBU WARD LIST

ITEM: PSB BCBU PRINT BLK MAR

ITEM: PSB BCBU PRINT MAR ALL CLINICS

ITEM: PSB BCBU PRINT MAR CLINIC

PSB BCBU SHOW PATIENT

List/Display Orders

This option will display orders to the screen by individual patient.
(Workstation Menu)

TYPE: run routine ROUTINE: ALPBSPAT

PSB BCBU SHOW WARD

Display Orders for Selected Ward

This option will display orders to the screen by Ward. (Workstation Menu)

TYPE: run routine ROUTINE: ALPBSWRD

PSB BCBU PRINT MAR ALL

Print MAR for All Wards

This option prints a MAR report for all wards. (Workstation Menu)

TYPE: run routine ROUTINE: ALPBPALL

PSB BCBU PRINT MAR PATIENT

Print MAR for Selected Patient

This option prints a MAR report by individual patients. (Workstation Menu)

TYPE: run routine ROUTINE: ALPBPPAT

PSB BCBU PRINT MAR WARD

Print MAR for Selected Ward

This option prints a MAR report by individual wards. (Workstation Menu)

TYPE: run routine ROUTINE: ALPBPWRD

PSB BCBU WARD LIST

List of Wards in BCMA Backup File

This option will display all the wards available on the workstation.
(Workstation Menu)

TYPE: run routine ROUTINE: WARDLIST^ALPBUTL

PSB BCBU PRINT BLK MAR

Print Blank Mar for Selected Patient

This option allows the user to select a patient from the BCMA contingency and print a blank 3 or 7 day MAR. The MAR will only contain patient info.

TYPE: run routine ROUTINE: ALPB BK

PSB BCBU PRINT MAR ALL CLINICS

Print MAR for All Clinics

This option prints a MAR report for all the clinics available on the workstation. (Workstation Menu)

TYPE: run routine ROUTINE: EN^ALPBCLN("ALL")

PSB BCBU PRINT MAR CLINIC

Print MAR for Selected Clinic

This option prints a MAR report for a selected clinic. (Workstation Menu)

TYPE: run routine ROUTINE: EN^ALPBCLN("CLN")

PSB BCBU VISTA MAIN

BCMA Backup System (VISTA)

This is the Primary Menu for the BCMA Backup Contingency. (VISTA Menu)

TYPE: menu

ITEM: PSB BCBU INIT WRKSTN DFT

ITEM: PSB BCBU INIT WRKSTN DIV

ITEM: PSB BCBU LINK ASSOCIATIONS

ITEM: PSB BCBU USER INIT

ITEM: PSB BCBU INIT SINGLE PT

PSB BCBU INIT WRKSTN DFT

Default Workstation Initialize

This option is used to initialize Workstations that are linked as default. This option will send inpatient and clinic orders to the BCMA Contingency to all or selected workstations. For non-divisional sites. (VISTA Option)

TYPE: run routine ROUTINE: OPT^ALPBIND

PSB BCBU INIT WRKSTN DIV

Divisional Workstation Initialize

This option is used to initialize Workstations that are linked by Division. This option will send inpatient and clinic orders to the BCMA Contingency workstation for all or selected divisions. For multi-divisional sites only. (VISTA Option)

TYPE: run routine ROUTINE: OPT^ALPBIN

PSB BCBU LINK ASSOCIATIONS

Associate Backup Workstations with a Division

For sites running the REAL-TIME BCMA BACKUP interface, use this option to assign your backup workstations to specific divisions. If you are not a multidivisional site, associate all backup workstations with a single division.

When HL7 events occur, the division associated with the patient will be used to determine which workstations will get the message. (VISTA Menu)

TYPE: run routine ROUTINE: ALPBPARAM

PSB BCBU USER INIT

Initialize a Backup Workstation with BCMA Users

This option searches the VISTA New Person file for authorized BCMA users and generates a version 2.4 HL7 message. Messages are addressed dynamically based on the parameter definitions for BCMA Backup using divisions or the default group.

TYPE: run routine ROUTINE: INIT^ALPBGEN2

PSB BCBU INIT SINGLE PT

Single Patient Init

This option will send inpatient and clinic orders to the BCMA Contingency workstation for a single patient.

TYPE: run routine ROUTINE: SNDPT^ALPBIND

HL7 Parameters

PSB BCBU CLIENT

ACTIVE/INACTIVE: ACTIVE

HL7 ENCODING CHARACTERS: ~|\&

PSB BCBU SERVER

ACTIVE/INACTIVE: ACTIVE

HL7 ENCODING CHARACTERS: ~|\&

PSB PMU RECV

ACTIVE/INACTIVE: ACTIVE

COUNTRY CODE: USA

HL7 ENCODING CHARACTERS: ~&^\

HL7 FIELD SEPARATOR: |

PSB PMU SEND

ACTIVE/INACTIVE: ACTIVE

COUNTRY CODE: USA

HL7 ENCODING CHARACTERS: ~&^\

HL7 FIELD SEPARATOR: |

HL7 Message Examples

Unit Dose Orders

Conditionally sending (exclusively for clinic orders) the clinic name in the ORC segment for orders placed in a clinic:

```
PID^^000-00-
0000~~^10748~2~M10^^BCMAPATIENT~TWO~~^19350517^M^^^^^^^^^^000002222
PV1^1^I^4E M-KC~SE403~3^^^5468~BCMAPROVIDER~ONE~^NSC VETERAN
ORC^XX^~OR^1U~PS^^DC~discontinued^^^199709191028-
0400^33~BCMAPROVIDER, ONE^^7356~BCMAPHARMACIST, ONE^^^199709191028-
0400^~~99ORN~~^^^SOUTH OUTPATIENT CLINIC
RXO^~~~~99PSP^^^^^^^^^^^^^^^^
RXE^&&2&~Q4H PRN&~~199709191028-0400~19970920120402-
0400^~~^326.2485~OXYCODONE HCL 5MG/ACETAMINOPHEN
325MG TAB~99NDF~7106~OXYCODONE 5MG/ACETAMINOPHEN 325MG
TAB UD~99PSD^^^~0~99PSU^~~~~99PSF^^^^^^24133~BCMAPROVIDER, TWO
~99NP^^^^^^^^^^^^^^^^~99PSU
RXR^~~~1~ORAL~99PSR^^^^
ZRX^^^^24133~BCMAPROVIDER, TWO~99NP^
```

```

NTE^21^L^These are long word processing text special instructions that can
be\.br\entered via CPRS as provider comments and then optionally
included in the\.br\Pharmacists Special instructions as is or amended by the
phrmamcists\.br\with more in
formation optionally added.\.br\
RXR^~~~1~ORAL~99PSR^^^^
ZRX^^^^^24133~BCMAPROVIDER, TWO~99NP^

```

IV Orders

Conditionally sending (exclusively for clinic orders) the clinic name in the ORC segment for orders placed in a clinic:

```

PID^^000-00-
0000~~^10748~2~M10^^BCMAPATIENT~TWO^^^19350517^M^^^^^^^^^^000002222
PV1^1^I^4E M-KC~SE403~3^^^^5468~BCMAPROVIDER~ONE~^^^^^^^^^^NSC VETERAN
ORC^XX^8547404;1~OR^53V~PS^^CM~finished/verified by
pharmacist (active) ^^^^20021206135950-0400^24133~BCMAPROVIDER, TWO
^^24133~BCMAPROVIDER, TWO^^^200212061359-
0400^~~~99ORN~~~^^^^^NORTH OUTPATIENT CLINIC
RXO^~~~1062~MULTIVITAMIN INJ, SOLN~99PSP^^^^^^^^^^^^^^^^^^
RXE^~&~~200212061359-0400~200212071400-
0400^^^^^^^^^^^^^^24133~BCMAPROVIDER, TWO~99NP^^^^^^^^^^10^~~~~ml/hr~PSU^^
NTE^21^L^I would like to enter these provider comments
RXC^A^~~~1062~MULTIVITAMIN~99PSP^10^~~~PSIV-1~ML~99OTH^^^^^^^^^^^^^^^^^^
RXC^A^~~~688~FOLIC ACID~99PSP^2^~~~PSIV-4~MG~99OTH^^^^^^^^^^^^^^^^^^
RXC^A^~~~1488~TRACE ELEMENTS~99PSP^2^~~~PSIV-1~ML~99OTH^^^^^^^^^^^^^^^^^^
RXC^B^~~~490~DEXTROSE 5%/WATER~99PSP^1000^~~~PSIV-
1~ML~99OTH^^^^^^^^^^^^^^^^^^
ZRX^^^N^^24133~BCMAPROVIDER, TWO~99NP^IV

```

Med Log

```

PID^^000-00-
0000~~^10748~2~M10^^BCMAPATIENT~TWO^^^19350517^M^^^^^^^^^^000002222
PV1^1^I^4E M-KC~SE403~3^^^^5468~BCMAPROVIDER~ONE~^^^^^^^^^^NSC VETERAN
ORC^ML^^330U~PS^^G~GIVEN^^^^^20010414131522-0400^15454~BCMAPROVIDER, THREE

```

Parameter Definitions

PSB BKUP DEFAULT

DISPLAY TEXT: Package-specific 'default' Logical Links

MULTIPLE VALUED: Yes

INSTANCE TERM: Logical Link

VALUE DATA TYPE: pointer

VALUE DOMAIN: 870

VALUE HELP: Enter the HL7 logical link

INSTANCE DATA TYPE: pointer

INSTANCE DOMAIN: 870

INSTANCE HELP: Enter the HL7 logical link

DESCRIPTION: This parameter is used by the BCMA Backup system to route messages to a "default" group of HL7 Logical Links that are associated with the BCMA package rather than individual divisions. When the default group is defined, all messages will be routed to this group rather than using division-based grouping under the following conditions:

1. If a call is made to the API, GET^ALPBPARM, and the division parameter is not present or null.
2. If a call is made to the API, GET^ALPBPARM, and the division specified has no logical links associated with it.

PRECEDENCE: .5

ENTITY FILE: PACKAGE

PSB BKUP MACHINES

DISPLAY TEXT: Division-specific Logical Links

MULTIPLE VALUED: Yes

INSTANCE TERM: Logical Link

VALUE DATA TYPE: Pointer

VALUE DOMAIN: 870

VALUE HELP: Enter the HL7 Logical Link

INSTANCE DATA TYPE: pointer

INSTANCE DOMAIN: 870

INSTANCE HELP: Enter the HL7 Logical Link

DESCRIPTION: This parameter defines the BCMA Backup Logical Links that may be associated with a division when there are one or more divisions at a site.

PRECEDENCE: 1

ENTITY FILE: DIVISION

PSB BKUP ONLINE

DISPLAY TEXT: BCMA Contingency Online

VALUE DATA TYPE: yes/no

DESCRIPTION: This parameter is used by the BCMA Backup system to activate the Contingency software. If the value is set to NO, then no HL7 messages will be sent to the Workstation. This does not affect the workstation initialization option.

PRECEDENCE: 1

ENTITY FILE: PACKAGE

PSB BKUP IPH

DISPLAY TEXT: BCMA Contingency Active Pharm Order

VALUE DATA TYPE: numeric

DESCRIPTION: The BCMA Backup Contingency software uses this parameter. During the Workstation initialization process, this tells the process how many days of historic Inpatient Medication and Clinic Orders to capture. It is based off the fact the order was active during that time.

PRECEDENCE: 1

ENTITY FILE: PACKAGE

PSB BKUP MEDLG

DISPLAY TEXT: BCMA Contingency MedLog DFT

VALUE DATA TYPE: numeric

DESCRIPTION: The BCMA Backup Contingency software uses this parameter. During the Workstation initialization process, this tells the process how many days of historic Med Log entries of Inpatient Medication and Clinic Orders to capture.

PRECEDENCE: 1

ENTITY FILE: PACKAGE

PSB BKUP DOM FILTER

DISPLAY TEXT: Filter out DOM patients

MULTIPLE VALUED: No

VALUE DATA TYPE: yes/no

VALUE HELP: Should the contingency backup filter out DOM patients?

DESCRIPTION: This parameter is used by the BCMA backup system to determine if DOM patients are included in the backup. If the value is set to YES, DOM patients will be filtered out of the backup and will not be sent to the workstation. If the value is NO or blank, DOM patients will be sent to the backup workstation.

PRECEDENCE: 1

ENTITY FILE: PACKAGE

List Templates

PSB ERROR LOG

TYPE OF LIST: PROTOCOL
RIGHT MARGIN: 80
TOP MARGIN: 4
BOTTOM MARGIN: 20
OK TO TRANSPORT?: OK
USE CURSOR CONTROL: YES
PROTOCOL MENU: PSB ERROR LOG MENU
SCREEN TITLE: BCMAbu Error Log
ALLOWABLE NUMBER OF ACTIONS: 1
AUTOMATIC DEFAULTS: YES
HIDDEN ACTION MENU: VALM IDDEN ACTIONS
ARRAY NAME: ^TMP("ALPBELOG", \$J)
EXIT CODE: D EXIT^ALPBELOG
HEADER CODE: D HDR^ALPBELOG
HELP CODE: D HELP^ALPBELOG
ENTRY CODE: D INIT^ALPBELOG

PSB SELECT ORDERS

TYPE OF LIST: PROTOCOL
RIGHT MARGIN: 80
TOP MARGIN: 7
BOTTOM MARGIN: 19
OK TO TRANSPORT?: OK
USE CURSOR CONTROL: YES
PROTOCOL MENU: PSB ORDERS MENU
SCREEN TITLE: BCMAbu ACTIVE Orders List
ALLOWABLE NUMBER OF ACTIONS: 1
HIDDEN ACTION MENU: VALM HIDDEN ACTIONS
ARRAY NAME: ^TMP("ALPBORDS", \$J)
ITEM NAME: OrderNum
COLUMN: 2
WIDTH: 10
DISPLAY TEXT: Order No.
ITEM NAME: OrderType
COLUMN: 22
WIDTH: 4
DISPLAY TEXT: Type
ITEM NAME: Status
COLUMN: 14
WIDTH: 7

DISPLAY TEXT: Status
ITEM NAME: Meds
COLUMN: 28
WIDTH: 45
DISPLAY TEXT: Medication(s)
ITEM NAME: SelNum
COLUMN: 2
WIDTH: 5
DISPLAY TEXT: Rec#
EXIT CODE: D EXIT^ALPBSP1
HEADER CODE: D HDR^ALPBSP1
HELP CODE: D HELP^ALPBSP1
ENTRY CODE: D INIT^ALPBSP1

PSB SELECT PATIENT

TYPE OF LIST: PROTOCOL
RIGHT MARGIN: 80
TOP MARGIN: 4
BOTTOM MARGIN: 15
OK TO TRANSPORT?: OK
USE CURSOR CONTROL: YES
PROTOCOL MENU: PSB PATIENT MENU
SCREEN TITLE: BCMABu Patient List (All)
ALLOWABLE NUMBER OF ACTIONS: 1
HIDDEN ACTION MENU: VALM HIDDEN ACTIONS
ARRAY NAME: ^TMP("ALPBPLIST", \$J)
ITEM NAME: RecNum
COLUMN: 2
WIDTH: 6
DISPLAY TEXT: Rec #
ITEM NAME: Patient
COLUMN: 2
WIDTH: 30
DISPLAY TEXT: Patient
ITEM NAME: SSN
COLUMN: 33
WIDTH: 9
DISPLAY TEXT: SSN
ITEM NAME: WARD
COLUMN: 43
WIDTH: 15
DISPLAY TEXT: Ward
ITEM NAME: ROOM

COLUMN: 62
WIDTH: 5
DISPLAY TEXT: Room
ITEM NAME: BED
COLUMN: 72
WIDTH: 5
DISPLAY TEXT: Bed
EXIT CODE: D EXIT^ALPBSPAT
HEADER CODE: D HDR^ALPBSPAT
HELP CODE: D HELP^ALPBSPAT
ENTRY CODE: D INIT^ALPBSPAT

PSB SHOW ORDERS

TYPE OF LIST: DISPLAY
RIGHT MARGIN: 80
TOP MARGIN: 7
BOTTOM MARGIN: 20
OK TO TRANSPORT?: OK
USE CURSOR CONTROL: YES
SCREEN TITLE: BCMABu Selected Order(s)
ALLOWABLE NUMBER OF ACTIONS: 1
AUTOMATIC DEFAULTS: YES
HIDDEN ACTION MENU: VALM HIDDEN ACTIONS
ARRAY NAME: ^TMP("ALPBFORM", \$J)
EXIT CODE: D EXIT^ALPBSP2
HEADER CODE: D HDR^ALPBSP2
HELP CODE: D HELP^ALPBSP2
ENTRY CODE: D INIT^ALPBSP2

HL Communication Server Parameters

These parameters exist only on the workstations and is included in the .dat file.

ONE: 1 DOMAIN: BCMABU.MED.VA.GOV
DEFAULT PROCESSING ID: training INSTITUTION: SOFTWARE SERVICE
DEFAULT NUMBER INCOMING FILERS: 2 DEFAULT NUMBER OUTGOING
FILERS: 2
PURGE COMPLETED MESSAGES: 2 PURGE AWAITING ACK MESSAGES: 2
PURGE ALL MESSAGES: 4

Select HL LOGICAL LINK NODE: LISTNER

NODE: LISTNER LLP TYPE: TCP
DEVICE TYPE: Single-threaded Server

AUTOSTART: Enabled
SHUTDOWN LLP ?: NO
QUEUE SIZE: 10 RE-TRANSMISSION ATTEMPTS: 2
BLOCK SIZE: 256 READ TIMEOUT: 2
ACK TIMEOUT: 10 EXCEED RE-TRANSMIT ACTION: restart
TCP/IP PORT: 10000 TCP/IP SERVICE TYPE: SINGLE LISTENER
PERSISTENT: NO RETENTION: 120

Files Associated with GT.M/Linux BCMA:

The following files are provided with the GT.M version of Bar Code Medication Administration Backup System (BCBU) and are unpacked from the `bcma_files.tar.gz` file into \$HOME of the BCMA manager account.

.bashrc – this is the BCMA manager's `$HOME/.bashrc` file. This file defines GT.M related global variables, sets convenient aliases and sets terminal characteristics. This file may be edited but all GT.M variable and terminal definitions should be retained to guarantee the proper functioning of the GT.M database.

bcmabashrc – `install_bcma` creates a generic "bcma" Linux account tied to VistA. `bcmabashrc` is renamed to `/home/bcma/.bashrc` and is called with each "bcma" user login. The call to this file ties the user to VistA and prevents access to the Linux or GT.M level as well as defining GT.M related global variables.

bcma.gld – this is the GT.M global directory file which defines the location of the BCMAbu database. `install_bcma` edits this file automatically to account for the directory structure specified by the installer. The GT.M database utility, GDE, accesses this file.

cronjrnclean – this file is used to generate the crontab procedure (found in `/var/spool/tar/bcma_manager_name`) which runs nightly to flip the GT.M journal file, remove old journal files and remove temporary GT.M process related files in the manager's \$HOME. This file is only used once during the BCMA install.

gcomp - run this file at your GT.M manager to recompile all M routines. At times, compiled objects may end up with the wrong user ownership (for example, if patches were installed and run as root). Run this script to correct such situations.

jrnclean – this file is called by `/var/spool/tar/bcma_manager_name` nightly at 1:00am to flip the GT.M journal file, remove old journal files and remove temporary GT.M process related files in the BCMA manager's \$HOME.

jrnoff - this file may be used to turn journaling off. Note that journaling is automatically enabled with every reboot of the system by `rc.local`.

jrnnon – this file may be used to turn journaling on or flip the current journal file to a new one. It is called by `jrnclean`. Journal files are found in `$HOME/jrn` of the bcma manager.

netmail_start – this file is called by *rc.local* during runlevel 5-system startup to start network mail on port 25. If netmail needs to be started manually, run this file as root (other users will not have the privileges to connect a process to port 25).

rc.local – this is a user-editable Linux file found in */etc/rc.d* and is called during system startup and shutdown. This file calls *\$HOME/recoverall*, *\$HOME/jrnon*, *\$HOME/taskman_start* and *\$HOME/netmail_start* during system startup. It will call *\$HOME/zgstop* during system shutdown. If *rc.local* is successful in each of these calls, the following empty files will be created in *\$HOME* of the BCMA manager account: *recovery*, *TaskMan*, *netmails*, and *rundowns*.

recoverall – this file is called by *rc.local* during system startup and attempts to recover the database should the system be shutdown uncleanly.

taskman_start – this file starts TaskMan automatically during system startup. If TaskMan needs to be started manually, run *taskman_start* as root (TaskMan automatically starts HL7 processes – the LISTNER link needs to connect with port 10000).

VistA – this script resides in the */home/bcma* and */home/gtm* manager directories and is called by the icon file *\$HOME/.gnome-desktop/ VistA -icon* for the respective users

***-icon** - these are the desktop icon files. The BCMA and GT.M manager users both have the VistA -icon, which will bring the user to the access/verify prompts. In addition to this, the GT.M manager user will also have the term-icon and editor-icon on its desktop to open a terminal session and gedit text editor, respectively.

zgstop - this file is called by *rc.local* during system shutdown to shutdown GT.M cleanly and performs a recovery if needed. Call this file as root if GT.M needs to be shutdown (only the root user will be permitted to stop ALL GT.M processes – if another user call zgstop, only its own processes will be shutdown). This file is derived from */usr/local/gtm/gstop*.

Adding a BCMA printer to the Cache/NT Contingency system:

Contingency Workstation (VistA) printer:

Slave printers are defined in VistA as P220/102 SLAVE CACHE/NT.
Test the printer through VistA.

DEVICE file entry:

```
NAME: P220/102 SLAVE CACHE/NT          $I: 0
  ASK DEVICE: NO                        ASK PARAMETERS: NO
  LOCATION OF TERMINAL: slave device for Cache/NT
MNEMONIC: SLAVE
  SUBTYPE: C-VT220                      TYPE: TERMINAL
```

Network printer:

From the NT menu:

1. **Start/Settings/Printers/Add Printer.**
2. Select the **My Computer** radio button then **Next** to continue.
3. Click the **Add Port** button.
4. Double click the **LPR Port** then fill in the IP address of the device and the name then **Close** to continue.
5. Make sure the box for the newly created port is checked then **Next** to continue.
6. Select the printer driver (note - you may need the NT install CD handy for this step) then **Next** to continue.
7. Enter the printer name then **Next** to continue
Note: this is the value that will be used in the \$I below.
8. Select shared or not shared then **Next** to continue.
9. Try printing a test page; at this point, NT might start requesting the install CD for specific drivers.

From the W2K menu:

1. **Start/Settings/Printers/Add Printer.**
2. **Next** at the welcome add printer wizard box.
3. Select the **Local Printer** radio button and uncheck the automatic detection for plug and play devices then **Next** to continue.
4. Select the **Create a new port** radio button then select either **LPR** or **Standard TCPIP port** from the dropdown menu.
 - For LPR:
 - o Fill in the IP address of the device and the name, then **Close** to continue.
 - For TCP/IP:
 - o Click **Next** to continue in the welcome wizard window.
 - o Enter the printer name or IP address then **Next** to continue.
5. Select the driver, then **Next** to continue.
6. Enter the printer name, then **Next** to continue
Note: this is the value that will be used in the \$I below.
7. Share or not, then **Next** to continue.
8. Print a test page, then **Next** to continue.

From within Contingency Workstation (VistA) Printer

1. No special terminal types need to be used for Cache/NT network printing. Several HP-LASER terminal types are available in the TERMINAL TYPE file as installed.
2. Create a new entry in the DEVICE file as per the example below. \$I syntax is |PRN|\\bcmaservername\LPR device defined above. In the example below, the A410 printer was defined as an LPR port through NT. The server name is VHAISADHC1
3. Test the printer through VistA.

Examples:

DEVICE file entry:

```
NAME: A410                                $I: |PRN|\\VHAISADHC2\A410
LOCATION OF TERMINAL: A410                 SUBTYPE: P-HP-P16
TYPE: TERMINAL
```

TERMINAL TYPE file entries:

```
NAME: P-HPLASER-P10                       RIGHT MARGIN: 80
FORM FEED: #                              PAGE LENGTH: 64
BACK SPACE: $C(8)                         OPEN EXECUTE: W *27,"E"
CLOSE EXECUTE: W *27,"E"                  PROPORTIONAL SPACING: $C(27)_"(s1P"
DESCRIPTION: LASER PRINTER PORTRAIT MODE 10 CPI

NAME: P-HP-P16                             RIGHT MARGIN: 132
FORM FEED: $C(12,13)                      PAGE LENGTH: 58
BACK SPACE: $C(8)                         OPEN EXECUTE: W
$C(27) ,"E", $C(27) ,"&k2S"
CLOSE EXECUTE: W $C(27) ,"E"              DESCRIPTION: HP LASER JET 16 PITCH
```

Adding a BCMA printer to the GT.M/Linux Contingency system:

Contingency Workstation (VistA)

From the Linux menu:

1. Select *System Settings* then *Printing*.
2. In the Red Hat printer config windows click *New* to create a new printer queue.
3. Read the instructions then click *Forward* to continue.
4. Specify 'local' or 'LOCAL' as the name for the new printer and select *local printer* radio button, then click *Forward* to continue.
5. Accept */dev/lp0* as printer device to use, then click *Forward* to continue.
6. Select the driver for your local printer, then click *Forward* to continue. *Postscript Printer* is usually acceptable for HP printers.
7. Click *Apply* button to restart LPD.
8. You may test the printer by selecting it in the Red Hat printer config window, then selecting *Test* from the horizontal menu.

From within Contingency Workstation (VistA)

1. P220/102 SLAVE GTM/LINUX entries are already pre-defined in VistA DEVICE file.
2. Test the printer through VistA.

DEVICE file entries:

```
NAME: P220/102 SLAVE GTM/LINUX            $I: $HOME/slave.dat
```

```
ASK DEVICE: NO                                ASK PARAMETERS: NO
LOCATION OF TERMINAL: basic slave device for gtm/linux
ASK HOST FILE: NO                             SUPPRESS FORM FEED AT CLOSE: YES
OPEN PARAMETERS: newversion
MNEMONIC: SLAVE
SUBTYPE: P-SLAVE TEXT GTM/LINUX              TYPE: HOST FILE SERVER
```

```
NAME: P220/102 HP 80 SLAVE GTM/LINUX        $I: $HOME/slave.dat
ASK DEVICE: NO                                ASK PARAMETERS: NO
LOCATION OF TERMINAL: HP 80 slave device for gtm/linux
ASK HOST FILE: NO                             SUPPRESS FORM FEED AT CLOSE: YES
OPEN PARAMETERS: newversion
MNEMONIC: SLAVE
SUBTYPE: P-SLAVE HP 80 GTM/LINUX            TYPE: HOST FILE SERVER
```

```
NAME: P220/102 HP 132 SLAVE GTM/LINU       $I: $HOME/slave.dat
ASK DEVICE: NO                                ASK PARAMETERS: NO
LOCATION OF TERMINAL: HP 132 slave device for gtm/linux
ASK HOST FILE: NO                             SUPPRESS FORM FEED AT CLOSE: YES
OPEN PARAMETERS: newversion
MNEMONIC: SLAVE
SUBTYPE: P-SLAVE HP 80 GTM/LINUX            TYPE: HOST FILE SERVER
```

TERMINAL TYPE file entries:

```
NAME: P-SLAVE HP 132 GTM/LINUX              RIGHT MARGIN: 132
FORM FEED: #                                PAGE LENGTH: 60
BACK SPACE: $C(8)
OPEN EXECUTE: W *27,"E",*27,"(s16.7H",*27,"&k3G"
CLOSE EXECUTE: W *27,"E" U IO K IO(1,IO) C IO ZSYSTEM "lpr -lr "_IO
```

```
NAME: P-SLAVE HP 80 GTM/LINUX               RIGHT MARGIN: 80
FORM FEED: #                                PAGE LENGTH: 60
BACK SPACE: $C(8)                           OPEN EXECUTE: W *27,"E",*27,"&k3G"
CLOSE EXECUTE: W *27,"E" U IO K IO(1,IO) C IO ZSYSTEM "lpr -lr "_IO
```

```
NAME: P-SLAVE TEXT GTM/LINUX                RIGHT MARGIN: 80
FORM FEED: #                                PAGE LENGTH: 60
BACK SPACE: $C(8)
CLOSE EXECUTE: U IO K IO(1,IO) C IO ZSYSTEM "lpr -r "_IO
```

Network printer:

From the Linux menu:

1. Select **System Settings** then **Printing**.
2. In the Red Hat printer config windows click **New** to create a new printer queue
3. Read the instructions then click **Forward** to continue.
4. Specify the name of the new printer (example: A405) and select either the **Unix Printer** or **Jetdirect Printer** radio button as type (**Note:** Unix printer uses port 515 and Jetdirect uses port 9100), then click **Forward** to continue.
 - a. if Unix printer: Enter the printer hostname or IP in the **Server** box - no need to enter queue information.
 - b. if Jetdirect printer: Enter the printer hostname or IP in the **Printer IP** box - accept

- 9100 as the port value then click **Forward** to continue.
5. Select the driver for your network printer, then click **Forward** to continue.
Note: Postscript Printer is usually acceptable for HP printers.
 6. Click **Apply** button to restart LPD.
 7. You may test the printer by selecting it in the Red Hat printer config window, then selecting **Test** from the horizontal menu.

From within Contingency Workstation (VistA)

1. P-TCP * GTM/LINUX entries are already pre-defined in VistA TERMINAL TYPE file. You may use the VA FileMan *Transfer File Entries* option to create new terminal types using these as templates. Edit the OPEN EXECUTE fields accordingly to vary print characteristics.
2. Create a new DEVICE file entry.
 - a. **Note:** The name of the new DEVICE must begin with the name of the Linux printer created above FOLLOWED BY A SPACE then a description (Example: "A405 - ADMIN 10/6/UP"). The CLOSE EXECUTE field of the TERMINAL TYPE being used parses the queue name from the first space backward)
 - b. IS's for network printers are normally /home/Linux bcma mgr acct/hfs/devicename.txt
 - c. Device TYPE - HFS
3. Test the printer through VistA.

Examples:

DEVICE file entries:

```
NAME: A405 10/6/UP                               $I: /home/gtmmgr/hfs/A405.dat
ASK DEVICE: NO                                   ASK PARAMETERS: NO
LOCATION OF TERMINAL: A405                         ASK HOST FILE: NO
SUPPRESS FORM FEED AT CLOSE: YES                 OPEN PARAMETERS: newversion
SUBTYPE: P-TCP 10/6/UP GTM/LINUX                 TYPE: HOST FILE SERVER
```

```
NAME: A405 16/6/UP                               $I: /home/gtmmgr/hfs/A405.dat
ASK DEVICE: NO                                   ASK PARAMETERS: NO
LOCATION OF TERMINAL: A405                         ASK HOST FILE: NO
SUPPRESS FORM FEED AT CLOSE: YES                 OPEN PARAMETERS: newversion
SUBTYPE: P-TCP 16/6/UP GTM/LINUX                 TYPE: HOST FILE SERVER
```

TERMINAL TYPE file entries:

```
NAME: P-TCP 10/6/UP GTM/LINUX                     SELECTABLE AT SIGN-ON: NO
RIGHT MARGIN: 80                                  FORM FEED: #
PAGE LENGTH: 60                                   BACK SPACE: $C(8)
OPEN EXECUTE: W *27,"E",*27,"&k3G"
CLOSE EXECUTE: W *27,"E" U IO K IO(1,IO) C IO ZSYSTEM "lpr -lrP
" $E(ION,1,$F(ION," ") -1) " " IO
```

```
NAME: P-TCP 16/6/UP GTM/LINUX                     SELECTABLE AT SIGN-ON: NO
```

```
RIGHT MARGIN: 132                FORM FEED: #
PAGE LENGTH: 60                 BACK SPACE: $C(8)
OPEN EXECUTE: W *27,"E",*27,"(s16.7H",*27,"&k3G"
CLOSE EXECUTE: W *27,"E" U IO K IO(1,IO) C IO ZSYSTEM "lpr -lrP
" $E(ION,1,$F(ION," ") -1) " " IO
```

Workstation Queued Tasks

The following tasks should be queued to run on the workstation. All except XMMGR-PURGE-AI-XREF (which has a rescheduling frequency of 7D) should have a rescheduling frequency of 1D. The GT.M and Cache dat files were released with these jobs scheduled properly but they should be checked, once TaskMan is started, to make sure they have run and are being rescheduled.

The following capture shows how to list the currently queued workstation tasks and verifies that the HL PURGE TRANSMISSIONS task has been rescheduled. Check the TaskMan error log should the jobs not appear to be run or scheduled properly.

```
Select Systems Manager Menu Option:

Core Applications ...
Device Management ...
Menu Management ...
Programmer Options ...
Operations Management ...
Spool Management ...
Information Security Officer Menu ...
Taskman Management ...
User Management ...
Application Utilities ...
Capacity Management ...
HL7 Main Menu ...

Select Systems Manager Menu Option: TASKman Management

Schedule/Unschedule Options
One-time Option Queue
Taskman Management Utilities ...
List Tasks
Dequeue Tasks
Requeue Tasks
Delete Tasks
Print Options that are Scheduled to run
Cleanup Task List
Print Options Recommended for Queueing

Select Taskman Management Option: SCHEdule/Unschedule Options

Select OPTION to schedule or reschedule: ?
Answer with OPTION SCHEDULING NAME
Choose from:
XQBUILDTREEQUE      (R)
XQ XUTL $J NODES   (R)
XUTM QCLEAN        (R)
XUERTRP AUTO CLEAN (R)
```

XMCLEAN (R)
XMAUTOPURGE (R)

XMMGR-PURGE-AI-XREF (R)
HL PURGE TRANSMISSIONS (R)
HL TASK RESTART (R)
HL AUTOSTART LINK MANAGER (R)
PSB BCBU WRKSTN PURGE ORDERS (R)

You may enter a new OPTION SCHEDULING, if you wish
Enter OPTION to schedule.

Only allow Action, Print, and Run type options.

Answer with OPTION NAME

Do you want the entire OPTION List? **N** (No)

Select OPTION to schedule or reschedule: PSB BCBU WRKSTN PURGE ORDERS

Purge Orders Past X days old

...OK? Yes// **<ENTER>** (Yes)

(R)

Edit Option Schedule

Option Name: PSB BCBU WRKSTN PURGE ORDERS

Menu Text: Purge Orders Past X days old

TASK ID: 8709

QUEUED TO RUN AT WHAT TIME: JUN 3,2003@01:30

DEVICE FOR QUEUED JOB OUTPUT:

QUEUED TO RUN ON VOLUME SET:

RESCHEDULING FREQUENCY: 1D

TASK PARAMETERS:

SPECIAL QUEUEING:

Quick Reference Installation Checklist

Action	Where	Completed
1. Install patch PSB*3.0*8	VistA	_____
A. FTP Software from an OI Field Office		_____
B. Install using Kids		_____
2. Workstation Setup		
Note: Ensure that the workstation has a static IP Address.		
A. Windows/Caché		
1. Setup Caché – InterSystems supplies software. Example of install can be found in the manual, "Bar Code Medication Administration Backup System (BCBU) InterSystems Cache Installation Setup".	Workstation	_____
2. Shutdown Caché		_____
3. Copy cache.dat file that was downloaded from the FTP site into C:\CACHESYS\folder. (If asked to replace file, answer yes.)		_____
4. Remove the Read-Only attribute from the cache.dat file.		_____
5. Ensure telnet is enabled in Caché Configuration.		_____
6. Move ZSTU routine from VistA namespace to %SYS namespace.		_____
7. Setup Telnet and Terminal users using Caché Control Panel.		_____
8. Stop and Restart Caché.		_____
9. Create BCMA Backup shortcut.		_____
B. Linux/GT.M		
1. Install Linux onto clean system	Workstation	_____
2. Example of install can be found in the manual, "Bar Code Medication Administration Backup System (BCBU) Linux Installation Setup. Make note of username entered and its password for future use. Also, remember the root password.		_____

Action	Where	Completed
3. Sign into Linux using the user created during the installation.		_____
4. Enter super user mode (\$ <u>su</u>)		_____
5. Copy downloaded Linux files to an accessible location.		_____
6. Ensure downloaded file has correct permissions.		_____
7. Run the install script. (./install_bcma) Note: BCMA manager account will be the user you created during the Linux install.		_____
8. Edit the TaskMan Site Parameters to enter the correct Box-Volume pair.		_____
9. Restart TaskMan.		_____
3. Workstation Database Initialization		_____
A. On new installs check the parameter PSB BKUP ONLINE VALUE=yes	VistA	_____
B. Add a new link using HL7 options.	VistA	_____
C. Associate the new link to a division using PSB BCBU VistA MAIN option.	VistA	_____
D. Start the new link using HL7 options.	VistA	_____
E. Check the HL7 Site Parameter to make sure the field, "Is this a Production or Test Account", is set correctly. It must match the setting in the Vista account sending the messages	Workstation	_____
F. Start the LISTNER link using HL7 options.	Workstation	_____
G. Review the Parameter settings and verify that all task jobs have been queued properly. This is described in the Workstation Queued Tasks section of this documentation.	Workstation	_____
H. Initialize the workstation using Default or Divisional Workstation initialize option.	VistA	_____

Contingency PC Workstation Reports

List/Display Orders

The BCBU List/Display Orders report will add Remove Times to Admin Times and will display both "Given" data and "Removed" data for medications requiring removal.

```
BCMAbu Selected Order(s)      May 19, 2016@09:36:02      Page: 1 of 1
TESTPATNM,THREE              SSN: 666122223      Ward: GEN MED
This record last updated: May 18, 2016@18:31:44      Room: B Bed: 4
Allergies: STRAWBERRIES
-----
Order Number: 46U              Start: May 11, 2016@05:45
Type: UNIT DOSE                Stop: Jun 01, 2016@07:00
Status: finished/verified by pharmacist(active)
Drug: FENTANYL 12MCG/HR PATCH
Give: 1 PATCH TRANSDERMAL Q12H
Provider: BCMAPROVIDER,ONE      RPh/Entry by: SMITH,NANCY SUE
Admin. Times: 0600-1800
Removal Times: 1800-0600
BCMA Medication Log History since
Log Date      Message      Log Entry Person
05/11/16@06:09  GIVEN      NURSE,TWENTY
05/11/16@18:23  REMOVED    NURSE,FOUR
05/11/16@18:27  HELD       NURSE,TWO
-----
Enter ?? for more actions

Select Action:Quit//
```

```
Select BCMA Backup System (Wrkstn) Option: SO <ENTER>      List/Display Orders
BCMAbu Patient List (All)      Mar 29, 2005@07:38:33      Page: 1 of 1
BCMA Backup System :: Patient Listing
Patient      SSN      Ward      Room      Bed
BCMAPATIENT1,ONE      000000001 4 MED      M20      A
BCMAPATIENT2,TWO      000000002 3W GS      NW304     2

Enter ?? for more actions
SP  Select Patient      LW  List by Ward      LA  List All Patients
Select Item(s): Quit// SP <ENTER>      Select Patient
Select PATIENT: BCMAPATIENT1,ONE <ENTER>

BCMAbu ACTIVE Orders List      Mar 29, 2005@07:39      Page: 1 of 1
BCMAPATIENT1,ONE      SSN: 000000001      Ward: 4 MED
This record last updated: Mar 29, 2005@07:29:43      Room: M20 Bed: A
Allergies: DYE,CATHETER; DILTIAZEM; SULFA; IBUPROFEN
-----
```

```
Order No.   Status   Type   Medication(s)
16U         Active   UD     SULFADIAZINE 500MG TAB (500MG ORAL QD)
```

Enter ?? for more actions

```
SO Select Order      L1 List Active Orders  L2 List All Orders
Select Action: Quit// SO <ENTER> Select Order
Select order number, more than one separated by a comma, or 'ALL':
```

Select ORDER#: ALL// 16U <ENTER>

```
BCMAbu Selected Order(s)      Mar 29, 2005@07:39:36      Page: 1 of 1
BCMAPATIENT1,ONE              SSN: 000000001  Ward: 4 MED
This record last updated: Mar 29, 2005@07:29:43  Room: M20 Bed: A
Allergies: DYE,CATHETER; DILTIAZEM; SULFA; IBUPROFEN
```

```
-----
Order Number: 16U              Start: Mar 29, 2005@07:29:53
Type: UNIT DOSE                Stop: Apr 11, 2005@14:00
Status: finished/verified by pharmacist(active)
Drug: SULFADIAZINE 500MG TAB
Give: 500MG ORAL QD
Provider: BCMAPROVIDER,ONE     RPh/Entry by: BCMAPHARMACIST,ONE
Admin. Times: 0900
-----
```

Enter ?? for more actions

```
Select Action:Quit// <ENTER> QUIT
```

```
BCMAbu Patient List (All)      Mar 29, 2005@07:40:28      Page: 1 of 1
BCMA Backup System :: Patient Listing
Patient      SSN      Ward      Room      Bed
BCMAPATIENT1,ONE 000000001 4 MED      M20      A
BCMAPATIENT2,TWO 000000002 3W GS      NW304    2
```

Enter ?? for more actions

```
SP Select Patient      LW List by Ward      LA List All Patients
Select Item(s): Quit// LW <ENTER> List by Ward
Wards with BCMA Backup Data on this workstation:
```

```
3W GS
4 MED
4 MED-CO
```

Select WARD: **3W** <ENTER>

BCMAbu Patient List (Ward) Mar 29, 2005@07:41:03

Page: 1 of 1

BCMA Backup System :: Patient Listing

Patient	SSN	Ward	Room	Bed
BCMAPATIENT2,TWO	000000002	3W GS	NW304	2

Enter ?? for more actions

SP Select Patient LW List by Ward LA List All Patients

Select Item(s): Quit// **SP** <ENTER> Select Patient

Select PATIENT: **BCMAPATIENT2,TWO** <ENTER>

BCMAbu ACTIVE Orders List Mar 29, 2005@07:41:20

Page: 1 of 1

BCMAPATIENT2,TWO SSN: 000000002 Ward: 3W GS

This record last updated: Mar 29, 2005@07:32:52 Room: NW304 Bed: 2

Order No.	Status	Type	Medication(s)
30U	Active	UD	EPOETIN ALFA,RECOMBINANT 4000 UNT/ML INJ (4000UNT/1ML)

Enter ?? for more actions

SO Select Order L1 List Active Orders L2 List All Orders

Select Action: Quit// **<ENTER>** QUIT

BCBU MAR (Medical Administration Record) Report

The BCBU MAR (Medical Administration Record) report will add Remove Times to Admin Times and will display both "Given" data and "Removed" data for medications requiring removal. The "Order #:" field containing the letter "U" that previously printed on the same line as "Type:" and which could be mistaken for unit dose information, has been removed from the report.

In addition, notifications will be displayed on the MAR informing the medical professional of drugs that are hazardous to handle and/or hazardous to dispose.

Location	Admin Times	05/20	05/21
Start	Stop		
INPATIENT	0600		
May 11, 2016@09:00	1800		
Jun 01, 2016@07:00	1800	*****	*****
<<FENTANYL 12MCG/HR PATCH>>	0600		
Give: 1 PATCH TRANSDERMAL Q12H			
Provider: BCMAPROVIDER,TWO			
RPh/Entry by: PHARMACIST,TEN			
Type: UNIT DOSE			
Status: finished/verified by pharmacist(active)			
BCMA MEDICATION LOG HISTORY			
Log Date	Message	Log Entry Person	
05/11/16@18:27	HELD	BCMANURSE,FOUR	
05/11/16@18:23	REMOVED	BCMANURSE,ONE	
05/11/16@18:09	GIVEN	BCMANURSE,ONE	

The hard-coded list of injection sites that prints as a legend at the end of the BCBU MAR reports has been removed. This report legend does not correspond with the medications requiring removal dermal sites or injectable medication injection sites.

BCBU MAR Report Prior to Report Legend Removal

Location	Admin Times	01/16	01/17	01/18	01/19	01/20	01/21	01/22
Start	Stop							
INPATIENT		*****	*****	*****	*****	*****	*****	*****
May 07, 2015@15:38	Jun 06, 2015@23:59	*****	*****	*****	*****	*****	*****	*****
<<SELENIUM SULFIDE 2.5% LOTION/SHAMPOO>>		*****	*****	*****	*****	*****	*****	*****
Give: SMALL AMOUNT TOPICAL ON CALL PRN		*****	*****	*****	*****	*****	*****	*****
Provider: TEAGUE,LYN D		*****	*****	*****	*****	*****	*****	*****
RPh/Entry by:		*****	*****	*****	*****	*****	*****	*****
Order #: 147U	Type: UNIT DOSE	*****	*****	*****	*****	*****	*****	*****
Status: finished/verified by pharmacist(active)		*****	*****	*****	*****	*****	*****	*****
BCMA MEDICATION LOG HISTORY		PRN Effectiveness: _____						
No Medication Log entries are on file for this order.								
Special Instructions:								
Give to patient as requested.								
SIGNATURE/TITLE		INIT	INJ SITES (Right or Left)		VA FORM 10-2970			
			1. DELTOID	4. MED (ANTERIOR) THIGH	7. ABDOMEN			
			2. VENTRAL GLUTEAL	5. VASTUS LATERALIS	8. THIGH			
			3. GLUTEUS MEDIUS	6. UPPER ARM	9. BUTTOCK			
			10. UPPER BACK	PRN: E=Effective N=Not Effective				

BCBU MAR Report After Report Legend Removal

Location Start	Stop	Admin Times	01/16	01/17	01/18	01/19	01/20	01/21	01/22

INPATIENT			*****	*****	*****	*****	*****	*****	*****
May 07, 2015@15:38	Jun 06, 2015@23:59		*****	*****	*****	*****	*****	*****	*****
<<SELENIUM SULFIDE 2.5% LOTION/SHAMPOO>>									
Give: SMALL AMOUNT TOPICAL ON CALL PRN									
Provider: TEAGUE, LYN D									
RPh/Entry by:									
Order #: 147U	Type: UNIT DOSE		*****	*****	*****	*****	*****	*****	*****
Status: finished/verified by pharmacist(active)									
BCMA MEDICATION LOG HISTORY PRN Effectiveness: _____									
No Medication Log entries are on file for this order.									
Special Instructions:									
Give to patient as requested.									

Print MAR for All Wards

```
Select BCMA Backup System (Wrkstn) Option: PA Print MAR for All Wards
Inpatient Pharmacy Orders for all wards

Report [A]LL or [C]URRENT orders? CURRENT// <ENTER>

Include Patients Without Active Medications? YES// <ENTER>

Sort Patients by [N]ame or [R]oom/Bed? Room/bed// <ENTER>

Print how many days MAR? 7// <ENTER>

Select how many BCMA Medication Log history: 1// <ENTER>

DEVICE: HOME// DEC Windows <ENTER>

MAR Ran: Jan 28, 2013@09:10:52 Inpatient Pharmacy Orders (Backup) Page: 1
PATIENT1,TEST SSN: 000000001 DOB: Sep 17, 1920 Sex: M
Ward: C MEDICINE Room: 320 Bed: 1
This record last updated: Mar 02, 2012@10:08:57
No allergies reported to the Contingency

No Active Medication Orders were reported to the Contingency at the time the MAR was printed

MAR Ran: Jan 28, 2013@09:10:52 Inpatient Pharmacy Orders (Backup) Page: 1
PATIENT2,TEST SSN: 000000002 DOB: Jan 01, 1920 Sex: M
Ward: C MEDICINE Room: 320 Bed: 2
This record last updated: Jan 22, 2013@15:35:08
No allergies reported to the Contingency
```

Location Start	Stop	Admin Times	01/28	01/29	01/30	01/31	02/01	02/02	02/03

INPATIENT									
Jan 22, 2013@15:34	Feb 21, 2013@18:00	0900							
<<BUSULFAN TAB>>									
<<HAZ HANDLE>> <<HAZ DISPOSE>>									
Give: 2MG ORAL (BY MOUTH)									
Provider: BCMAPROVIDER, ONE									
RPh/Entry by: BCMAPHARMACIST, ONE									
Order #: 3U	Type: UNIT DOSE								
Status: finished/verified by pharmacist(active)									
BCMA MEDICATION LOG HISTORY									
No Medication Log entries are on file for this order.									

Location Start	Stop	Admin Times	01/28	01/29	01/30	01/31	02/01	02/02	02/03

INPATIENT					*****	*****	*****	*****	*****
Jan 27, 2013@09:00	Jan 29, 2013@24:00	2100			*****	*****	*****	*****	*****
<<NICOTINE 11MG/24HRS PATCH>>									
Give: ONE PATCH TRANSDERMAL Q12H									
Provider: BCMAPROVIDER, ONE									
RPh/Entry by: BCMAPHARMACIST, ONE									
Order #: 14U	Type: UNIT DOSE	0900			*****	*****	*****	*****	*****
Status: finished/verified by pharmacist(active)									
BCMA MEDICATION LOG HISTORY									

Log Date	Message	Log Entry Person								
07/27/16@21:03	GIVEN	BCMANURSE,ONE								
MAR Ran: Jan 28, 2013@09:10:52 Inpatient Pharmacy Orders (Backup)			Page: 1							
PATIENT3,TEST SSN: 000000003 DOB: Jan 01, 1930 Sex: F										
Ward: C MEDICINE Room: 321 Bed: 1										
This record last updated: Jan 18, 2013@11:54:28										
No allergies reported to the Contingency										
Location			Admin							
Start			Times	01/28	01/29	01/30	01/31	02/01	02/02	02/03

INPATIENT										
Jan 18, 2013@11:51 Feb 17, 2013@18:00			0600							
<<ALLOPURINOL 50MG (1/2 X 100MG) TAB>>			1200							
Give: 150mg ORAL (BY MOUTH) Q6H			1800							
Provider: BCMAPROVIDER, ONE			2400							
RPh/Entry by: BCMAPHARMACIST, ONE										
Order #: 17U Type: UNIT DOSE										
Status: finished/verified by pharmacist (active)										
BCMA MEDICATION LOG HISTORY										
No Medication Log entries are on file for this order.										

MAR Ran: Jan 28, 2013@09:10:52 Inpatient Pharmacy Orders (Backup)			Page: 1							
PATIENT4,TEST SSN: 000000004 DOB: Apr 23, 1966 Sex: M										
Ward: C MEDICINE Room: 321 Bed: 2										
This record last updated: Oct 23, 2012@13:34:56										
Allergies: HALOTHANE; MALT BARLEY; PALMOLIVE SOAP; WATERMELONS; KELP; OLEPTRO; SARDINES;										
MALTOSE; NICOTINAMIDE HYDRIODIDE/P; POLLEN; NAMENDA TITRATION PAK;										
PINE NEEDLES; PINE PRODUCTS; IBUPROFEN/PSEUDOEPHEDRINE; TALBUTAL;										
FARBITAL (NEW FORMULA); CARBONATED BEVERAGES; METHYLCELLULOSE;										
CADEXOMER IODINE; ALUMINUM ACETATE/BENZETHO; HALAZEPAM;										
ADR ALUMINUM HYDROXIDE/ASPIRI										
No Active Medication Orders were reported to the Contingency at the time the MAR was printed										

Print MAR for Selected Patient

```

Select BCMA Backup System (Wrkstn) Option: PP Print MAR for Selected Patient

Inpatient Pharmacy Orders for a selected patient
Select PATIENT NAME: TESTPATIENT,ANOTHER <ENTER>

Report [A]LL or [C]URRENT orders? CURRENT// <ENTER>

Print how many days MAR? 7// <ENTER>

Select how many BCMA Medication Log history: 1// <ENTER>

DEVICE: HOME// DEC Windows <ENTER>

MAR Ran: Jan 28, 2013@09:25:40 Inpatient Pharmacy Orders (Backup) Page: 1
TESTPATIENT,ANOTHER SSN: 000000006 DOB: May 04, 1960 Sex: M
Ward: C MEDICINE Room: 100 Bed: A
This record last updated: Jul 30, 2012@13:47:23
No allergies reported to the Contingency

No Active Medication Orders were reported to the Contingency at the time the MAR was printed

Select BCMA Backup System (Wrkstn) <TEST ACCOUNT> Option: PP Print MAR for Selected Patient

Inpatient Pharmacy Orders for a selected patient
Select PATIENT NAME: TESTPATIENT,ANOTHER <ENTER>

Report [A]LL or [C]URRENT orders? CURRENT// ALL <ENTER>

Print how many days MAR? 7// <ENTER>

Select how many BCMA Medication Log history: 1// <ENTER>

DEVICE: HOME// DEC Windows <ENTER>

MAR Ran: Jan 28, 2013@09:31:05 Inpatient Pharmacy Orders (Backup) Page: 1
TESTPATIENT,ANOTHER SSN: 000000006 DOB: Apr 04, 1960 Sex: M
Ward: Room: 100 Bed: A
This record last updated: Oct 23, 2012@13:34:57
No allergies reported to the Contingency

Location
Start Stop Times Admin 01/28 01/29 01/30 01/31 02/01 02/02 02/03
-----
INPATIENT
Not on file Not on file | *****|*****|*****|*****|*****|*****|*****|*****|
<<ALDESLEUKIN 22 MU/VIAL INJ>> | *****|*****|*****|*****|*****|*****|*****|*****|
Give: 22MILLION UNIT/1VIL IV PIGGYBACK Q5H | *****|*****|*****|*****|*****|*****|*****|*****|
Provider: BCMAPROVIDER, ONE | *****|*****|*****|*****|*****|*****|*****|*****|
RPh/Entry by: BCMAPHARMACIST, ONE | *****|*****|*****|*****|*****|*****|*****|*****|
Order #: 257468P Type: PENDING | *****|*****|*****|*****|*****|*****|*****|*****|
Status: pending | *****|*****|*****|*****|*****|*****|*****|*****|
BCMA MEDICATION LOG HISTORY | *****|*****|*****|*****|*****|*****|*****|*****|
No Medication Log entries are on file for this order.
CAUTION! THIS IS A PENDING ORDER :: CHECK WITH PROVIDER OR PHARMACIST!
-----

Location Admin
Start Stop Times 01/28 01/29 01/30 01/31 02/01 02/02 02/03
-----
INPATIENT
Jul 17, 2012@10:40 Jul 17, 2012@15:00 | 1200 |*****|*****|*****|*****|*****|*****|*****|
<<FLUOROURACIL>> | 1500 |*****|*****|*****|*****|*****|*****|*****|
<<HAZ Handle>> <<HAZ Dispose>>

Additive(s): <<FLUOROURACIL BOTTLE: A 10MG>>
Solution(s): <<DEXTRROSE 50% INJ 1000ML>>
Give: IV PIGGYBACK BID S INFUSE OVER 60 Minutes
Provider: BCMAPROVIDER, ONE
RPh/Entry by: BCMAPHARMACIST, ONE
Order #: 1V Type: IV
Status: expired
BCMA MEDICATION LOG HISTORY
No Medication Log entries are on file for this order.
Special Instructions:
TEST
-----

```

Print MAR for Selected Ward

Select BCMA Backup System (Wrkstn) Option: PW Print MAR for Selected Ward
 Inpatient Pharmacy Orders for a selected ward
 Select WARD: C MED C MEDICINE

Report [A]LL or [C]URRENT orders? CURRENT// <ENTER>

Include Patients Without Active Medications? YES// <ENTER>

Sort Patients by [N]ame or [R]oom/Bed? Room/bed// Name <ENTER>

Print how many days MAR? 7// <ENTER>

Select how many BCMA Medication Log history: 1// <ENTER>

DEVICE: HOME// DEC Windows <ENTER>

MAR Ran: Jan 28, 2013@09:10:52 Inpatient Pharmacy Orders (Backup) Page: 1
 PATIENT1,TEST SSN: 000000001 DOB: Sep 17, 1950 Sex: M
 Ward: C MEDICINE Room: 320 Bed: 1
 This record last updated: Mar 02, 2012@10:08:57
 No allergies reported to the Contingency
 No Active Medication Orders were reported to the Contingency at the time the MAR was printed

MAR Ran: Jan 28, 2013@09:10:52 Inpatient Pharmacy Orders (Backup) Page: 1
 PATIENT2,TEST SSN: 000000002 DOB: Jan 01, 1920 Sex: M
 Ward: C MEDICINE Room: 320 Bed: 2
 This record last updated: Jan 22, 2013@15:35:08
 No allergies reported to the Contingency

Location	Start	Stop	Times	Admin	01/28	01/29	01/30	01/31	02/01	02/02	02/03
INPATIENT	Jan 22, 2013@15:34	Feb 21, 2013@18:00	0900								

<<ASPIRIN 325MG BUFFERED TAB>>
 Give: 325MG ORAL (BY MOUTH) QD-(EVERY DAY)%0900
 Provider: BCMAPROVIDER, ONE
 RPh/Entry by: BCMAPHARMACIST, ONE
 Order #: 3U Type: UNIT DOSE
 Status: finished/verified by pharmacist(active)
 BCMA MEDICATION LOG HISTORY
 No Medication Log entries are on file for this order.

MAR Ran: Jan 28, 2013@09:10:52 Inpatient Pharmacy Orders (Backup) Page: 1
 PATIENT3,TEST SSN: 000000003 DOB: Jan 01, 1930 Sex: F
 Ward: C MEDICINE Room: 321 Bed: 1
 This record last updated: Jan 18, 2013@11:54:28
 No allergies reported to the Contingency

Location	Start	Stop	Times	Admin	01/28	01/29	01/30	01/31	02/01	02/02	02/03
INPATIENT	Jan 18, 2013@11:51	Feb 17, 2013@18:00	0600								

<<ALLOPURINOL 50MG (1/2 X 100MG) TAB>>
 Give: 150mg ORAL (BY MOUTH) Q6H
 Provider: BCMAPROVIDER, ONE
 RPh/Entry by: BCMAPHARMACIST, ONE
 Order #: 17U Type: UNIT DOSE
 Status: finished/verified by pharmacist(active)
 BCMA MEDICATION LOG HISTORY
 No Medication Log entries are on file for this order.

MAR Ran: Jan 28, 2013@09:10:52 Inpatient Pharmacy Orders (Backup) Page: 1
 PATIENT4,TEST SSN: 000000004 DOB: Apr 23, 1966 Sex: M
 Ward: C MEDICINE Room: 321 Bed: 2
 This record last updated: Oct 23, 2012@13:34:56
 Allergies: HALOTHANE; MALT BARLEY; PALMOLIVE SOAP; WATERMELONS; KELP; OLEPTRO; SARDINES;
 MALTOSE; NICOTINAMIDE HYDRIODIDE/P; POLLEN; NAMENDA TITRATION PAK;
 PINE NEEDLES; PINE PRODUCTS; IBUPROFEN/PSEUDOEPHEDRINE; TALBUTAL;
 FARBITAL (NEW FORMULA); CARBONATED BEVERAGES; METHYLCELLULOSE;
 CADEXOMER IODINE; ALUMINUM ACETATE/BENZETHO; HALAZEPAM;
 ADR ALUMINUM HYDROXIDE/ASPIRI

No Active Medication Orders were reported to the Contingency at the time the MAR was printed

Print MAR for All Clinics

Select BCMA Backup System (Wrkstn) Option: PAC <ENTER> Print MAR for All Clinics

Report [A]LL or [C]URRENT orders? CURRENT// <ENTER>
 Include a Patient's Inpatient Medications on the Clinic report? YES// <ENTER>
 Print how many days MAR? 7// <ENTER>
 Select how many BCMA Medication Log history: 1// <ENTER>

MAR Ran: Mar 05, 2013@11:11:05 Inpatient Pharmacy Orders (Backup) Page: 1
 BCMACO,ELEVEN SSN: 666001111 DOB: Mar 10, 1900 Sex: M
 Ward: Room: Bed:

This record last updated: Mar 01, 2013@00:16:06

Allergies: LATEX STRAP

Location	Start	Stop	Admin Times	03/05	03/06	03/07	03/08	03/09	03/10	03/11
INPATIENT	Feb 25, 2013@19:26	Mar 17, 2013@24:00	0100							
<<BACLOFEN 10MG TABS>> Give: 10 MG ORAL (BY MOUTH) BID-AM Provider: BCMAPROVIDER,ONE RPh/Entry by: BCMAPHARMACIST,TWO Order #: 13U Type: UNIT DOSE Status: finished/verified by pharmacist(active) BCMA MEDICATION LOG HISTORY No Medication Log entries are on file for this order.										

Location	Start	Stop	Admin Times	03/05	03/06	03/07	03/08	03/09	03/10	03/11
AL-CLINIC MED SOUTH	Mar 01, 2013@00:16	Mar 21, 2013@23:00	0100 0500 0900							
<<ACETAMINOPHEN 325MG C.T.>> Give: 325 MG ORAL (BY MOUTH) Q4H Provider: BCMAPROVIDER,ONE RPh/Entry by: BCMAPHARMACIST,TWO Order #: 48U Type: UNIT DOSE Status: finished/verified by pharmacist(active) BCMA MEDICATION LOG HISTORY No Medication Log entries are on file for this order. Special Instructions: Test special instructions to show that they can extend out 80 characters before Wrapping to next line. Print as was typed and saved by Pharmacy.										

Location	Start	Stop	Admin Times	03/05	03/06	03/07	03/08	03/09	03/10	03/11
AL-CLINIC MED SOUTH	Feb 25, 2013@14:23	May 07, 2013@24:00	0100 0500 0900							
<<ASPIRIN BUFFERED 325MG TAB>> Give: 325MG ORAL (BY MOUTH) Q4H Provider: BCMAPROVIDER,ONE RPh/Entry by: BCMAPHARMACIST,TWO Order #: 11U Type: UNIT DOSE Status: finished/verified by pharmacist(active) BCMA MEDICATION LOG HISTORY No Medication Log entries are on file for this order.										

Location	Start	Stop	Admin Times	03/05	03/06	03/07	03/08	03/09	03/10	03/11
AL-CLINIC MED SOUTH	Feb 25, 2013@14:26	May 07, 2013@24:00	0100							
<<OXYTOCIN 10 UNIT INJ>> <<HAZ Handle>> Give: 10 UNIT INJ TID Provider: BCMAPROVIDER,ONE RPh/Entry by: BCMAPHARMACIST,TWO Order #: 13U Type: UNIT DOSE Status: finished/verified by pharmacist(active) BCMA MEDICATION LOG HISTORY No Medication Log entries are on file for this order.										

MAR Ran: Mar 05, 2013@11:11:05 Inpatient Pharmacy Orders (Backup) Page: 2
 BCMACO,SEVEN SSN: 666007777 DOB: Sep 22, 1900 Sex: M
 Ward: 7A GEN MED Room: "" Bed: ""
 This record last updated: Feb 22, 2013@11:34:47

Location	Start	Stop	Admin Times	03/05	03/06	03/07	03/08	03/09	03/10	03/11
AL-CLINIC MED SOUTH	Feb 20, 2013@09:11	Mar 31, 2013@24:00	0400 0600 0800							
<<ACETAMINOPHEN 325MG C.T.>> Give: 325 MG ORAL (BY MOUTH) Q2H Provider: BCMAPROVIDER,ONE RPh/Entry by: BCMAPHARMACIST,TWO Order #: 14U Type: UNIT DOSE Status: finished/verified by pharmacist(active) BCMA MEDICATION LOG HISTORY No Medication Log entries are on file for this order.										

MAR Ran: Mar 05, 2013@11:11:05 Inpatient Pharmacy Orders (Backup) Page: 1
 BCMACO,TWELVE SSN: 666001212 DOB: Apr 16, 1900 Sex: F
 Ward: Room: Bed:

This record last updated: Mar 01, 2013@18:02:35
 Allergies: LATEX STRAP

Location	Start	Stop	Admin Times	03/05	03/06	03/07	03/08	03/09	03/10	03/11
AL-DERM			0200							
Mar 01, 2013@18:00		Mar 15, 2013@24:00	0700							
<<UREA WITH HC 1% CREAM 30GM>>			1200							
Give: SMALL AMOUNT TOPICAL 5XD			1700							
Provider: BCMAPROVIDER,TWO			2200							
RPh/Entry by: BCMAPHARMACIST,ONE										
Order #: 3U										
Type: UNIT DOSE										
Status: finished/verified by pharmacist(active)										
BCMA MEDICATION LOG HISTORY										
Log Date	Message	Log Entry Person								
03/01/13@18:02	GIVEN	BCMAPHARMACIST,ONE								

Location	Start	Stop	Admin Times	03/05	03/06	03/07	03/08	03/09	03/10	03/11
AL-DERM			0200							
Mar 01, 2013@22:00		Mar 15, 2013@24:00	0600							
<<HYDROXYZINE 10MG TAB>>			1000							
Give: 20 MG ORAL (BY MOUTH) Q4HPRN			1400							
Provider: BCMAPROVIDER,TWO			1800							
RPh/Entry by: BCMAPHARMACIST,ONE			2200							
Order #: 4U										
Type: UNIT DOSE										
Status: finished/verified by pharmacist(active)										
BCMA MEDICATION LOG HISTORY										
No Medication Log entries are on file for this order.										

Print MAR for Selected Clinic

Select BCMA Backup System (Wrkstn) Option: PC <ENTER> Print MAR for Selected Clinic
 Inpatient Pharmacy Orders for a selected Clinic
 Select CLINIC: SY-CLINIC <ENTER> SY-CLINIC NORTH
 Report [A]LL or [C]URRENT orders? CURRENT// <ENTER>
 Include a Patient's Inpatient Medications on the Clinic report? YES// NO <ENTER>
 Print how many days MAR? 7// 3 <ENTER>
 Select how many BCMA Medication Log history: 1// <ENTER>

MAR Ran: Mar 05, 2013@09:00:29 Inpatient Pharmacy Orders (Backup) Page: 1
 BCMACO,ELEVEN SSN: 666001111 DOB: Mar 10, 1900 Sex: M
 Ward: Room: Bed:

This record last updated: Mar 01, 2013@00:16:06
 Allergies: LATEX STRAP

Location	Start	Stop	Admin Times	03/05	03/06	03/07	Notes
SY-CLINIC NORTH			0100				
Feb 27, 2013@10:02		Mar 09, 2013@24:00	0500				
<<THIORIDAZINE 30MG/ML CONC.>>			0900				
Give: 10 MG ORAL (BY MOUTH) Q4H			1300				
Provider: BCMAPROVIDER,TWO			1700				
RPh/Entry by: BCMAPROVIDER,ONE			2100				
Order #: 47U							
Type: UNIT DOSE							
Status: finished/verified by pharmacist(active)							
BCMA MEDICATION LOG HISTORY							
No Medication Log entries are on file for this order.							
Special Instructions:							
tst							

Location	Start	Stop	Admin Times	03/05	03/06	03/07	Notes
SY-CLINIC NORTH			0900				
Jan 03, 2013@10:06		Jun 30, 2013@11:11	2100				
<<CHLORAL HYDRATE 500MG CAP>>							
Give: 500 MG ORAL (BY MOUTH) Q12H							
Provider: BCMAPROVIDER,ONE							
RPh/Entry by: BCMAPHARMACIST,TWO							
Order #: 29U							
Type: UNIT DOSE							
Status: finished/verified by pharmacist(active)							
BCMA MEDICATION LOG HISTORY							
No Medication Log entries are on file for this order.							

Location	Start	Stop	Admin Times	03/05	03/06	03/07	Notes
SY-CLINIC NORTH			0900				
Jan 03, 2013@10:05	Jun 30, 2013@11:11		2100				<<LIDOCAINE JELLY 2% >>
Give: 1 DOSE TOPICAL Q12H							
Provider: BCMAPROVIDER,ONE							
RPh/Entry by: BCMAPHARMACIST,TWO							
Order #: 30U Type: UNIT DOSE							
Status: finished/verified by pharmacist(active)							
BCMA MEDICATION LOG HISTORY							
No Medication Log entries are on file for this order.							

MAR Ran: Mar 05, 2013@09:00:29 Inpatient Pharmacy Orders (Backup) Page: 2
 BCMACOIM,ELEVEN SSN: 000009011 DOB: Mar 10, 1900 Sex: M
 Ward: 7A GEN MED Room: 726 Bed: B
 This record last updated: Mar 01, 2013@16:41:56
 Allergies: STRAWBERRIES

Location	Start	Stop	Admin Times	03/05	03/06	03/07	Notes
SY-CLINIC NORTH			0300				
Jan 03, 2013@10:06	Jun 24, 2013@12:00		0900				
<<LORAZEPAM 1MG TAB>>							
Give: 2 MG ORAL (BY MOUTH) Q6H							
Provider: BCMAPROVIDER,ONE							
RPh/Entry by: BCMAPHARMACIST,TWO							
Order #: 23U Type: UNIT DOSE							
Status: finished/verified by pharmacist(active)							
BCMA MEDICATION LOG HISTORY							
Log Date	Message	Log Entry Person					
02/07/13@15:26	GIVEN	WILSON,REMELE					

Location	Start	Stop	Admin Times	03/05	03/06	03/07	Notes
SY-CLINIC NORTH			0500				
Jan 03, 2013@10:07	Jun 24, 2013@12:00		1300				
<<METHADONE 10MG TAB >>							
Give: 20 MG ORAL (BY MOUTH) Q8H							
Provider: BCMAPROVIDER,ONE							
RPh/Entry by: BCMAPHARMACIST,TWO							
Order #: 24U Type: UNIT DOSE							
Status: finished/verified by pharmacist(active)							
BCMA MEDICATION LOG HISTORY							
No Medication Log entries are on file for this order.							

Location	Start	Stop	Admin Times	03/05	03/06	03/07	Notes
SY-CLINIC NORTH			0900				
Jan 03, 2013@10:07	Jun 24, 2013@12:00		2100				
<<METHOTREXATE 2.5MG TAB>>							
Give: 2.5 MG ORAL (BY MOUTH) Q12H							
Provider: BCMAPROVIDER,ONE							
RPh/Entry by: BCMAPHARMACIST,TWO							
Order #: 25U Type: UNIT DOSE							
Status: finished/verified by pharmacist(active)							
BCMA MEDICATION LOG HISTORY							
No Medication Log entries are on file for this order.							

Print Blank MAR for Selected Patient

Blank 3 Day MAR for Selected Patient

```
Select BCMA Backup System (Wrkstn) Option: BL <ENTER> Print Blank Mar for Selected Patient

Inpatient Pharmacy Orders for a selected patient
Select PATIENT NAME: BCMAPATIENT1,ONE <ENTER>

Print how many days MAR? 7// 3 <ENTER>

DEVICE: BCBU// <ENTER>

MAR Ran: Mar 29, 2005@07:49:18 Inpatient Pharmacy Orders (Backup) Page: 1
```


BCMAPATIENT1,ONE SSN: 000000001 DOB: Jul 29, 1915 Sex: M
 Ward: 4 MED Room: M20 Bed: A
 This record last updated: Mar 29, 2005@07:29:43
 Allergies: DYE,CATHETER; DILTIAZEM; SULFA; IBUPROFEN

Order	Start	Stop	Admin Times	MAR			Notes
				29	30	31	

RPH Verify: _____ Nurse Verify: _____							

RPH Verify: _____ Nurse Verify: _____							

RPH Verify: _____ Nurse Verify: _____							

RPH Verify: _____ Nurse Verify: _____							

Blank 7 Day MAR for Selected Patient

```
Select BCMA Backup System (Wrkstn) Option: BL <ENTER> Print Blank Mar for Selected Patient
```

Inpatient Pharmacy Orders for a selected patient
 Select PATIENT NAME: **BCMAPATIENT1, ONE <ENTER>**

Print how many days MAR? 7// <ENTER>

DEVICE: BCBU// <ENTER>

MAR Ran: Mar 29, 2005@07:50:10 Inpatient Pharmacy Orders (Backup) Page: 1
 BCMAPATIENT1, ONE SSN: 000000001 DOB: Jul 29, 1915 Sex: M
 Ward: 4 MED Room: M20 Bed: A
 This record last updated: Mar 29, 2005@07:29:43
 Allergies: DYE, CATHETER; DILTIAZEM; SULFA; IBUPROFEN

Order	Start	Stop	Admin Times	MAR 29	30	31	APR 1	2	3	4	Notes
RPH Verify: _____ Nurse Verify: _____											
RPH Verify: _____ Nurse Verify: _____											
RPH Verify: _____ Nurse Verify: _____											
RPH Verify: _____ Nurse Verify: _____											

List of Wards in BCMA Backup File

```
Select BCMA Backup System (Wrkstn) Option: WL <ENTER> List of Wards in BCMA Backup File
Wards with BCMA Backup Data on this workstation:
```

- 10W
- 2B APCU
- 3E GEM
- 3E SUBACUTE
- 3W GS
- 3W ORTHO
- 4 MED
- 4 SURG
- 4E ENT
- 4E M
- 4E ON
- MICU
- TICU

Trouble Shooting Guide

The messages are building on the VistA side, but I see an open fail in the link monitor.

Check the following areas:

- The IP address on both and make sure they match.
- The Port numbers on both and make sure they match.
- The Firewall on the workstation.
- The Filers on the workstation.
- The Link Manager on the workstation.

When logging into the Cache Terminal on the workstation I get a <FILEFULL> error. When looking at the HL7 System Link Monitor on VistA the BCBU Workstation shows a READ ERROR state.

This may be caused by the BCBU workstation reaching its defined maximum allowed database size. To increase the size of the BCBU workstations database go into the Cache Cube / Control Panel / Local Databases. Right click on VISTA and select properties. If the database has reached the maximum defined the fields # of MB and Max # of MB will be equal. To increase the size edit only the Max # of MB field. (**Note:** Make sure the physical hard drive has enough space available for the increase in the database size)

When logging into the Cache Terminal on the workstation I get a <NOROUTINE> error.

Verify that the two user accounts setup under the Cache Cube / Control Panel / Security / User Accounts are set to VISTA Namespace and ^ZU Routine.

The messages appear to be transmitting but no data is filing on the workstation.

Verify that the HL COMMUNICATION SERVER PARAMETERS field, "DEFAULT PROCESSING ID" is set correctly. This field must match the value of the sending VistA system. In addition, verify that INCOMING and OUTGOING HL7 filers are running on the workstation.

I don't see the message queue increase for my HL7 link when I run the 'Initialize Workstation' option or during activity on the VistA side?

The following two places need to be checked:

Make sure the Link is enabled on the VistA side. *HL7 Main Menu* [HL MAIN MENU] option. Make sure the Workstation Link is associated to the correct division or Default parameter. [PSB BCBU LINK ASSOCIATIONS] option.

I'm able to start TaskMan up with the Taskman_start script, but I notice that the HL7 link

jobs do not start. What could be the problem?

Linux requires root privs to start listener jobs on TCPIP ports. TaskMan needs to be started by the root user so its submanagers (which start the listener) can have those privs as well. To do this, login as the BCMA Manager the issue the command "su -m" and enter the root password. Once you're logged in as root, start TaskMan by issuing the command "./taskman_start". The HL7 link manager and the listener link should start automatically. **Note:** Netmail startup has root requirements as well.

Running the netmail_start script does not start netmail. What could be the problem?

Linux requires root privs to start listener jobs on TCPIP ports. To start up the network mail listener job, log in as the BCMA Manager, then issue the command "su -m" and enter the root password. Once you're logged in as root, start network mail by issuing the command "./netmail_start". **Note:** HL7 links have root requirements as well.

How can I verify the TCPIP listening jobs on Linux?

As root, issue the "netstat -tln" command. This will provide information similar to the following:

Proto	Recv-Q	Send-Q	Local Address	Foreign Address	State	PID/Program name
tcp	0	0	*:32768	*:*	LISTEN	523/rpc.statd
tcp	0	0	BCMA.med.va.gov:32769	*:*	LISTEN	628/xinetd
tcp	0	0	*:printer	*:*	LISTEN	658/lpd Waiting
tcp	0	0	*:sunrpc	*:*	LISTEN	504/portmap
tcp	0	0	*:10000	*:*	LISTEN	1174/mumps
tcp	0	0	*:5904	*:*	LISTEN	13884/Xvnc
tcp	0	0	*:x11	*:*	LISTEN	813/X
tcp	0	0	*:ftp	*:*	LISTEN	628/xinetd
tcp	0	0	*:ssh	*:*	LISTEN	614/sshd
tcp	0	0	*:telnet	*:*	LISTEN	628/xinetd
tcp	0	0	*:smtp	*:*	LISTEN	1390/mumps

Ports of primary interest are 10000 (HL7 listener link) and SMTP (port 25-netmail).

To see the numeric ports for common TCPIP protocols, issue the "netstat -tln - numeric" command.

What is the best way to shut GT.M down?

\$HOME of the BCMA manager account contains the script zgstop. This script is customized to shut down the BCMA configuration cleanly and run the GT.M database down (to ensure database integrity). To use this script properly, it must be run as root (the BCMA manager will not be able to shutdown HL7 link, netmail, and TaskMan jobs started as root - this will prevent the database to rundown properly). To do this, login as the BCMA manager then issue the command "su -m" and enter the root password. Once you're logged in as root, issue the command './zgstop'.

How do I start GT.M up?

There is no single GT.M daemon. This means that each GT.M process 'starts' GT.M for itself. GT.M processes (TaskMan, netmail, HL7 jobs) should start automatically with a system reboot provided the /etc/init.d/gtm script was enabled when BCMA was installed using the install_bcma

script.

From within GT.M, how can I view system status (like when I D ^%SS in Cache)?

GT.M does not provide a utility of its own to provide this functionality. However, SD&D have provided the ^ZSY routine to accomplish this. As with other BCMA tasks, it is best to run this as the root user; otherwise, not all process information will be accessible. To do this, login as the BCMA manager, then issue the command "su -m" and enter the root password. Drop into GT.M, issue the ZSY command as follows, and select the type of display desired.

GTM>D ^ZSY

1 pid

2 cpu time

3 image/pid

4 image/cpu

1// 1

INTRPT issued to process 1409
INTRPT issued to process 1148
INTRPT issued to process 1390
INTRPT issued to process 1315
INTRPT issued to process 1307
INTRPT issued to process 1295
INTRPT issued to process 1291
INTRPT issued to process 1239
INTRPT issued to process 1229
INTRPT issued to process 1225
INTRPT issued to process 1222
INTRPT issued to process 1216
INTRPT issued to process 1213
INTRPT issued to process 1189
INTRPT issued to process 1179
INTRPT issued to process 1177
INTRPT issued to process 1174
INTRPT issued to process 1157
INTRPT issued to process 1145

System Status for GT/M

```
GT.M Mumps users on 18-Mar-03 11:11:10
```

Proc. id	Proc. name	PS	Terminal	Routine	Mode	CPU time
1145	TaskMan VISTA 1	S	?	IDLE+1^%ZTM	-direct	
1148		S	pts/2		-direct	
1157	HLmgr:538	S	?	LOOP+3^HLCSLM	-direct	
1174	HLsrv:182	S	?		-direct	
1177		S	?	SUB+1^%ZTMS1	-direct	
1179	BTASK 546	S	?	STARTIN+17^HLCSIN	-direct	
1189	BTASK 545	S	?	STARTIN+17^HLCSIN	-direct	
1213	BTASK 547	S	?	STARTOUT+16^HLCSOUT	-direct	
1216	BTASK 548	S	?	STARTOUT+16^HLCSOUT	-direct	
1222	BTASK 550	S	?	STARTIN+17^HLCSIN	-direct	

1225	BTask 551	S	?	STARTIN+17^HLCSIN	-direct
1229	BTask 552	S	?	STARTOUT+16^HLCSOUT	-direct
1239	BTask 553	S	?	STARTOUT+16^HLCSOUT	-direct
1291	Sub 1291	S	?	GETTASK+3^%ZTMS1	-direct
1295	Sub 1295	S	?	SUB+1^%ZTMS1	-direct
1307	Sub 1307	S	?	GETTASK+3^%ZTMS1	-direct
1315	Sub 1315	S	?	SUB+1^%ZTMS1	-direct
1390		S	?		-direct
1409		S	pts/3	jobset+4^ZSY	-direct

I'm getting <RECOMPILE> errors when working on the Caché system.

If you are getting this error, the routines need to be recompiled on the workstation. There are two different methods you can use to accomplish this:

CHUI

1. Get to the programmer prompt on the workstation.
2. D ^%RCOMPIL
3. At the routine selection prompt, select %*, press **Enter**.
4. Repeat the D ^%RCOMPIL command and select * at the routine selection prompt.

GUI

1. Right-click on the Cache cube and select Explorer.
2. On the left side of the screen expand VistA under the Local Databases, select routines.
3. In the routine selection box, enter %*
4. From the Edit menu, click on Select All.
5. In the Contents screen on the right, right-click, then click Advanced/Compile.
6. Repeat steps 3-5, selecting * in the routine selection.